

# PINK LADY

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 11/8/2023 Revision date: 11/8/2023 Supersedes version of: 2/21/2022 Version: 2.0

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture
Trade name : PINK LADY

UFI : JRKH-A2RD-Q009-6010
Product code : Parf\_Pink\_Lady
Type of product : Perfumes, fragrances
Product group : Trade product

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

# 1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use

Industrial/Professional use spec : Industrial

For professional use only Perfumes, fragrances

Use of the substance/mixture : Perfumes, frag Function or use category : Odour agents

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

BAKED GAMES SRL ROMANIA, BUCHAREST, SECTOR 4 +40771326626

contact@kitlumanari.ro | www.kitlumanari.ro

## 1.4. Emergency telephone number

Emergency number : 1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731;

Brazil: +0-800-591-6042; India: +000-800-100-4086

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

# Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitisation, Category 1 H317 Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

# Adverse physicochemical, human health and environmental effects

Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. May cause an allergic skin reaction.

# 2.2. Label elements

# Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

Signal word (CLP) : Warning

Contains : Grapefruit oil; Linalool; Melonal; Geraniol; Nerol; Anisic alcohol; Anisyl acetate; Cyclamal;

Aldehyde C-16

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP) : H317 - May cause an allergic skin reaction.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P321 - Specific treatment (see supplemental first aid instruction on this label).

Extra phrases : For professional users only.

### 2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

## 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Dimyrcetol	CAS-No.: 25279-09-8 EC-No.: 246-788-1	3.075 – 6.15	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Grapefruit oil	CAS-No.: 8016-20-4 EC-No.: 600-007-4	1.85 – 3.7	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Resin acids and Rosin acids, hydrogenated, methyl esters	CAS-No.: 8050-15-5 EC-No.: 232-476-2	1.75 – 3.5	Aquatic Chronic 3, H412
hexan-1-ol substance with national workplace exposure limit(s) (DE, RO, SI)	CAS-No.: 111-27-3 EC-No.: 203-852-3 EC Index-No.: 603-059-00-6 REACH-no: 01-2119487967- 12	0.45 – 0.9	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Eye Irrit. 2, H319
Linalool	CAS-No.: 78-70-6 EC-No.: 201-134-4 EC Index-No.: 603-235-00-2 REACH-no: 01-2119474016-	0.45 – 0.9	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
isobutyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH)	CAS-No.: 110-19-0 EC-No.: 203-745-1 EC Index-No.: 607-026-00-7	0.425 – 0.85	Flam. Liq. 2, H225 STOT SE 3, H336
Melonal	CAS-No.: 106-72-9 EC-No.: 203-427-2	0.3 – 0.6	Skin Sens. 1B, H317

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Anisic alcohol	CAS-No.: 105-13-5 EC-No.: 203-273-6 REACH-no: 01-2119934494- 33	0.25 – 0.5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Skin Sens. 1, H317
	CAS-No.: 104-21-2 EC-No.: 203-185-8	0.225 – 0.45	Skin Sens. 1, H317
Geraniol	CAS-No.: 106-24-1 EC-No.: 203-377-1 EC Index-No.: 603-241-00-5 REACH-no: 01-2119552430-	0.165 – 0.33	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317
isopentyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, DE, DK, EE, ES, FI, FR, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, TR); substance with a Community workplace exposure limit	CAS-No.: 123-92-2 EC-No.: 204-662-3 EC Index-No.: 607-130-00-2 REACH-no: 01-2119548408- 32	0.15 – 0.3	Flam. Liq. 3, H226
Cyclamal	CAS-No.: 103-95-7 EC-No.: 203-161-7 REACH-no: 01-2119970582- 32	0.15 – 0.3	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Nerol	CAS-No.: 106-25-2 EC-No.: 203-378-7	0.11 – 0.22	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Allyl heptanoate	CAS-No.: 142-19-8 EC-No.: 205-527-1 REACH-no: 01-2119488961- 23	0.1 – 0.2	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Allyl caproate	CAS-No.: 123-68-2 EC-No.: 204-642-4 REACH-no: 01-2119983573- 26	0.075 – 0.15	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Aldehyde C-16	CAS-No.: 77-83-8 EC-No.: 201-061-8 REACH-no: 01-2119967770- 28	0.05 – 0.1	Skin Sens. 1B, H317 Aquatic Chronic 2, H411

Full text of H- and EUH-statements: see section 16

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash

occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : May cause an allergic skin reaction.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing

dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

# 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

# 6.4. Reference to other sections

For further information refer to section 13.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Avoid

contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

Storage temperature : 25 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Store in a closed container.

11/8/2023 (Revision date) EN (English) 4/22

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Packaging materials : Do not store in corrodable metal.

# 7.3. Specific end use(s)

No additional information available

# SECTION 8: Exposure controls/personal protection

# 8.1. Control parameters

# 8.1.1 National occupational exposure and biological limit values

hexan-1-ol (111-27-3)		
Germany - Occupational Exposure Limits (TRGS 900)		
AGW (OEL TWA) [1]	105 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed (long-chain Alcohols)	
AGW (OEL TWA) [2]	25 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed (long-chain Alcohols)	
Romania - Occupational Exposure Limits		
OEL TWA	150 mg/m³	
OEL TWA	36 ppm	
OEL STEL	250 mg/m³	
OEL STEL	60 ppm	
Slovenia - Occupational Exposure Limits		
OEL TWA	210 mg/m³	
OEL TWA	50 ppm	
OEL STEL	210 mg/m³	
OEL STEL	50 ppm	
isobutyl acetate (110-19-0)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	241 mg/m³ (Butyl acetates)	
MAK (OEL TWA) [ppm]	50 ppm (Butyl acetates)	
MAK (OEL STEL)	480 mg/m³ (Butyl acetate)	
MAK (OEL STEL) [ppm]	100 ppm (Butyl acetate)	
Belgium - Occupational Exposure Limits		
OEL TWA	238 mg/m³	
OEL TWA	50 ppm	
OEL STEL	712 mg/m³	
OEL STEL	150 ppm	
Bulgaria - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA	50 ppm	
OEL TWA		
OEL STEL	723 mg/m³	

isobutyl acetate (110-19-0)			
Croatia - Occupational Exposure Limits			
GVI (OEL TWA) [1]	241 mg/m³		
GVI (OEL TWA) [2]	50 ppm		
KGVI (OEL STEL)	723 mg/m³		
KGVI (OEL STEL) [ppm]	150 ppm		
Cyprus - Occupational Exposure Limits			
OEL TWA	241 mg/m³		
OEL TWA	50 ppm		
OEL STEL	723 mg/m³		
OEL STEL	150 ppm		
Czech Republic - Occupational Exposure Limits			
PEL (OEL TWA)	241 mg/m³		
Denmark - Occupational Exposure Limits			
OEL TWA [1]	241 mg/m³ (Butyl acetate, all isomers)		
OEL TWA [2]	50 ppm (Butyl acetate, all isomers)		
OEL STEL	723 mg/m³		
OEL STEL	150 ppm		
Estonia - Occupational Exposure Limits			
OEL TWA	241 mg/m³		
OEL TWA	50 ppm		
OEL STEL	723 mg/m³		
OEL STEL	150 ppm		
Finland - Occupational Exposure Limits			
HTP (OEL TWA) [1]	240 mg/m³ (Butyl acetate)		
HTP (OEL TWA) [2]	50 ppm (Butyl acetate)		
HTP (OEL STEL)	725 mg/m³ (Butyl acetate)		
HTP (OEL STEL) [ppm]	150 ppm (Butyl acetate)		
France - Occupational Exposure Limits			
VME (OEL TWA)	241 mg/m³ (restrictive limit)		
VME (OEL TWA) [ppm]	50 ppm (restrictive limit)		
VLE (OEL C/STEL)	723 mg/m³ (restrictive limit)		
VLE (OEL C/STEL) [ppm]	150 ppm (restrictive limit)		
Germany - Occupational Exposure Limits (TRGS 90	Germany - Occupational Exposure Limits (TRGS 900)		
AGW (OEL TWA) [1]	300 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)		
AGW (OEL TWA) [2]	62 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)		
Greece - Occupational Exposure Limits			
OEL TWA	241 mg/m³		
OEL TWA	50 ppm		

isobutyl acetate (110-19-0)		
OEL STEL	723 mg/m³	
OEL STEL	150 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	241 mg/m³	
CK (OEL STEL)	723 mg/m³	
OEL chemical category	Sensitizer	
Ireland - Occupational Exposure Limits		
OEL TWA [1]	241 mg/m³	
OEL TWA [2]	50 ppm	
OEL STEL	723 mg/m³ (calculated)	
OEL STEL	150 ppm (calculated)	
Italy - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL	150 ppm	
Latvia - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA	50 ppm	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	241 mg/m³	
IPRV (OEL TWA) [ppm]	50 ppm	
TPRV (OEL STEL)	723 mg/m³	
TPRV (OEL STEL) [ppm]	150 ppm	
Luxembourg - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL	150 ppm	
Malta - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL	150 ppm	
Netherlands - Occupational Exposure Limits		
TGG-8u (OEL TWA)	241 mg/m³	
TGG-8u (OEL TWA) [ppm]	50 ppm	
TOO 45 1 (OS! OTS!)		
TGG-15min (OEL STEL)	723 mg/m³	

isobutyl acetate (110-19-0)		
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	240 mg/m³	
NDSCh (OEL STEL)	720 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	241 mg/m³ (indicative limit value)	
OEL TWA	50 ppm (indicative limit value)	
OEL STEL	723 mg/m³ (indicative limit value)	
OEL STEL	150 ppm (indicative limit value)	
Romania - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL	150 ppm	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA) [1]	480 mg/m³	
NPHV (OEL TWA) [2]	100 ppm	
NPHV (OEL C)	700 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL	150 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	241 mg/m³	
VLA-ED (OEL TWA) [2]	50 ppm	
VLA-EC (OEL STEL)	723 mg/m³	
VLA-EC (OEL STEL) [ppm]	150 ppm	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	241 mg/m³ (Butyl acetates)	
NGV (OEL TWA) [ppm]	50 ppm (Butyl acetates)	
KTV (OEL STEL)	723 mg/m³ (Butyl acetates)	
KTV (OEL STEL) [ppm]	150 ppm (Butyl acetates)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	724 mg/m³	
WEL TWA (OEL TWA) [2]	150 ppm	
WEL STEL (OEL STEL)	903 mg/m³	
WEL STEL (OEL STEL) [ppm]	187 ppm	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA) [1]	241 mg/m³	

Consequent (CRL TWA) [2]   50 ppm	isobutyl acetate (110-19-0)	
Kortidsverdi (DEL STEL)   ppm    150 ppm (value from the regulation)	` '	50 ppm
Sometideserdi (OEL STEL) (ppm]   150 ppm (value from the regulation)		
Switzerland - Occupational Exposure Limits         240 mg/m²           MAK (OEL TWA) [1]         240 mg/m²           MAK (OEL TWA) [2]         50 ppm           KZGW (OEL STEL) [ppm]         150 ppm           USA - ACGIH - Occupational Exposure Limits         ACGIH OEL TWA [ppm]           ACGIH OEL TWA [ppm]         50 ppm (Butyl acetates, all isomers)           ACGIH OEL STEL [ppm]         150 ppm (Butyl acetates, all isomers)           ISSpentyl acetate (123-92-2)         Image: Image acetate (123-92-2)           EU - Indicative Occupational Exposure Limit (IOEL)         IOEL TWA           IOEL TWA [ppm]         50 ppm           IOEL STEL [ppm]         100 ppm           Austria - Occupational Exposure Limits         MAK (OEL TWA)           MAK (OEL TWA) [ppm]         50 ppm (Pentyl acetate (all isomers))           MAK (OEL TWA) [ppm]         50 ppm (Pentyl acetate (all isomers))           MAK (OEL STEL) [ppm]         50 ppm (Pentylacetate)           Belglum - Occupational Exposure Limits         CUL TWA           OEL TWA         270 mg/m²           OEL TWA         50 ppm           OEL STEL         540 mg/m²           OEL STEL         540 mg/m²           OEL TWA         270 mg/m²           OEL TWA         50 ppm           OEL STEL <td></td> <td></td>		
MAK (OEL TWA) [1] 240 mg/m³  MAK (OEL TWA) [2] 50 ppm  KZGW (OEL STEL) 720 mg/m³  KZGW (OEL STEL) 150 ppm  USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 50 ppm (Butyl acetates, all isomers)  ACGIH OEL STEL [ppm] 150 ppm (Butyl acetates, all isomers)  Isopentyl acetate (123-92-2)  EU - Indicative Occupational Exposure Limit (IOEL)  IOEL TWA 20 ppm  IOEL TWA 20 ppm  IOEL STEL 360 mg/m³  IOEL TWA) 100 ppm  Austria - Occupational Exposure Limits  MAK (OEL TWA) 100 ppm  MAK (OEL STEL) 100 ppm  IOEL STEL 360 mg/m³ (Pentyl acetate (all isomers))  MAK (OEL STEL) 100 ppm  IOEL STEL 360 mg/m³ (Pentylacetate)  Belgium - Occupational Exposure Limits  OEL TWA 270 mg/m³  OEL STEL 360 mg	, , , , , , , , , , , , , , , , , , , ,	130 ppm (value from the regulation)
MAK (OEL TWA) [2]         50 ppm           KZGW (OEL STEL)         720 mg/m²           KZGW (OEL STEL) [ppm]         150 ppm           USA - ACGIH - Occupational Exposure Limits         ACGIH OEL TWA [ppm]         50 ppm (Butyl acetates, all isomers)           ACGIH OEL STEL [ppm]         150 ppm (Butyl acetates, all isomers)           Isopentyl acetate (123-92-2)         EU - Indicative Occupational Exposure Limit (IOEL)           IOEL TWA         270 mg/m²           IOEL TWA [ppm]         50 ppm           IOEL STEL         540 mg/m²           OEL STEL [ppm]         100 ppm           Austria - Occupational Exposure Limits         Austria - Occupational Exposure Limits           MAK (OEL TWA)         270 mg/m² (Pentyl acetate (all isomers))           MAK (OEL STEL)         540 mg/m² (Pentylacetate)           MAK (OEL STEL) [ppm]         50 ppm (Pentylacetate)           Belgium - Occupational Exposure Limits         OEL TWA           OEL TWA         270 mg/m²           OEL TWA         50 ppm           OEL STEL         540 mg/m²           OEL TWA         270 mg/m² <td></td> <td>240</td>		240
KZGW (OEL STEL)   720 mg/m²		-
Variety   Vari		
USA - ACGIH - Occupational Exposure Limits         50 ppm (Butyl acetates, all isomers)           ACGIH OEL TWA [ppm]         50 ppm (Butyl acetates, all isomers)           isopontyl acetate (123-92-2)         EU - Indicative Occupational Exposure Limit (IOEL)           IOEL TWA         270 mg/m²           IOEL TWA [ppm]         50 ppm           IOEL STEL         540 mg/m²           IOEL STEL [ppm]         100 ppm           Austria - Occupational Exposure Limits         Austria - Occupational Exposure Limits           MAK (OEL TWA)         270 mg/m² (Pentyl acetate (all isomers))           MAK (OEL STEL)         540 mg/m² (Pentylacetate)           MAK (OEL STEL) [ppm]         100 ppm (Pentylacetate)           Belgium - Occupational Exposure Limits         OEL TWA           OEL TWA         270 mg/m²           OEL TWA         50 ppm           OEL STEL         540 mg/m²           OEL STEL         540 mg/m²           OEL TWA         90 ppm           OEL TWA         90 ppm           OEL TWA         90 ppm           OEL STEL         100 ppm           CH STEL         540 mg/m²           OEL TWA         90 ppm           OEL TWA         90 ppm           OEL TWA         90 ppm	, ,	-
ACGIH OEL TWA [ppm] 50 ppm (Butyl acetates, all isomers)  ACGIH OEL STEL [ppm] 150 ppm (Butyl acetates, all isomers)  isopentyl acetate (123-92-2)  EU - Indicative Occupational Exposure Limit (IOEL)  IOEL TWA [ppm] 50 ppm  IOEL STEL 540 mg/m³  IOEL STEL [ppm] 100 ppm  Austria - Occupational Exposure Limits  MAK (OEL TWA) [ppm] 50 ppm (Pentyl acetate (all isomers))  MAK (OEL TWA) [ppm] 50 ppm (Pentyl acetate (all isomers))  MAK (OEL STEL) 540 mg/m³ (Pentyl acetate)  Belgium - Occupational Exposure Limits  OEL TWA 270 mg/m³ (Pentylacetate)  Belgium - Occupational Exposure Limits  OEL TWA 270 mg/m³  OEL STEL 540 mg/m³  OEL STEL 100 ppm  Bulgaria - Occupational Exposure Limits  OEL TWA 270 mg/m³  OEL STEL 540 mg/m³  OEL STEL 100 ppm  DEL STEL 100 ppm  DEL STEL 100 ppm  OEL STEL 540 mg/m³  OEL STEL 540 mg/m³  OEL STEL 540 mg/m³  OEL TWA 270 mg/m³  OEL STEL 540 mg/m³  OEL STEL 54		150 ppm
ACGIH OEL STEL [ppm]   150 ppm (Butyl acetates, all isomers)		T
Sopentyl acetate (123-92-2)		
EU - Indicative Occupational Exposure Limit (IOEL)   IOEL TWA	ACGIH OEL STEL [ppm]	150 ppm (Butyl acetates, all isomers)
IOEL TWA	isopentyl acetate (123-92-2)	
IOEL TWA [ppm]   50 ppm     IOEL STEL   540 mg/m³     IOEL STEL [ppm]   100 ppm     Austria - Occupational Exposure Limits     MAK (OEL TWA)   270 mg/m³ (Pentyl acetate (all isomers))     MAK (OEL TWA) [ppm]   50 ppm (Pentyl acetate (all isomers))     MAK (OEL STEL)   540 mg/m³ (Pentylacetate)     MAK (OEL STEL) [ppm]   100 ppm (Pentylacetate)     Belgium - Occupational Exposure Limits     OEL TWA   270 mg/m³     OEL TWA   50 ppm     OEL STEL   540 mg/m³     OEL STEL   100 ppm     Bulgaria - Occupational Exposure Limits     OEL TWA   270 mg/m³     OEL TWA   50 ppm     OEL STEL   100 ppm     OEL TWA   50 ppm     OEL TWA   50 ppm     OEL TWA   50 ppm     OEL TWA   50 ppm     OEL STEL   540 mg/m³     OEL STEL   5	EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL STEL	IOEL TWA	270 mg/m³
DEL STEL [ppm]   100 ppm	IOEL TWA [ppm]	50 ppm
Austria - Occupational Exposure Limits           MAK (OEL TWA)         270 mg/m³ (Pentyl acetate (all isomers))           MAK (OEL TWA) [ppm]         50 ppm (Pentyl acetate (all isomers))           MAK (OEL STEL)         540 mg/m³ (Pentylacetate)           MAK (OEL STEL) [ppm]         100 ppm (Pentylacetate)           Belgium - Occupational Exposure Limits         270 mg/m³           OEL TWA         50 ppm           OEL STEL         540 mg/m³           OEL STEL         100 ppm           Bulgaria - Occupational Exposure Limits         270 mg/m³           OEL TWA         50 ppm           OEL STEL         540 mg/m³           OEL STEL         100 ppm           Croatia - Occupational Exposure Limits         GVI (OEL TWA) [1]         270 mg/m³           GVI (OEL TWA) [2]         50 ppm           GVI (OEL TWA) [2]         540 mg/m³           KGVI (OEL STEL) [ppm]         100 ppm           Cyprus - Occupational Exposure Limits         640 mg/m³           Cyprus - Occupational Exposure Limits	IOEL STEL	540 mg/m³
MAK (OEL TWA)       270 mg/m³ (Pentyl acetate (all isomers))         MAK (OEL TWA) [ppm]       50 ppm (Pentyl acetate (all isomers))         MAK (OEL STEL)       540 mg/m³ (Pentylacetate)         MAK (OEL STEL) [ppm]       100 ppm (Pentylacetate)         Belgium - Occupational Exposure Limits       270 mg/m³         OEL TWA       50 ppm         OEL STEL       540 mg/m³         OEL STEL       100 ppm         Bulgaria - Occupational Exposure Limits         OEL TWA       270 mg/m³         OEL TWA       50 ppm         OEL STEL       540 mg/m³         OEL STEL       100 ppm         CFOATIA - Occupational Exposure Limits       100 ppm         CFOATIA - Occupational Exposure Limits       50 ppm         GVI (OEL TWA) [1]       270 mg/m³         GVI (OEL TWA) [2]       50 ppm         KGVI (OEL STEL)       540 mg/m³         KGVI (OEL STEL) [ppm]       100 ppm         Cyprus - Occupational Exposure Limits       100 ppm	IOEL STEL [ppm]	100 ppm
MAK (OEL TWA) [ppm]       50 ppm (Pentyl acetate (all isomers))         MAK (OEL STEL)       540 mg/m³ (Pentylacetate)         MAK (OEL STEL) [ppm]       100 ppm (Pentylacetate)         Belgium - Occupational Exposure Limits       270 mg/m³         OEL TWA       50 ppm         OEL STEL       540 mg/m³         OEL STEL       100 ppm         Bulgaria - Occupational Exposure Limits         OEL TWA       270 mg/m³         OEL TWA       50 ppm         OEL STEL       540 mg/m³         OEL STEL       100 ppm         Croatia - Occupational Exposure Limits       Croatia - Occupational Exposure Limits         GVI (OEL TWA) [1]       270 mg/m³         GVI (OEL TWA) [2]       50 ppm         KGVI (OEL STEL)       540 mg/m²         KGVI (OEL STEL) [ppm]       100 ppm         Cyprus - Occupational Exposure Limits	Austria - Occupational Exposure Limits	
MAK (OEL STEL)       540 mg/m³ (Pentylacetate)         MAK (OEL STEL) [ppm]       100 ppm (Pentylacetate)         Belgium - Occupational Exposure Limits       270 mg/m³         OEL TWA       50 ppm         OEL STEL       540 mg/m³         OEL STEL       100 ppm         Bulgaria - Occupational Exposure Limits         OEL TWA       270 mg/m³         OEL TWA       50 ppm         OEL STEL       540 mg/m³         OEL STEL       100 ppm         Croatia - Occupational Exposure Limits       GVI (OEL TWA) [1]       270 mg/m³         GVI (OEL TWA) [2]       50 ppm         KGVI (OEL STEL)       540 mg/m³         KGVI (OEL STEL) [ppm]       100 ppm         Cyprus - Occupational Exposure Limits       Cyprus - Occupational Exposure Limits	MAK (OEL TWA)	270 mg/m³ (Pentyl acetate (all isomers))
MAK (OEL STEL) [ppm]         100 ppm (Pentylacetate)           Belgium - Occupational Exposure Limits           OEL TWA         270 mg/m³           OEL TWA         50 ppm           OEL STEL         540 mg/m³           OEL STEL         100 ppm           Bulgaria - Occupational Exposure Limits           OEL TWA         270 mg/m³           OEL TWA         50 ppm           OEL STEL         540 mg/m³           OEL STEL         100 ppm           Croatia - Occupational Exposure Limits         GVI (OEL TWA) [1]         270 mg/m³           GVI (OEL TWA) [2]         50 ppm           KGVI (OEL STEL)         540 mg/m³           KGVI (OEL STEL) [ppm]         100 ppm           Cyprus - Occupational Exposure Limits         Cyprus - Occupational Exposure Limits	MAK (OEL TWA) [ppm]	50 ppm (Pentyl acetate (all isomers))
Belgium - Occupational Exposure Limits           OEL TWA         270 mg/m³           OEL STEL         540 mg/m³           OEL STEL         100 ppm           Bulgaria - Occupational Exposure Limits           OEL TWA         270 mg/m³           OEL TWA         50 ppm           OEL STEL         540 mg/m³           OEL STEL         100 ppm           Croatia - Occupational Exposure Limits         GVI (OEL TWA) [1]         270 mg/m³           GVI (OEL TWA) [2]         50 ppm           KGVI (OEL STEL)         540 mg/m³           KGVI (OEL STEL) [ppm]         100 ppm           Cyprus - Occupational Exposure Limits	MAK (OEL STEL)	540 mg/m³ (Pentylacetate)
OEL TWA         270 mg/m³           OEL TWA         50 ppm           OEL STEL         540 mg/m³           OEL STEL         100 ppm           Bulgaria - Occupational Exposure Limits           OEL TWA         270 mg/m³           OEL TWA         50 ppm           OEL STEL         540 mg/m³           OEL STEL         100 ppm           Croatia - Occupational Exposure Limits           GVI (OEL TWA) [1]         270 mg/m³           GVI (OEL STEL)         540 mg/m³           KGVI (OEL STEL)         540 mg/m³           KGVI (OEL STEL) [ppm]         100 ppm           Cyprus - Occupational Exposure Limits	MAK (OEL STEL) [ppm]	100 ppm (Pentylacetate)
OEL TWA 50 ppm  OEL STEL 540 mg/m³  OEL STEL 100 ppm  Bulgaria - Occupational Exposure Limits  OEL TWA 270 mg/m³  OEL TWA 50 ppm  OEL STEL 540 mg/m³  OEL STEL 540 mg/m³  OEL STEL 100 ppm  Croatia - Occupational Exposure Limits  GVI (OEL TWA) [1] 270 mg/m³  GVI (OEL TWA) [2] 50 ppm  KGVI (OEL STEL) 540 mg/m³  KGVI (OEL STEL) [ppm] 100 ppm	Belgium - Occupational Exposure Limits	
OEL STEL       540 mg/m³         OEL STEL       100 ppm         Bulgaria - Occupational Exposure Limits         OEL TWA       270 mg/m³         OEL TWA       50 ppm         OEL STEL       540 mg/m³         OEL STEL       100 ppm         Croatia - Occupational Exposure Limits         GVI (OEL TWA) [1]       270 mg/m³         GVI (OEL TWA) [2]       50 ppm         KGVI (OEL STEL)       540 mg/m³         KGVI (OEL STEL) [ppm]       100 ppm         Cyprus - Occupational Exposure Limits	OEL TWA	270 mg/m³
OEL STEL         100 ppm           Bulgaria - Occupational Exposure Limits           OEL TWA         270 mg/m³           OEL TWA         50 ppm           OEL STEL         540 mg/m³           OEL STEL         100 ppm           Croatia - Occupational Exposure Limits           GVI (OEL TWA) [1]         270 mg/m³           GVI (OEL TWA) [2]         50 ppm           KGVI (OEL STEL)         540 mg/m³           KGVI (OEL STEL) [ppm]         100 ppm           Cyprus - Occupational Exposure Limits	OEL TWA	50 ppm
Bulgaria - Occupational Exposure Limits   270 mg/m³	OEL STEL	540 mg/m³
OEL TWA       270 mg/m³         OEL TWA       50 ppm         OEL STEL       540 mg/m³         OEL STEL       100 ppm         Croatia - Occupational Exposure Limits         GVI (OEL TWA) [1]       270 mg/m³         GVI (OEL TWA) [2]       50 ppm         KGVI (OEL STEL)       540 mg/m³         KGVI (OEL STEL) [ppm]       100 ppm         Cyprus - Occupational Exposure Limits	OEL STEL	100 ppm
OEL TWA         50 ppm           OEL STEL         540 mg/m³           OEL STEL         100 ppm           Croatia - Occupational Exposure Limits           GVI (OEL TWA) [1]         270 mg/m³           GVI (OEL TWA) [2]         50 ppm           KGVI (OEL STEL)         540 mg/m³           KGVI (OEL STEL) [ppm]         100 ppm           Cyprus - Occupational Exposure Limits	Bulgaria - Occupational Exposure Limits	
OEL STEL         540 mg/m³           OEL STEL         100 ppm           Croatia - Occupational Exposure Limits           GVI (OEL TWA) [1]         270 mg/m³           GVI (OEL TWA) [2]         50 ppm           KGVI (OEL STEL)         540 mg/m³           KGVI (OEL STEL) [ppm]         100 ppm           Cyprus - Occupational Exposure Limits	OEL TWA	270 mg/m³
OEL STEL 100 ppm  Croatia - Occupational Exposure Limits  GVI (OEL TWA) [1] 270 mg/m³  GVI (OEL TWA) [2] 50 ppm  KGVI (OEL STEL) 540 mg/m³  KGVI (OEL STEL) [ppm] 100 ppm  Cyprus - Occupational Exposure Limits	OEL TWA	50 ppm
Croatia - Occupational Exposure Limits  GVI (OEL TWA) [1] 270 mg/m³  GVI (OEL TWA) [2] 50 ppm  KGVI (OEL STEL) 540 mg/m³  KGVI (OEL STEL) [ppm] 100 ppm  Cyprus - Occupational Exposure Limits	OEL STEL	540 mg/m³
GVI (OEL TWA) [1] 270 mg/m³  GVI (OEL TWA) [2] 50 ppm  KGVI (OEL STEL) 540 mg/m³  KGVI (OEL STEL) [ppm] 100 ppm  Cyprus - Occupational Exposure Limits	OEL STEL	100 ppm
GVI (OEL TWA) [2] 50 ppm  KGVI (OEL STEL) 540 mg/m³  KGVI (OEL STEL) [ppm] 100 ppm  Cyprus - Occupational Exposure Limits	Croatia - Occupational Exposure Limits	
KGVI (OEL STEL) 540 mg/m³  KGVI (OEL STEL) [ppm] 100 ppm  Cyprus - Occupational Exposure Limits	GVI (OEL TWA) [1]	270 mg/m³
KGVI (OEL STEL) [ppm] 100 ppm  Cyprus - Occupational Exposure Limits	GVI (OEL TWA) [2]	50 ppm
KGVI (OEL STEL) [ppm] 100 ppm  Cyprus - Occupational Exposure Limits	KGVI (OEL STEL)	540 mg/m³
Cyprus - Occupational Exposure Limits	KGVI (OEL STEL) [ppm]	100 ppm
	OEL TWA	270 mg/m³

isopentyl acetate (123-92-2)		
OEL TWA	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL	100 ppm	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	271 mg/m³ (Amyl acetate, all isomers)	
OEL TWA [2]	50 ppm (Amyl acetate, all isomers)	
OEL STEL	540 mg/m³	
OEL STEL	100 ppm	
Estonia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL	100 ppm	
Finland - Occupational Exposure Limits		
HTP (OEL TWA) [1]	270 mg/m³ (Pentyl acetate)	
HTP (OEL TWA) [2]	50 ppm (Pentyl acetate)	
HTP (OEL STEL)	540 mg/m³	
HTP (OEL STEL) [ppm]	100 ppm	
France - Occupational Exposure Limits		
VME (OEL TWA)	270 mg/m³ (restrictive limit)	
VME (OEL TWA) [ppm]	50 ppm (restrictive limit)	
VLE (OEL C/STEL)	540 mg/m³ (restrictive limit)	
VLE (OEL C/STEL) [ppm]	100 ppm (restrictive limit)	
Germany - Occupational Exposure Limits (TRGS 90	0)	
AGW (OEL TWA) [1]	270 mg/m³	
AGW (OEL TWA) [2]	50 ppm	
Gibraltar - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL	100 ppm	
Greece - Occupational Exposure Limits		
OEL TWA	530 mg/m³	
OEL TWA	100 ppm	
OEL STEL	800 mg/m³	
OEL STEL	150 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	270 mg/m³	
CK (OEL STEL)	540 mg/m³	

isopentyl acetate (123-92-2)		
Ireland - Occupational Exposure Limits		
OEL TWA [1]	260 mg/m³	
OEL TWA [2]	50 ppm	
OEL STEL	520 mg/m³	
OEL STEL	100 ppm	
Italy - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL	100 ppm	
Latvia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA	50 ppm	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	270 mg/m³	
IPRV (OEL TWA) [ppm]	50 ppm	
TPRV (OEL STEL)	540 mg/m³	
TPRV (OEL STEL) [ppm]	100 ppm	
Luxembourg - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL	100 ppm	
Malta - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL	100 ppm	
Netherlands - Occupational Exposure Limits		
TGG-15min (OEL STEL)	530 mg/m³	
TGG-15min (OEL STEL) [ppm]	98.1 ppm	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	250 mg/m³	
NDSCh (OEL STEL)	500 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	270 mg/m³ (indicative limit value)	
OEL TWA	50 ppm (indicative limit value (Pentyl acetate, all isomers)	
OEL STEL		
	540 mg/m³ (indicative limit value)	

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

isopentyl acetate (123-92-2)	isopentyl acetate (123-92-2)		
Romania - Occupational Exposure Limits	Romania - Occupational Exposure Limits		
OEL TWA	270 mg/m³		
OEL TWA	50 ppm		
OEL STEL	540 mg/m³		
OEL STEL	100 ppm		
Slovakia - Occupational Exposure Limits			
NPHV (OEL TWA) [1]	270 mg/m³		
NPHV (OEL TWA) [2]	50 ppm		
NPHV (OEL C)	540 mg/m³		
Slovenia - Occupational Exposure Limits			
OEL TWA	270 mg/m³		
OEL TWA	50 ppm		
OEL STEL	540 mg/m³		
OEL STEL	100 ppm		
Spain - Occupational Exposure Limits			
VLA-ED (OEL TWA) [1]	270 mg/m³ (indicative limit value)		
VLA-ED (OEL TWA) [2]	50 ppm (indicative limit value)		
VLA-EC (OEL STEL)	540 mg/m³		
VLA-EC (OEL STEL) [ppm]	100 ppm		
Sweden - Occupational Exposure Limits			
NGV (OEL TWA)	270 mg/m³ (Pentyl acetates)		
NGV (OEL TWA) [ppm]	50 ppm (Pentyl acetates)		
KTV (OEL STEL)	540 mg/m³ (Pentyl acetates)		
KTV (OEL STEL) [ppm]	100 ppm (Pentyl acetates)		
Norway - Occupational Exposure Limits			
Grenseverdi (OEL TWA) [1]	260 mg/m³		
Grenseverdi (OEL TWA) [2]	50 ppm		
Korttidsverdi (OEL STEL)	325 mg/m³ (value calculated)		
Korttidsverdi (OEL STEL) [ppm]	75 ppm (value calculated)		
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA [ppm]	50 ppm (Pentyl acetate, all isomers)		
ACGIH OEL STEL [ppm]	100 ppm (Pentyl acetate, all isomers)		

# 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

#### Personal protective equipment symbol(s):







#### 8.2.2.1. Eye and face protection

## Eye protection:

Safety glasses

### 8.2.2.2. Skin protection

#### Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Protective gloves

#### 8.2.2.3. Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

#### **Environmental exposure controls:**

Avoid release to the environment.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : light yellow. amber. Conforms to standard.

Odour : characteristic. characteristic.

Odour threshold : Not available Not applicable Melting point Freezing point Not available Boiling point Not available Flammability Not applicable **Explosive limits** Not available Lower explosion limit Not available Upper explosion limit Not available

Flash point : 64.9 °C (closed cup) ASTM D7094

Auto-ignition temperature Not available Decomposition temperature Not available рΗ : Not available Viscosity, kinematic Not available Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : Not available Vapour pressure at 50°C : Not available Density : Not available Relative density : ≈ 0.91

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

#### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

#### 10.5. Incompatible materials

No additional information available

# 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Dimyrcetol (25279-09-8)		
LD50 oral	2500 mg/kg bodyweight	
Grapefruit oil (8016-20-4)		
LD50 oral rat	> 5 g/kg (Source: NLM_CIP)	
Resin acids and Rosin acids, hydrogenated, r	nethyl esters (8050-15-5)	
LD50 oral rat	> 2000 mg/kg (Source: CHEMVIEW)	
LD50 dermal rabbit	> 10000 mg/kg (Source: ECHA_API)	
hexan-1-ol (111-27-3)		
LD50 oral rat	3210 mg/kg (Source: OECD_SIDS)	
LD50 oral	500 mg/kg bodyweight	
LD50 dermal rabbit	1500 – 2000 mg/kg (Source: OECD_SIDS)	
LD50 dermal	1750 mg/kg bodyweight	

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

hexan-1-ol (111-27-3)		
LC50 Inhalation - Rat	> 21 mg/l (Exposure time: 1 h Source: OECD_SIDS)	
Linalool (78-70-6)		
LD50 oral	2790 mg/kg bodyweight	
isobutyl acetate (110-19-0)		
LD50 oral rat	15400 mg/kg (Source: JAPAN_GHS)	
LD50 dermal rabbit	> 17400 mg/kg (Source: NLM_CIP)	
Melonal (106-72-9)		
LD50 oral rat	> 5 g/kg (Source: NLM_CIP)	
Geraniol (106-24-1)		
LD50 oral rat	3600 mg/kg (Source: NLM_CIP)	
LD50 oral	3600 mg/kg bodyweight	
LD50 dermal rabbit	> 5 g/kg (Source: NLM_CIP)	
Nerol (106-25-2)		
LD50 oral rat	4500 mg/kg (Source: NLM_CIP)	
LD50 oral	4500 mg/kg bodyweight	
LD50 dermal rabbit	> 5 g/kg (Source: NLM_CIP)	
Anisic alcohol (105-13-5)		
LD50 oral rat	1200 μl/kg (Source: NLM_CIP)	
LD50 dermal rabbit	3000 mg/kg (Source: ECHA_API)	
LD50 dermal	3000 mg/kg bodyweight	
(104-21-2)		
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)	
Cyclamal (103-95-7)		
LD50 oral rat	3810 mg/kg (Source: NLM_CIP)	
LD50 oral	3810 mg/kg bodyweight	
LD50 dermal rat	> 5000 mg/kg (Source: ECHA_API)	
Allyl heptanoate (142-19-8)		
LD50 oral rat	500 mg/kg (Source: NLM_CIP)	
LD50 oral	218 mg/kg bodyweight	
LD50 dermal rabbit	810 mg/kg (Source: ECHA_API)	
LD50 dermal	810 mg/kg bodyweight	
Allyl caproate (123-68-2)		
LD50 oral	300 mg/kg bodyweight	
LD50 dermal rabbit	820 mg/kg (Source: ECHA_API)	
LD50 dermal	300 mg/kg bodyweight	
LC50 Inhalation - Rat (Vapours)	3 mg/l/4h	

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Aldehyde C-16 (77-83-8)	
LD50 oral rat	5470 mg/kg (Source: NLM_CIP)
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
isobutyl acetate (110-19-0)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

# 11.2. Information on other hazards

No additional information available

# **SECTION 12: Ecological information**

-							
и	2.	7		VI		41/	
	<b>∠</b> .		w.	ХΙ	L I	LV	

Ecology - general : Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long–term : Harmful to aquatic life with long lasting effects.

(chronic)

(cnronic)	
hexan-1-ol (111-27-3)	
LC50 - Fish [1]	89.7 – 106 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	144 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static] Source: IUCLID)
Linalool (78-70-6)	
EC50 96h - Algae [1]	88.3 mg/l (Species: Desmodesmus subspicatus)
isobutyl acetate (110-19-0)	
LC50 - Fish [1]	17 mg/l (Exposure time: 96 h - Species: Oryzias latipes Source: ECHA)
Geraniol (106-24-1)	
LC50 - Fish [1]	22 mg/l (Exposure time: 96 h - Species: Danio rerio [static] Source: ECHA)
Nerol (106-25-2)	
LC50 - Fish [1]	20.3 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
Allyl caproate (123-68-2)	
LC50 - Fish [1]	0.117 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
Aldehyde C-16 (77-83-8)	
LC50 - Fish [1]	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static] Source: ECHA)

# 12.2. Persistence and degradability

No additional information available

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

# 12.3. Bioaccumulative potential

12.3. Dioaccumulative potential		
Dimyrcetol (25279-09-8)		
Partition coefficient n-octanol/water (Log Pow)	3.55 (at 20 °C (at pH >=6.55-<=6.7)	
Resin acids and Rosin acids, hydrogenated, methyl esters (8050-15-5)		
Partition coefficient n-octanol/water (Log Pow)	6.4 – 7.6 (at pH 6)	
hexan-1-ol (111-27-3)		
Partition coefficient n-octanol/water (Log Pow)	1.8	
isobutyl acetate (110-19-0)		
BCF - Fish [1]	(no significant bioconcentration)	
Partition coefficient n-octanol/water (Log Pow)	2.3 (at 25 °C (at pH 7)	
Melonal (106-72-9)		
Partition coefficient n-octanol/water (Log Pow)	3.4 (at 35 °C (at pH 7)	
Geraniol (106-24-1)		
Partition coefficient n-octanol/water (Log Pow)	2.6 (at 25 °C)	
Nerol (106-25-2)		
Partition coefficient n-octanol/water (Log Pow)	2.76 (at 30 °C (at pH 6.5)	
Anisic alcohol (105-13-5)		
Partition coefficient n-octanol/water (Log Pow)	-0.08 (at 27 °C (at pH 4.57)	
(104-21-2)		
Partition coefficient n-octanol/water (Log Pow)	1.9 (at 35 °C)	
isopentyl acetate (123-92-2)		
Partition coefficient n-octanol/water (Log Pow)	2.7 (at 35 °C)	
Cyclamal (103-95-7)		
Partition coefficient n-octanol/water (Log Pow)	3.4 (at 35 °C)	
Allyl heptanoate (142-19-8)		
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 20 °C (at pH 5.3)	
Allyl caproate (123-68-2)		
Partition coefficient n-octanol/water (Log Pow)	3.191 (at 20 °C (at pH 5)	
Aldehyde C-16 (77-83-8)		
Partition coefficient n-octanol/water (Log Pow)	2.4 (at 25 °C (cis isomer)	

# 12.4. Mobility in soil

No additional information available

# 12.5. Results of PBT and vPvB assessment

No additional information available

# 12.6. Endocrine disrupting properties

No additional information available

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.7. Other adverse effects

No additional information available

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste treatment methods HP Code

- $: \ \, \text{Dispose of contents/container in accordance with licensed collector's sorting instructions}.$
- : HP3 "Flammable:"
  - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and  $\leq$  75 °C;
  - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
  - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
  - flammable gaseous waste: gaseous waste which is flammable in air at 20  $^{\circ}\text{C}$  and a standard pressure of 101.3 kPa;
  - water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
  - other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

# **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID n	14.1. UN number or ID number			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shippin	g name			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard	14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

# 14.6. Special precautions for user

#### **Overland transport**

Not applicable

#### Transport by sea

Not applicable

# Air transport

Not applicable

### Inland waterway transport

Not applicable

#### Rail transport

Not applicable

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

#### **REACH Annex XVII (Restriction List)**

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	Grapefruit oil ; hexan-1-ol ; isobutyl acetate ; isopentyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	; Dimyrcetol ; Grapefruit oil ; hexan-1-ol ; Linalool ; isobutyl acetate ; Melonal ; Geraniol ; Nerol ; Anisic alcohol ; ; Cyclamal ; Allyl heptanoate ; Allyl caproate ; Aldehyde C-16	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	; Grapefruit oil ; Resin acids and Rosin acids, hydrogenated, methyl esters ; Cyclamal ; Allyl heptanoate ; Allyl caproate ; Aldehyde C-16	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	Grapefruit oil ; hexan-1-ol ; isobutyl acetate ; isopentyl acetate	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

## **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

# Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

#### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

#### Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).

Observe restrictions according Act on the Protection of Young People in Employment

(JArbSchG)

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

**Netherlands** 

ABM category : A(3) - hazardous for aquatic organisms, may have longterm hazardous effects in aquatic

environment

SZW-lijst van kankerverwekkende stoffen : Resin acids and Rosin acids, hydrogenated, methyl esters is listed

SZW-lijst van mutagene stoffen : Resin acids and Rosin acids, hydrogenated, methyl esters is listed

SZW-lijst van reprotoxische stoffen – Borstvoeding  $\phantom{a}$  : None of the components are listed

SZW-lijst van reprotoxische stoffen – : None of the components are listed

Vruchtbaarheid SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

**Denmark** 

Class for fire hazard : Class III-1 Store unit : 50 liter

Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines

for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with

the product

# 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## **SECTION 16: Other information**

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BLV	Biological limit value	
CAS-No.	Chemical Abstract Service number	
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC50	Median effective concentration	
EC-No.	European Community number	
EN	European Standard	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:		
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
vPvB	Very Persistent and Very Bioaccumulative	
WGK	Water Hazard Class	

Full text of H- and EUH-statements:		
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3	
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3	
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 2	Flammable liquids, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H301	Toxic if swallowed.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H311	Toxic in contact with skin.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H331	Toxic if inhaled.	

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
H336	May cause drowsiness or dizziness.	
H400	Very toxic to aquatic life.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	
Skin Sens. 1B	Skin sensitisation, category 1B	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.