

PURPLE LILAC

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 5/19/2020 Revision date: 11/13/2024 Supersedes version of: 8/21/2024 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : PURPLE LILAC

UFI : C5XN-3CWH-N00T-E1ED
Product code : Parf_Purple_Lilac
Type of product : Perfumes, fragrances
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use,Professional use Industrial/Professional use spec : For professional use only

Industrial

Use of the substance/mixture : Perfumes, fragrances Function or use category : Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

BAKED GAMES SRL ROMANIA, BUCHAREST, SECTOR 4 +40771326626

contact@kitlumanari.ro | www.kitlumanari.ro

1.4. Emergency telephone number

Emergency number : 1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731;

Brazil: +0-800-591-6042; India: +000-800-100-4086

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Carcinogenicity, Category 2 H351
Hazardous to the aquatic environment – Acute Hazard, H400

Category 1

Hazardous to the aquatic environment – Chronic Hazard, H412

Category 3

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Suspected of causing cancer. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects. May cause an allergic skin reaction. Very toxic to aquatic life.

11/13/2024 (Revision date) EN (English) 1/30

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







GHS07

GHS08

GHS09

Signal word (CLP) : Warning

Contains : Linalool; Cinnamic alcohol; Benzyl salicylate; Anisic alcohol; 3-(2,2-dimethyl-3-

hydroxypropyl)toluene; (alt.): 2,2-dimethyl-3-(3-methylphenyl)propanol; Hydroxy; Veratryl aldehyde (Veratraldehyde); Citronellol Pure; musk ketone; 3,5-dinitro-2,6-dimethyl-4-tert-butylacetophenone; 4'-tert-butyl-2', 6'-dimethyl-3',5'-dinitroacetophenone; isoeugenol

Hazard statements (CLP) : H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.H319 - Causes serious eye irritation.H351 - Suspected of causing cancer.

H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Bis(2-ethylhexyl) adipate substance with national workplace exposure limit(s) (PL)	CAS-No.: 103-23-1 EC-No.: 203-090-1 REACH-no: 01-2119439699-	23.9 – 47.75	Aquatic Acute 1, H400
Terpineol	CAS-No.: 8000-41-7 EC-No.: 232-268-1	7.5 – 15	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Phenylethyl alcohol	CAS-No.: 60-12-8 EC-No.: 200-456-2 REACH-no: 01-2119963921- 31	5 – 10	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319
Benzyl acetate substance with national workplace exposure limit(s) (BE, DK, ES, IE, LT, LV, PT, RO)	CAS-No.: 140-11-4 EC-No.: 205-399-7 REACH-no: 01-2119638272- 42	1.8 – 3.5	Aquatic Chronic 3, H412

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Linalool	CAS-No.: 78-70-6 EC-No.: 201-134-4 EC Index-No.: 603-235-00-2 REACH-no: 01-2119474016-	1.5 – 3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Cinnamic alcohol	CAS-No.: 104-54-1 EC-No.: 203-212-3 REACH-no: 01-2119934496- 29	1.5 – 3	Acute Tox. 4 (Oral), H302 Skin Sens. 1B, H317
Benzyl salicylate	CAS-No.: 118-58-1 EC-No.: 204-262-9 EC Index-No.: 607-754-00-5 REACH-no: 01-2119969442- 31	1.5 – 3	Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Anisic alcohol	CAS-No.: 105-13-5 EC-No.: 203-273-6 REACH-no: 01-2119934494- 33	1.30018 – 2.500375	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Skin Sens. 1, H317
Hydroxy	CAS-No.: 107-75-5 EC-No.: 203-518-7 REACH-no: 01-2119973482- 31	1.0774 – 2.1548	Eye Irrit. 2, H319 Skin Sens. 1B, H317
3-(2,2-dimethyl-3-hydroxypropyl)toluene; (alt.): 2,2-dimethyl-3-(3-methylphenyl)propanol	CAS-No.: 103694-68-4 EC-No.: 403-140-4 EC Index-No.: 603-138-00-5	0.01 – 2	Skin Sens. 1, H317 Aquatic Chronic 3, H412
Carbitol substance with national workplace exposure limit(s) (AT, DE, EE, SE, SI, CH)	CAS-No.: 111-90-0 EC-No.: 203-919-7 REACH-no: 01-2119475105- 42	0.7233 – 1.4466	Not classified
Anisic aldehyde	CAS-No.: 123-11-5 EC-No.: 204-602-6 REACH-no: 01-2119977101- 43	0.668 – 1.35	Aquatic Chronic 3, H412
Citronellol Pure	CAS-No.: 106-22-9 EC-No.: 203-375-0 REACH-no: 01-2119453995- 23	0.50003 – 1.0000625	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Ethylene brassylate	CAS-No.: 105-95-3 EC-No.: 203-347-8 REACH-no: 01-2119976314- 33	0.5 – 1	Aquatic Chronic 2, H411
musk ketone; 3,5-dinitro-2,6-dimethyl-4-tert-butylacetophenone; 4'-tert-butyl-2', 6'-dimethyl-3',5'-dinitroacetophenone	CAS-No.: 81-14-1 EC-No.: 201-328-9 EC Index-No.: 609-069-00-7	0.5 – 1	Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Phenylpropyl alcohol	CAS-No.: 122-97-4 EC-No.: 204-587-6	0.5 – 1	Skin Irrit. 2, H315 Eye Irrit. 2, H319

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
isoeugenol	CAS-No.: 97-54-1 EC-No.: 202-590-7 EC Index-No.: 604-094-00-X; 202-590-1 REACH-no: 17-2119417630-	0.4 – 0.75	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 Carc. 2, H351 STOT SE 3, H335
Veratryl aldehyde (Veratraldehyde)	CAS-No.: 120-14-9 EC-No.: 204-373-2	0.15 – 0.3125	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	0.001524 – 0.003175	Not classified
Toluene substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3	≤ 0.0000375	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
isoeugenol	CAS-No.: 97-54-1 EC-No.: 202-590-7 EC Index-No.: 604-094-00-X; 202-590-1 REACH-no: 17-2119417630-	(0.01 ≤ C ≤ 100) Skin Sens. 1A, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Suspected of causing cancer. IF exposed or concerned: Get medical advice/attention. First-aid measures after inhalation Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest. First-aid measures after skin contact If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash with plenty of water/.... Wash contaminated clothing before reuse. Get medical advice/attention. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention. First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center or a doctor if you feel unwell.

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : Causes skin irritation. Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew

with proper protection. For further information refer to section 8: "Exposure

controls/personal protection".

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or

diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild

soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment. Avoid

contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be

allowed out of the workplace. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep

container closed when not in use. Store locked up. Store in a well-ventilated place. Keep

cool.

Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight.

Storage temperature : 25 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Store in a closed container.

Packaging materials : Do not store in corrodable metal.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Bis(2-ethylhexyl) adipate (103-23-1)	
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	400 mg/m³
Benzyl acetate (140-11-4)	
Belgium - Occupational Exposure Limits	
OEL TWA	62 mg/m³
	10 ppm
Denmark - Occupational Exposure Limits	
OEL TWA	61 mg/m³
	10 ppm
OEL STEL	122 mg/m³
	20 ppm
Ireland - Occupational Exposure Limits	
OEL TWA	10 ppm
OEL STEL	30 ppm (calculated)
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m³

Benzyl acetate (140-11-4)		
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	10 ppm	
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen	
Romania - Occupational Exposure Limits		
OEL TWA	50 mg/m³	
	8 ppm	
OEL STEL	80 mg/m³	
	13 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	62 mg/m³	
	10 ppm	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	10 ppm	
ACGIH chemical category	Not Classifiable as a Human Carcinogen	
Carbitol (111-90-0)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	35 mg/m³	
	6 ppm	
MAK (OEL STEL)	140 mg/m³	
	24 ppm	
Estonia - Occupational Exposure Limits		
OEL TWA	50.1 mg/m³	
	10 ppm	
OEL chemical category	Skin notation	
Germany - Occupational Exposure Limits (TRGS 9	00)	
AGW (OEL TWA)	35 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
	6 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
Slovenia - Occupational Exposure Limits		
OEL TWA	35 mg/m³	
	6 ppm	
OEL STEL	70 mg/m³	
	12 ppm	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	80 mg/m³	
	15 ppm	

Carbitol (111-90-0)		
KGV (OEL STEL)	170 mg/m³	
	30 ppm	
OEL chemical category	Skin notation	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	50 mg/m³ (aerosol, inhalable dust, vapour)	
KZGW (OEL STEL)	100 mg/m³ (aerosol, inhalable dust, vapour)	
Toluene (108-88-3)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	192 mg/m³	
	50 ppm	
IOEL STEL	384 mg/m³	
	100 ppm	
Remark	Possibility of significant uptake through the skin	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	190 mg/m³	
	50 ppm	
MAK (OEL STEL)	380 mg/m³	
	100 ppm	
OEL chemical category	Skin notation	
Belgium - Occupational Exposure Limits		
OEL TWA	77 mg/m³	
	20 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Skin, Skin notation	
Bulgaria - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
Bulgaria - Biological limit values		
BLV	1.6 mmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of exposure or end of work shift	
Croatia - Occupational Exposure Limits		
GVI (OEL TWA)	192 mg/m³	
	50 ppm	
KGVI (OEL STEL)	384 mg/m³	
	100 ppm	
OEL chemical category	Skin notation	

Toluene (108-88-3)		
Croatia - Biological limit values		
BLV	1 mg/l Parameter: Toluene - Medium: blood - Sampling time: at the end of the work shift 20 ppm Parameter: Toluene - Medium: final exhaled air - Sampling time: during exposure 2.5 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine) 1 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine)	
Cyprus - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Skin-potential for cutaneous absorption	
Czech Republic - Occupational Exposure Limits		
PEL (OEL TWA)	200 mg/m³	
OEL chemical category	Potential for cutaneous absorption	
Czech Republic - Biological limit values		
BLV	1.6 μmol/mmol Creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1000 μmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.) 1.5 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1600 mg/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.)	
Denmark - Occupational Exposure Limits		
OEL TWA	94 mg/m³	
	25 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Potential for cutaneous absorption	
Estonia - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Skin notation	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	81 mg/m³	

Toluene (108-88-3)			
	25 ppm		
HTP (OEL STEL)	380 mg/m³		
	100 ppm		
OEL chemical category	Potential for cutaneous absorption		
Finland - Biological limit values			
BLV	500 nmol/L Parameter: Toluene - Medium: blood - Sampling time: in the morning after a working day		
France - Occupational Exposure Limits			
VME (OEL TWA)	76.8 mg/m³ (restrictive limit)		
	20 ppm (restrictive limit)		
VLE (OEL C/STEL)	384 mg/m³ (restrictive limit)		
	100 ppm (restrictive limit)		
OEL chemical category	Reproductive Toxin category 2, Risk of cutaneous absorption		
France - Biological limit values			
BLV	20 µg/l Parameter: Toluene - Medium: blood - Sampling time: end of workweek (Semi- quantitative (ambiguous interpretation)) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (per the Authority, the values for this substance must be decided and/or determined on a case by case basis. Guidance for the calculation of and interpretation of values is provided in the source)		
Germany - Occupational Exposure Limits (TRGS 90	0)		
AGW (OEL TWA)	190 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)		
	50 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)		
Chemical category	Skin notation		
Germany - Biological limit values (TRGS 903)			
Biological limit value	600 μg/l Parameter: Toluene - Medium: whole blood - Sampling time: immediately after exposure 75 μg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 1.5 mg/l Parameter: o-Cresol (after hydrolysis) - Medium: urine - Sampling time: for long-term exposures: at the end of the shift after several shifts 1.5 mg/l Parameter: o-Cresol (after hydrolysis) - Medium: urine - Sampling time: end of shift		
Gibraltar - Occupational Exposure Limits	Gibraltar - Occupational Exposure Limits		
OEL TWA	192 mg/m³		
	50 ppm		
OEL STEL	384 mg/m³		
	100 ppm		
OEL chemical category	Skin notation		
Greece - Occupational Exposure Limits			
OEL TWA	192 mg/m³		
	50 ppm		
OEL STEL	384 mg/m³		

Toluene (108-88-3)		
	100 ppm	
OEL chemical category	skin - potential for cutaneous absorption	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	190 mg/m³	
CK (OEL STEL)	384 mg/m³	
OEL chemical category	Potential for cutaneous absorption	
Ireland - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Potential for cutaneous absorption	
Italy - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL chemical category	skin - potential for cutaneous absorption	
Latvia - Occupational Exposure Limits		
OEL TWA	50 mg/m³	
	14 ppm	
OEL chemical category	skin - potential for cutaneous exposure	
Latvia - Biological Exposure Indices		
BEI	1.6 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift 0.05 mg/l Parameter: Toluene - Medium: blood - Sampling time: end of shift	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	192 mg/m³	
	50 ppm	
TPRV (OEL STEL)	384 mg/m³	
	100 ppm	
OEL chemical category	Reproductive toxin, Skin notation	
Luxembourg - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Possibility of significant uptake through the skin	
Malta - Occupational Exposure Limits	1	
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	

Toluene (108-88-3)		
	100 ppm	
OEL chemical category	Possibility of significant uptake through the skin	
Netherlands - Occupational Exposure Limits		
TGG-8u (OEL TWA)	150 mg/m³	
	39 ppm	
TGG-15min (OEL STEL)	384 mg/m³	
	100 ppm	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	100 mg/m³	
NDSCh (OEL STEL)	200 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	192 mg/m³ (indicative limit value)	
	50 ppm (indicative limit value)	
OEL STEL	384 mg/m³ (indicative limit value)	
	100 ppm (indicative limit value)	
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure indicative limit value	
Romania - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Skin notation	
Romania - Biological limit values		
BLV	2 g/l Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift 3 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA)	192 mg/m³	
	50 ppm	
NPHV (OEL C)	384 mg/m³ (also biological monitoring considered)	
OEL chemical category	Potential for cutaneous absorption	
Slovakia - Biological limit values		
BLV	600 μg/l Parameter: Toluene - Medium: blood - Sampling time: end of exposure or work shift	
	1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: after all work shifts (for long-term exposure) 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of exposure or work shift 2401 mg/g creatinine Parameter: Hippuric acid - Sampling time: end of exposure or work shift	
Slovenia - Occupational Exposure Limits		
OEL TWA	192 mg/m³	

Toluene (108-88-3)	
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Category 2, Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	192 mg/m³ (indicative limit value)
	50 ppm (indicative limit value)
VLA-EC (OEL STEL)	384 mg/m³
	100 ppm
OEL chemical category	skin - potential for cutaneous absorption
Spain - Biological limit values	
BLV	0.6 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift 0.05 mg/l Parameter: Toluene - Medium: blood - Sampling time: start of last shift of workweek 0.08 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	192 mg/m³
	50 ppm
KGV (OEL STEL)	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	191 mg/m³
	50 ppm
WEL STEL (OEL STEL)	384 mg/m³
	100 ppm
WEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	94 mg/m³
	25 ppm
Korttidsverdi (OEL STEL)	141 mg/m³ (value calculated)
	37.5 ppm (value calculated)
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	190 mg/m³
	50 ppm
KZGW (OEL STEL)	760 mg/m³
	200 ppm
OEL chemical category	Skin notation, Category 2 reproductive toxin

Toluene (108-88-3)			
Switzerland - BAT			
BAT	600 μg/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 6.48 μmol/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 2 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 0.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 4.62 μmol/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 75 μg/l Parameter: Toluol - Medium: urine - Sampling time: end of shift		
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA	20 ppm		
ACGIH chemical category	Not Classifiable as a Human Carcinogen		
USA - ACGIH - Biological Exposure Indices			
BEI	0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 0.3 mg/g creatinine Parameter: o-Cresol with hydrolysis - Medium: urine - Sampling time: end of shift (background)		
Dipropylene glycol monomethyl ether (34590-	94-8)		
EU - Indicative Occupational Exposure Limit (IOEL)			
IOEL TWA	308 mg/m³		
	50 ppm		
Remark	Possibility of significant uptake through the skin		
Austria - Occupational Exposure Limits			
MAK (OEL TWA)	307 mg/m³ (mixed isomers)		
	50 ppm (mixed isomers)		
MAK (OEL STEL)	614 mg/m³ (isomers mixtures)		
	100 ppm (isomers mixtures)		
OEL chemical category	Skin notation		
Belgium - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
	50 ppm		
OEL chemical category	Skin, Skin notation		
Bulgaria - Occupational Exposure Limits	Bulgaria - Occupational Exposure Limits		
OEL TWA	308 mg/m³		
	50 ppm		
Croatia - Occupational Exposure Limits			
GVI (OEL TWA)	308 mg/m³		
	50 ppm		
OEL chemical category	Skin notation		

Dipropylene glycol monomethyl ether (34590-94-8)		
Cyprus - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
	50 ppm	
OEL chemical category	Skin-potential for cutaneous absorption	
Czech Republic - Occupational Exposure Limits		
PEL (OEL TWA)	270 mg/m³	
OEL chemical category	Potential for cutaneous absorption	
Denmark - Occupational Exposure Limits		
OEL TWA	309 mg/m³	
	50 ppm	
OEL STEL	618 mg/m³	
	100 ppm	
OEL chemical category	Potential for cutaneous absorption	
Estonia - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
	50 ppm	
OEL chemical category	Skin notation	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	310 mg/m³	
	50 ppm	
OEL chemical category	Potential for cutaneous absorption	
France - Occupational Exposure Limits		
VME (OEL TWA)	308 mg/m³ (restrictive limit)	
	50 ppm (restrictive limit)	
OEL chemical category	Risk of cutaneous absorption	
Germany - Occupational Exposure Limits (TRGS 90	00)	
AGW (OEL TWA)	310 mg/m³ (isomer mixture)	
	50 ppm (isomer mixture)	
Gibraltar - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
	50 ppm	
OEL chemical category	Skin notation	
Greece - Occupational Exposure Limits		
OEL TWA	600 mg/m³	
	100 ppm	
OEL STEL	900 mg/m³	
	150 ppm	
1	skin - potential for cutaneous absorption	

Dipropylene glycol monomethyl ether (34590-94-8)	
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	308 mg/m³
Ireland - Occupational Exposure Limits	
OEL TWA	308 mg/m³ ((2-Methoxymethylethoxy)propanol)
	50 ppm ((2-Methoxymethylethoxy)propanol)
OEL STEL	924 mg/m³ (calculated (2-(2-Methoxypropoxy)-1-propanol)
	150 ppm (calculated (2-(2-Methoxypropoxy)-1-propanol)
OEL chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	308 mg/m³ (1-(3-Methoxypropoxy)propan-1-ol)
	50 ppm (1-(3-Methoxypropoxy)propan-1-ol)
OEL chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	skin - potential for cutaneous exposure
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	300 mg/m³ (2-(2-Methoxypropoxy)-propanol)
	50 ppm (2-(2-Methoxypropoxy)-propanol)
TPRV (OEL STEL)	450 mg/m³ (2-(2-Methoxypropoxy)-propanol)
	75 ppm (2-(2-Methoxypropoxy)-propanol)
OEL chemical category	Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	300 mg/m³
	48.7 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
NDSCh (OEL STEL)	480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
Portugal - Occupational Exposure Limits	
OEL TWA	308 mg/m³ (indicative limit value)

Dipropylene glycol monomethyl ether (34590-94-8)		
	50 ppm (indicative limit value)	
OEL STEL	150 ppm	
OEL chemical category	skin - potential for cutaneous exposure indicative limit value	
Romania - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
	50 ppm	
OEL chemical category	Skin notation	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA)	308 mg/m³	
	50 ppm	
OEL chemical category	Potential for cutaneous absorption	
Slovenia - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
	50 ppm	
OEL STEL	308 mg/m³	
	50 ppm	
OEL chemical category	Potential for cutaneous absorption	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	308 mg/m³ (indicative limit value)	
	50 ppm (indicative limit value)	
OEL chemical category	skin - potential for cutaneous absorption	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	300 mg/m³	
	50 ppm	
KGV (OEL STEL)	450 mg/m³	
	75 ppm	
OEL chemical category	Skin notation	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	308 mg/m³	
	50 ppm	
WEL STEL (OEL STEL)	924 mg/m³ (calculated)	
	150 ppm (calculated)	
WEL chemical category	Potential for cutaneous absorption	
Norway - Occupational Exposure Limits	·	
Grenseverdi (OEL TWA)	300 mg/m³	
	50 ppm	
Korttidsverdi (OEL STEL)	375 mg/m³ (value calculated)	
	75 ppm (value calculated)	
OEL chemical category	Skin notation	

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	300 mg/m³ (aerosol, vapour)
	50 ppm (aerosol, vapour)
KZGW (OEL STEL)	300 mg/m³ (aerosol, vapour)
	50 ppm (aerosol, vapour)
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	50 ppm (Dipropylene glycol methyl ether)
musk ketone; 3,5-dinitro-2,6-dimethyl-4-tert-butylacetophenone; 4'-tert-butyl-2', 6'-dimethyl-3',5'-dinitroacetophenone (81-14-1)	
Austria - Occupational Exposure Limits	
OEL chemical category	Group B Carcinogen

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):







8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves. Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Wear appropriate mask

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Odour

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

: light yellow. amber. Conforms to standard. Colour

characteristic.

Odour threshold : Not available Melting point : Not applicable Freezing point : Not available Boiling point Not available Flammability : Not applicable Lower explosion limit : Not available Upper explosion limit : Not available · > 93 °C Flash point Auto-ignition temperature : Not available Decomposition temperature : Not available рΗ : Not available Viscosity, kinematic Not available Solubility Not available

Partition coefficient n-octanol/water (Log Kow) : Not available

Vapour pressure : 0.002974156 mm Hg (calculated value)

Vapour pressure at 50°C : Not available Density : Not available Relative density :≈0.98 Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 23.9564375 % (calculated value)(CARB VOC) (%w/w)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions. Not established.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Not established.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Direct sunlight. Extremely high or low temperatures.

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (inhalation)	Not classified	
Bis(2-ethylhexyl) adipate (103-23-1)		
LD50 oral rat	5600 mg/kg (Source: NLM_CIP)	
LD50 dermal rabbit	8410 mg/kg (Source: NLM_CIP)	
LC50 Inhalation - Rat	> 5.7 mg/l/4h	
Terpineol (8000-41-7)		
LD50 oral rat	2900 mg/kg (Source: IUCLID)	
LD50 oral	4300 mg/kg bodyweight	
LD50 dermal rabbit	> 3000 mg/kg (Source: IUCLID)	
Phenylethyl alcohol (60-12-8)		
LD50 oral rat	1609 mg/kg (Source: EPA_HPV)	
LD50 oral	1610 mg/kg	
LD50 dermal rabbit	2535 mg/kg (Source: EPA_HPV)	
LC50 Inhalation - Rat	> 4.63 mg/l/4h	
Benzyl acetate (140-11-4)		
LD50 oral rat	2490 mg/kg (Source: JAPAN_GHS)	
LD50 oral	2490 mg/kg bodyweight	
LD50 dermal rabbit	> 5000 mg/kg (Source: JAPAN_GHS)	
Linalool (78-70-6)		
LD50 oral	2790 mg/kg	
Cinnamic alcohol (104-54-1)		
LD50 oral	2000 mg/kg bodyweight	
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA_API)	
Benzyl salicylate (118-58-1)		
LD50 oral rat	2227 mg/kg (Source: NLM_CIP)	
LD50 oral	2200 mg/kg bodyweight	
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)	
Anisic alcohol (105-13-5)		
LD50 oral rat	1200 μl/kg (Source: NLM_CIP)	
LD50 dermal rabbit	3000 mg/kg (Source: ECHA_API)	

Anisic alcohol (105-13-5)		
LD50 dermal	3000 mg/kg bodyweight	
3-(2,2-dimethyl-3-hydroxypropyl)toluene; (alt.): 2,2-dimethyl-3-(3-methylphenyl)propanol (103694-68-4)	
LD50 oral	3440 mg/kg bodyweight	
LD50 dermal rabbit	> 5 ml/kg (Source: ECHA_API)	
Carbitol (111-90-0)		
LD50 oral rat	10502 mg/kg (Source: OECD_SIDS)	
LD50 dermal rabbit	9143 mg/kg (Source: OECD_SIDS)	
LC50 Inhalation - Rat	> 5240 mg/m³ (Exposure time: 4 h Source: NLM_CIP)	
Hydroxy (107-75-5)		
LD50 oral rat	> 6400 mg/kg (Source: ECHA)	
LD50 dermal rabbit	> 2000 mg/kg (Source: ECHA_API)	
Anisic aldehyde (123-11-5)		
LD50 oral rat	3210 mg/kg (Source: ECHA)	
LD50 oral	3210 mg/kg bodyweight	
LD50 dermal rabbit	> 5000 mg/kg (Source: EPA_HPV)	
LC50 Inhalation - Rat	> 0.32 mg/l (Exposure time: 7 h Source: ECHA)	
Veratryl aldehyde (Veratraldehyde) (120-14-9)		
LD50 oral rat	2 g/kg (Source: NLM_CIP)	
LD50 oral	2000 mg/kg bodyweight	
Toluene (108-88-3)		
LD50 oral rat	2600 mg/kg (Source: JAPAN_GHS)	
LD50 dermal rabbit	12000 mg/kg (Source: JAPAN_GHS)	
LC50 Inhalation - Rat	12.5 mg/l/4h	
Citronellol Pure (106-22-9)		
LD50 oral rat	3450 mg/kg (Source: NLM_CIP)	
LD50 oral	3450 mg/kg bodyweight	
LD50 dermal rabbit	2650 mg/kg (Source: EPA_HPV)	
LD50 dermal	2650 mg/kg bodyweight	
Dipropylene glycol monomethyl ether (34590-94-8)		
LD50 oral rat	5.35 g/kg (Source: NLM_HSDB)	
LD50 dermal rabbit	9500 mg/kg (Source: NLM_CIP)	
Ethylene brassylate (105-95-3)		
LD50 oral rat	> 5000 mg/kg (Source: ECHA)	
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA)	
musk ketone; 3,5-dinitro-2,6-dimethyl-4-tert-butylacetophenone; 4'-tert-butyl-2', 6'-dimethyl-3',5'-dinitroacetophenone (81-14-1)		
LD50 oral rat	10 g/kg	
	1	

musk ketone; 3,5-dinitro-2,6-dimethy 14-1)	yl-4-tert-butylacetophenone; 4'-tert-butyl-2', 6'-dimethyl-3',5'-dinitroacetophenone (81
LD50 dermal rabbit	> 10 g/kg (Source: NLM_HSDB)
LC50 Inhalation - Rat	> 2.99 mg/l/4h
Phenylpropyl alcohol (122-97-4)	
LD50 oral rat	2250 mg/kg (Source: NICNAS)
LD50 oral	2275 mg/kg bodyweight
LD50 dermal rabbit	< 5000 mg/kg (Source: NICNAS)
LD50 dermal	5000 mg/kg bodyweight
isoeugenol (97-54-1)	
LD50 oral rat	1560 mg/kg (Source: NLM_CIP)
LD50 oral	1500 mg/kg bodyweight
LD50 dermal	1912 mg/kg bodyweight
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Bis(2-ethylhexyl) adipate (103-23-1)	
IARC group	3 - Not classifiable
Benzyl acetate (140-11-4)	
IARC group	3 - Not classifiable
Toluene (108-88-3)	
IARC group	3 - Not classifiable
isoeugenol (97-54-1)	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity STOT-single exposure	: Not classified: Not classified
Toluene (108-88-3)	. Not dassilied
STOT-single exposure	May cause drowsiness or dizziness.
isoeugenol (97-54-1)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Toluene (108-88-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Toluene (108-88-3)	
Hydrocarbon	Yes
	I .

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2.2. Other information

Potential adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

: Harmful to aquatic life with long lasting effects. Very toxic to aquatic life. : Very toxic to aquatic life.

Hazardous to the aquatic environment, short-term

(chronic)

Hazardous to the aquatic environment, long-term : Harmful to aquatic life with long lasting effects.

(Gillottic)		
Bis(2-ethylhexyl) adipate (103-23-1)		
LC50 - Fish [1]	0.48 – 0.85 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)	
LC50 - Fish [2]	0.48 – 0.85 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)	
EC50 - Crustacea [1]	> 1.6 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 72h - Algae [1]	> 500 mg/l (Species: Desmodesmus subspicatus)	
Phenylethyl alcohol (60-12-8)		
EC50 - Crustacea [1]	287.17 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 72h - Algae [1]	490 mg/l (Species: Desmodesmus subspicatus)	
Linalool (78-70-6)		
EC50 96h - Algae [1]	88.3 mg/l (Species: Desmodesmus subspicatus)	
Benzyl salicylate (118-58-1)		
LC50 - Fish [1]	1.03 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)	
Carbitol (111-90-0)		
LC50 - Fish [1]	10000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)	
LC50 - Fish [2]	19100 – 23900 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through] Source: EPA)	
EC50 - Crustacea [1]	3940 – 4670 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
Toluene (108-88-3)		
LC50 - Fish [1]	15.22 – 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
LC50 - Fish [2]	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)	
EC50 - Crustacea [1]	5.46 – 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
EC50 - Crustacea [2]	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 72h - Algae [1]	12.5 mg/l (Species: Pseudokirchneriella subcapitata [static])	
EC50 96h - Algae [1]	> 433 mg/l (Species: Pseudokirchneriella subcapitata)	
Dipropylene glycol monomethyl ether (34590-94-8)		
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)	

12.2. Persistence and degradability

Persistence and degradability	Not established.
Bis(2-ethylhexyl) adipate (103-23-1)	
Persistence and degradability	Rapidly degradable
Terpineol (8000-41-7)	
Persistence and degradability	Rapidly degradable
Phenylethyl alcohol (60-12-8)	
Persistence and degradability	Rapidly degradable
Benzyl acetate (140-11-4)	
Persistence and degradability	Rapidly degradable
Linalool (78-70-6)	
Persistence and degradability	Rapidly degradable
Cinnamic alcohol (104-54-1)	
Persistence and degradability	Rapidly degradable
Benzyl salicylate (118-58-1)	
Persistence and degradability	Rapidly degradable
Anisic alcohol (105-13-5)	
Persistence and degradability	Rapidly degradable
3-(2,2-dimethyl-3-hydroxypropyl)toluene; (alt.): 2,2-dimethyl-3-(3-methylphenyl)propanol (103694-68-4)
Persistence and degradability	Rapidly degradable
Carbitol (111-90-0)	
Persistence and degradability	Rapidly degradable
Hydroxy (107-75-5)	
Persistence and degradability	Rapidly degradable
Anisic aldehyde (123-11-5)	
Persistence and degradability	Rapidly degradable
Veratryl aldehyde (Veratraldehyde) (120-14-9)	
Persistence and degradability	Rapidly degradable
Toluene (108-88-3)	
Persistence and degradability	Rapidly degradable
Citronellol Pure (106-22-9)	
Persistence and degradability	Rapidly degradable
Dipropylene glycol monomethyl ether (34590-	94-8)
Persistence and degradability	Rapidly degradable
Ethylene brassylate (105-95-3)	
Persistence and degradability	Rapidly degradable
	EN (English) 24/30

musk ketone; 3,5-dinitro-2,6-dimethyl-4-tert-butylacetophenone; 4'-tert-butyl-2', 6'-dimethyl-3',5'-dinitroacetophenone (81-14-1)		
Persistence and degradability	Rapidly degradable	
Phenylpropyl alcohol (122-97-4)		
Persistence and degradability	Rapidly degradable	
isoeugenol (97-54-1)		
Persistence and degradability	Rapidly degradable	
12.3. Bioaccumulative potential		
Bioaccumulative potential	Not established.	
Bis(2-ethylhexyl) adipate (103-23-1)		
BCF - Fish [1]	(27 dimensionless)	
Partition coefficient n-octanol/water (Log Pow)	8.94 (at 25 °C)	
Phenylethyl alcohol (60-12-8)		
Partition coefficient n-octanol/water (Log Pow)	1.36 (at 20 °C (at pH 7)	
Benzyl acetate (140-11-4)		
Partition coefficient n-octanol/water (Log Pow)	1.96 (at 25 °C (at pH 7)	
Cinnamic alcohol (104-54-1)		
Partition coefficient n-octanol/water (Log Pow)	1.636 (at 27 °C (at pH 3.52)	
Benzyl salicylate (118-58-1)		
Partition coefficient n-octanol/water (Log Pow)	4	
Anisic alcohol (105-13-5)		
Partition coefficient n-octanol/water (Log Pow)	-0.08 (at 27 °C (at pH 4.57)	
3-(2,2-dimethyl-3-hydroxypropyl)toluene; (alt.): 2,2-dimethyl-3-(3-methylphenyl)propanol (103694-68-4)	
Partition coefficient n-octanol/water (Log Pow)	3.07 (at 20 °C)	
Carbitol (111-90-0)		
Partition coefficient n-octanol/water (Log Pow)	-0.8	
Hydroxy (107-75-5)		
Partition coefficient n-octanol/water (Log Pow)	1.68 (at 25 °C)	
Anisic aldehyde (123-11-5)		
Partition coefficient n-octanol/water (Log Pow)	1.56 (at 25 °C (at pH >7.9-<8.25)	
Veratryl aldehyde (Veratraldehyde) (120-14-9)		
Partition coefficient n-octanol/water (Log Pow)	0.8 (at 25 °C)	
Toluene (108-88-3)		
Partition coefficient n-octanol/water (Log Pow)	2.73 (at 20 °C (at pH 7)	
Citronellol Pure (106-22-9)		
Partition coefficient n-octanol/water (Log Pow)	3.41 (at 25 °C)	

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)		
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7)	
Ethylene brassylate (105-95-3)		
Partition coefficient n-octanol/water (Log Pow)	4.3 (at 25 °C (at pH 6.4-7)	
musk ketone; 3,5-dinitro-2,6-dimethyl-4-tert-butylacetophenone; 4'-tert-butyl-2', 6'-dimethyl-3',5'-dinitroacetophenone (81-14-1)		
Partition coefficient n-octanol/water (Log Pow)	4.24 (at 25 °C)	
Phenylpropyl alcohol (122-97-4)		
Partition coefficient n-octanol/water (Log Pow)	1.6 (at 35 °C (at pH 7)	

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

Product/Packaging disposal recommendations

Ecological information HP Code

- $: \ \, \text{Dispose of contents/container in accordance with licensed collector's sorting instructions}.$
- : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with local/national laws and regulations.
- : Avoid release to the environment.
- : HP7 "Carcinogenic:" waste which induces cancer or increases its incidence

HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID	
14.1. UN number or ID number					
Not applicable	olicable Not applicable Not applicable Not applicable Not applicable		Not applicable		
14.2. UN proper shipping name					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.3. Transport hazard class(es)					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.4. Packing group					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.5. Environmental hazards				
Not applicable	t applicable Not applicable Not applicable Not applicable Not applicable			
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)				
Reference code	Applicable on	Entry title or description		
3(b)	; Terpineol ; Benzyl salicylate ; Phenylethyl alcohol ; Anisic alcohol ; Hydroxy ; Citronellol Pure ; Linalool ; 3-(2,2-dimethyl-3-hydroxypropyl)toluene; (alt.): 2,2-dimethyl-3-(3-methylphenyl)propanol ; Phenylpropyl alcohol ; musk ketone; 3,5-dinitro-2,6-dimethyl-4-tert-butylacetophenone; 4'-tert-butyl-2', 6'-dimethyl-3',5'-dinitroacetophenone ; isoeugenol	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10		

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EU restriction list (REACH Annex XVII)			
Reference code	Applicable on	Entry title or description	
3(c)	; Benzyl salicylate; Benzyl acetate; Ethylene brassylate; Anisic aldehyde; 3-(2,2- dimethyl-3- hydroxypropyl)toluene; (alt.): 2,2-dimethyl-3-(3- methylphenyl)propanol; musk ketone; 3,5- dinitro-2,6-dimethyl-4-tert- butylacetophenone; 4'- tert-butyl-2', 6'- dimethyl-3',5'- dinitroacetophenone	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 23.9564375 % (calculated value)(CARB VOC) (%w/w)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Na	ame	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Tol	luene		108-88-3	2902 30 00	Category 3		Annex I

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.1.2. National regulations

France

Occupational diseases		
Code	Description	
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them	
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide	

Germany

Employment restrictions Observe restrictions according Act on the Protection of Working Mothers (MuSchG).

Observe restrictions according Act on the Protection of Young People in Employment

(JArbSchG).

Water hazard class (WGK) WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

Hazardous Incident Ordinance (12. BImSchV) Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(1) - highly toxic for aquatic organisms, may have longterm hazardous effects in aquatic

environment

SZW-lijst van kankerverwekkende stoffen Terpineol is listed

SZW-lijst van mutagene stoffen Terpineol is listed

SZW-lijst van reprotoxische stoffen – Borstvoeding

SZW-lijst van reprotoxische stoffen -

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen - Ontwikkeling

: None of the components are listed None of the components are listed

: Toluene is listed

Denmark

Classification remarks Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with

the product

The requirements from the Danish Working Environment Authorities regarding work with

carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Other information : None.

Full text of H- and EUH-statements:		
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3	
Asp. Tox. 1	Aspiration hazard, Category 1	
Carc. 2	Carcinogenicity, Category 2	

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 2	Flammable liquids, Category 2	
H225	Highly flammable liquid and vapour.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H351	Suspected of causing cancer.	
H361d	Suspected of damaging the unborn child.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Repr. 2	Reproductive toxicity, Category 2	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	
Skin Sens. 1A	Skin sensitisation, category 1A	
Skin Sens. 1B	Skin sensitisation, category 1B	
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

The classification complies with Safety Data Sheet (SDS), EU

: ATP 12

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.