

SUGAR CHERRY

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 8/14/2023 Revision date: 12/4/2020 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Trade name	: SUGAR CHERRY
UFI	: 9SE2-F2MN-N00X-0HJ4
Product code	: Parf_Sugar_Cherry
Type of product	: Perfumes, fragrances
Product group	: Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	: Professional use, Industrial use
Industrial/Professional use spec	: Industrial
	For professional use only
Use of the substance/mixture	: Perfumes, fragrances
Function or use category	: Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

BAKED GAMES SRL ROMANIA, BUCHAREST, SECTOR 4 +40771326626 contact@kitlumanari.ro | www.kitlumanari.ro

1.4. Emergency telephone number

Emergency number


: 1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731; Brazil: +0-800-591-6042; India: +000-800-100-4086

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	
Acute toxicity (oral), Category 4	H302
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411
Full text of H- and EUH-statements: see section 16	

Adverse physicochemical, human health and environmental effects

Harmful to aquatic life with long lasting effects. Harmful if swallowed. Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Oxypheylon (Raspberry ketone) crystals; Geranyl acetate; Citronellol Pure; beta- Caryophyllene; Triplal (Vertocitral)
Caryophyllene; Triplal (Vertocitral)
: H302 - Harmful if swallowed.
H317 - May cause an allergic skin reaction.
H411 - Toxic to aquatic life with long lasting effects.
: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing
protection.
: For professional users only.

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371- 33	35.7 – 71.322	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Benzaldehyde substance with national workplace exposure limit(s) (BG, FI, HU, LT, LV, PL)	CAS-No.: 100-52-7 EC-No.: 202-860-4 EC Index-No.: 605-012-00-5 REACH-no: 01-2119455540- 44	2.6 – 5.25	Acute Tox. 4 (Oral), H302
beta-lonone	CAS-No.: 14901-07-6 EC-No.: 238-969-9	1.8 – 3.5	Aquatic Chronic 2, H411
Aldehyde C-16	CAS-No.: 77-83-8 EC-No.: 201-061-8 REACH-no: 01-2119967770- 28	1.6 – 3.1	Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Benzyl acetate substance with national workplace exposure limit(s) (BE, DK, ES, IE, LT, LV, PT, RO)	CAS-No.: 140-11-4 EC-No.: 205-399-7 REACH-no: 01-2119638272- 42	1.1 – 2.1	Aquatic Chronic 3, H412
Hexyl cinnamic aldehyde	CAS-No.: 101-86-0 EC-No.: 202-983-3 REACH-no: 01-2119533092- 50	0.9 – 1.75	Skin Sens. 1, H317 Aquatic Chronic 2, H411

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Orange oil	CAS-No.: 8008-57-9 EC-No.: 232-433-8 REACH-no: 01-2119493353- 35	0.9 – 1.75	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Oxypheylon (Raspberry ketone) crystals	CAS-No.: 5471-51-2 EC-No.: 226-806-4	0.5 – 1	Acute Tox. 4 (Oral), H302
alpha-lonone	CAS-No.: 127-41-3 EC-No.: 204-841-6 REACH-no: 01-2119965149- 27	0.5 – 1	Aquatic Chronic 3, H412
Ethyl acetoacetate substance with national workplace exposure limit(s) (RO)	CAS-No.: 141-97-9 EC-No.: 205-516-1	0.4 - 0.7	Not classified
Geranyl acetate	CAS-No.: 105-87-3 EC-No.: 203-341-5 REACH-no: 01-2119973480- 35	0.1 – 0.25	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Isoamyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, DE, DK, EE, ES, FI, FR, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, TR); substance with a Community workplace exposure limit	CAS-No.: 123-92-2 EC-No.: 204-662-3 EC Index-No.: 607-130-00-2 REACH-no: 01-2119548408- 32	0.1 – 0.2	Flam. Liq. 3, H226
Citronellol Pure	CAS-No.: 106-22-9 EC-No.: 203-375-0 REACH-no: 01-2119453995- 23	0.1 – 0.15	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
beta-Caryophyllene	CAS-No.: 87-44-5 EC-No.: 201-746-1 REACH-no: 01-2120745237- 53	0.1 – 0.15	Skin Sens. 1B, H317 Asp. Tox. 1, H304
Triplal (Vertocitral)	CAS-No.: 68039-49-6 EC-No.: 268-264-1	0.1 – 0.1168	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412
decyl alcohol substance with national workplace exposure limit(s) (BG, DE, LT, LV, RO, CH)	CAS-No.: 112-30-1 EC-No.: 203-956-9	0 – 0.0014	Aquatic Chronic 3, H412
Aldehyde C-6 substance with national workplace exposure limit(s) (FI, PL)	CAS-No.: 66-25-1 EC-No.: 200-624-5	0 – 0.0004	Flam. Liq. 3, H226

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a poison center or a doctor if you feel unwell.

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Do NOT induce vomiting. Obtain emergency medical attention. Rinse mouth. Call a poison center or a doctor if you feel unwell.
4.2. Most important symptoms and ef	fects, both acute and delayed
Symptoms/effects Symptoms/effects after skin contact	 Not expected to present a significant hazard under anticipated conditions of normal use. May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media Unsuitable extinguishing media	Sand. Water spray. Dry powder. Foam. Carbon dioxide.Do not use a heavy water stream.	
5.2. Special hazards arising from the substance or mixture		
Hazardous decomposition products in case of fire	: Toxic fumes may be released.	
5.3. Advice for firefighters		
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.	
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.	

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective	equipment and emergency procedures	
6.1.1. For non-emergency personnel		
Emergency procedures	: Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.	
6.1.2. For emergency responders		
Protective equipment	Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".	
Emergency procedures	: Ventilate area.	
6.2. Environmental precautions		

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up		
For containment	: Collect spillage.	
Methods for cleaning up	: Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.	
Other information	: Dispose of materials or solid residues at an authorized site.	

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage	ge	
7.1. Precautions for safe handling		
Precautions for safe handling	: Ensure good ventilation of the work station. Wash hands and other exposed areas with mile soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.	
Hygiene measures	: Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.	
7.2. Conditions for safe storage, including any incompatibilities		
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Store in a well-ventilated place. Keep cool.	
Incompatible products	: Strong bases. Strong acids.	
Incompatible materials	: Sources of ignition. Direct sunlight.	
Storage temperature	: 25 °C	
Storage area	: Store in a well-ventilated place. Store away from heat.	
Special rules on packaging	: Store in a closed container.	
Packaging materials	: Do not store in corrodable metal.	

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Benzaldehyde (100-52-7)		
Bulgaria - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Finland - Occupational Exposure Limits		
HTP (OEL TWA) [1]	4.4 mg/m ³	
HTP (OEL TWA) [2]	1 ppm	
HTP (OEL C)	17.4 mg/m³	
HTP (OEL C) [ppm]]	4 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³	
CK (OEL STEL)	10 mg/m ³	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	

Benzaldehyde (100-52-7)		
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	10 mg/m³	
NDSCh (OEL STEL)	40 mg/m ³	
Benzyl acetate (140-11-4)	·	
Belgium - Occupational Exposure Limits		
OEL TWA	62 mg/m³	
OEL TWA [ppm]	10 ppm	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	61 mg/m³	
OEL TWA [2]	10 ppm	
OEL STEL	122 mg/m³	
OEL STEL [ppm]	20 ppm	
Ireland - Occupational Exposure Limits		
OEL TWA [2]	10 ppm	
OEL STEL [ppm]	30 ppm (calculated)	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA [ppm]	10 ppm	
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen	
Romania - Occupational Exposure Limits		
OEL TWA	50 mg/m³	
OEL TWA [ppm]	8 ppm	
OEL STEL	80 mg/m³	
OEL STEL [ppm]	13 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	62 mg/m³	
VLA-ED (OEL TWA) [2]	10 ppm	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	10 ppm	
ACGIH chemical category	Not Classifiable as a Human Carcinogen	
Ethyl acetoacetate (141-97-9)		
Romania - Occupational Exposure Limits		
OEL TWA	100 mg/m³	
OEL TWA [ppm]	19 ppm	
OEL STEL	200 mg/m ³	

Ethyl acetoacetate (141-97-9)		
OEL STEL [ppm]	38 ppm	
Isoamyl acetate (123-92-2)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	270 mg/m³	
IOEL TWA [ppm]	50 ppm	
IOEL STEL	540 mg/m³	
IOEL STEL [ppm]	100 ppm	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	270 mg/m³ (Pentyl acetate (all isomers))	
MAK (OEL TWA) [ppm]	50 ppm (Pentyl acetate (all isomers))	
MAK (OEL STEL)	540 mg/m ³ (Pentylacetate)	
MAK (OEL STEL) [ppm]	100 ppm (Pentylacetate)	
Belgium - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Bulgaria - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Croatia - Occupational Exposure Limits		
GVI (OEL TWA) [1]	270 mg/m³	
GVI (OEL TWA) [2]	50 ppm	
KGVI (OEL STEL)	540 mg/m³	
KGVI (OEL STEL) [ppm]	100 ppm	
Cyprus - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	271 mg/m³ (Amyl acetate, all isomers)	
OEL TWA [2]	50 ppm (Amyl acetate, all isomers)	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Estonia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	

Isoamyl acetate (123-92-2)	Isoamyl acetate (123-92-2)		
OEL TWA [ppm]	50 ppm		
OEL STEL	540 mg/m³		
OEL STEL [ppm]	100 ppm		
Finland - Occupational Exposure Limits			
HTP (OEL TWA) [1]	270 mg/m³ (Pentyl acetate)		
HTP (OEL TWA) [2]	50 ppm (Pentyl acetate)		
HTP (OEL STEL)	540 mg/m³		
HTP (OEL STEL) [ppm]	100 ppm		
France - Occupational Exposure Limits			
VME (OEL TWA)	270 mg/m³ (restrictive limit)		
VME (OEL TWA) [ppm]	50 ppm (restrictive limit)		
VLE (OEL C/STEL)	540 mg/m³ (restrictive limit)		
VLE (OEL C/STEL) [ppm]	100 ppm (restrictive limit)		
Germany - Occupational Exposure Limits (TRGS 90	0)		
AGW (OEL TWA) [1]	270 mg/m³		
AGW (OEL TWA) [2]	50 ppm		
Gibraltar - Occupational Exposure Limits			
OEL TWA	270 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL STEL	540 mg/m³		
OEL STEL [ppm]	100 ppm		
Greece - Occupational Exposure Limits			
OEL TWA	530 mg/m³		
OEL TWA [ppm]	100 ppm		
OEL STEL	800 mg/m³		
OEL STEL [ppm]	150 ppm		
Hungary - Occupational Exposure Limits			
AK (OEL TWA)	270 mg/m³		
CK (OEL STEL)	540 mg/m³		
Ireland - Occupational Exposure Limits			
OEL TWA [1]	260 mg/m³		
OEL TWA [2]	50 ppm		
OEL STEL	520 mg/m³		
OEL STEL [ppm]	100 ppm		
Italy - Occupational Exposure Limits			
OEL TWA	270 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL STEL	540 mg/m³		
OEL STEL [ppm]	100 ppm		

Isoamyl acetate (123-92-2)		
Latvia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	270 mg/m³	
IPRV (OEL TWA) [ppm]	50 ppm	
TPRV (OEL STEL)	540 mg/m ³	
TPRV (OEL STEL) [ppm]	100 ppm	
Luxembourg - Occupational Exposure Limits		
OEL TWA	270 mg/m ³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m ³	
OEL STEL [ppm]	100 ppm	
Malta - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Netherlands - Occupational Exposure Limits		
TGG-15min (OEL STEL)	530 mg/m³	
TGG-15min (OEL STEL) [ppm]	98.1 ppm	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	250 mg/m³	
NDSCh (OEL STEL)	500 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	270 mg/m³ (indicative limit value)	
OEL TWA [ppm]	50 ppm (indicative limit value (Pentyl acetate, all isomers)	
OEL STEL	540 mg/m³ (indicative limit value)	
OEL STEL [ppm]	100 ppm (indicative limit value)	
Romania - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA) [1]	270 mg/m³	
NPHV (OEL TWA) [2]	50 ppm	
NPHV (OEL C)	540 mg/m³	

Isoamyl acetate (123-92-2)		
Slovenia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	270 mg/m³ (indicative limit value)	
VLA-ED (OEL TWA) [2]	50 ppm (indicative limit value)	
VLA-EC (OEL STEL)	540 mg/m³	
VLA-EC (OEL STEL) [ppm]	100 ppm	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	270 mg/m³ (Pentyl acetates)	
NGV (OEL TWA) [ppm]	50 ppm (Pentyl acetates)	
KTV (OEL STEL)	540 mg/m³ (Pentyl acetates)	
KTV (OEL STEL) [ppm]	100 ppm (Pentyl acetates)	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA) [1]	260 mg/m ³	
Grenseverdi (OEL TWA) [2]	50 ppm	
Korttidsverdi (OEL STEL)	325 mg/m³ (value calculated)	
Korttidsverdi (OEL STEL) [ppm]	75 ppm (value calculated)	
USA - ACGIH - Occupational Exposure Limits	·	
ACGIH OEL TWA [ppm]	50 ppm (Pentyl acetate, all isomers)	
ACGIH OEL STEL [ppm]	100 ppm (Pentyl acetate, all isomers)	
decyl alcohol (112-30-1)	·	
Bulgaria - Occupational Exposure Limits		
OEL TWA	10 mg/m³	
Germany - Occupational Exposure Limits (TRGS 90)0)	
AGW (OEL TWA) [1]	66 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
AGW (OEL TWA) [2]	10 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
Latvia - Occupational Exposure Limits		
OEL TWA	10 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	10 mg/m³	
Romania - Occupational Exposure Limits		
OEL TWA	100 mg/m ³	
OEL TWA [ppm]	15 ppm	
OEL STEL	200 mg/m³	

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

decyl alcohol (112-30-1)		
OEL STEL [ppm]	30 ppm	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA) [1]	66 mg/m³ (aerosol, vapour)	
MAK (OEL TWA) [2]	10 ppm (aerosol, vapour)	
KZGW (OEL STEL)	66 mg/m³ (aerosol, vapour)	
KZGW (OEL STEL) [ppm]	10 ppm (aerosol, vapour)	
Aldehyde C-6 (66-25-1)		
Finland - Occupational Exposure Limits		
HTP (OEL STEL)	42 mg/m³	
HTP (OEL STEL) [ppm]	10 ppm	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	40 mg/m ³	
NDSCh (OEL STEL)	80 mg/m³	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection: Chemical goggles or safety glasses. Safety glasses

8.2.2.2. Skin protection

Skin and body protection: Wear suitable protective clothing

Hand protection:

Protective gloves. Wear protective gloves.

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light yellow. amber. Conforms to standard.
Odour	: characteristic. characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 86 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
рН	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: ≈ 0.93
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions. Not established.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Not established.

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008		
Acute toxicity (dermal) :	Harmful if swallowed. Not classified Not classified	
ATE CLP (oral)	678.127 mg/kg bodyweight	
Benzyl benzoate (120-51-4)		
LD50 oral rat	500 mg/kg (Source: NLM_CIP)	
LD50 oral	1160 mg/kg bodyweight	
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)	
Benzaldehyde (100-52-7)		
LD50 oral rat	1292 mg/kg (Source: JAPAN_GHS)	
LD50 dermal rabbit	> 1250 mg/kg (Source: JAPAN_GHS)	
beta-lonone (14901-07-6)		
LD50 oral rat	4590 mg/kg (Source: NLM_HSDB)	
LD50 oral	3940 mg/kg bodyweight	
Aldehyde C-16 (77-83-8)		
LD50 oral rat	5470 mg/kg (Source: NLM_CIP)	
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)	
Benzyl acetate (140-11-4)		
LD50 oral rat	2490 mg/kg (Source: JAPAN_GHS)	
LD50 oral	2490 mg/kg bodyweight	
LD50 dermal rabbit	> 5000 mg/kg (Source: JAPAN_GHS)	
Hexyl cinnamic aldehyde (101-86-0)		
LD50 oral rat	3100 mg/kg (Source: NLM_CIP)	
LD50 oral	3100 mg/kg bodyweight	
LD50 dermal rabbit	> 3000 mg/kg (Source: EPA_HPV)	
LC50 Inhalation - Rat	> 5 mg/l/4h	
Orange oil (8008-57-9)		
LD50 oral rat	4400 mg/kg (Source: NZ_CCID)	
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)	

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Oxypheylon (Raspberry ketone) crystals (547	Oxypheylon (Raspberry ketone) crystals (5471-51-2)	
LD50 oral rat	1320 mg/kg (Source: NLM_CIP)	
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)	
alpha-lonone (127-41-3)	·	
LD50 oral	4590 mg/kg bodyweight	
Ethyl acetoacetate (141-97-9)	·	
LD50 oral rat	3980 mg/kg (Source: NLM_CIP)	
LD50 dermal rabbit	> 5000 mg/kg (Source: NLM_CIP)	
Geranyl acetate (105-87-3)		
LD50 oral rat	6330 mg/kg (Source: NLM_CIP)	
Citronellol Pure (106-22-9)		
LD50 oral rat	3450 mg/kg (Source: NLM_CIP)	
LD50 oral	3450 mg/kg bodyweight	
LD50 dermal rabbit	2650 mg/kg (Source: EPA_HPV)	
LD50 dermal	2650 mg/kg bodyweight	
Triplal (Vertocitral) (68039-49-6)		
LD50 oral	3900 mg/kg bodyweight	
decyl alcohol (112-30-1)		
LD50 oral rat	4720 mg/kg (Source: NZ_CCID)	
LD50 dermal rabbit	3560 mg/kg (Source: NLM_CIP)	
Aldehyde C-6 (66-25-1)		
LD50 oral rat	4890 mg/kg (Source: NLM_CIP)	
LD50 dermal rabbit	> 8100 mg/kg (Source: ECHA_API)	
Skin corrosion/irritation :	Not classified	
Serious eye damage/irritation :	Not classified	
Respiratory or skin sensitisation : Germ cell mutagenicity :	May cause an allergic skin reaction. Not classified	
Carcinogenicity :	Not classified	
Benzyl acetate (140-11-4)		
IARC group	3 - Not classifiable	
Reproductive toxicity :	Not classified	
STOT-single exposure :	Not classified	
STOT-repeated exposure :	Not classified	
Aspiration hazard :	Not classified	
Benzyl benzoate (120-51-4)		
Viscosity, kinematic	7.456 mm²/s	
Orange oil (8008-57-9)		
Hydrocarbon	Yes	
11.2. Information on other hazards		
11.2.1. Endocrine disrupting properties		

11.2.1. Endocrine disrupting properties

No additional information available

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2.2. Other information

Potential adverse human health effects and symptoms

: Based on available data, the classification criteria are not met

SECTION 12: Ecological information		
12.1. Toxicity		
Ecology - general Hazardous to the aquatic environment, short–term acute)	: Harmful to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects : Not classified	
Hazardous to the aquatic environment, long–term chronic)	: Toxic to aquatic life with long lasting effects.	
Benzyl benzoate (120-51-4)		
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)	
NOEC (chronic)	0.168 mg/l	
Benzaldehyde (100-52-7)		
LC50 - Fish [1]	10.6 – 11.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through] Source: EPA)	
LC50 - Fish [2]	12.69 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: IUCLID)	
Aldehyde C-16 (77-83-8)		
LC50 - Fish [1]	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static] Source: ECHA)	
Ethyl acetoacetate (141-97-9)		
LC50 - Fish [1]	298 mg/l (Exposure time: 96 h - Species: Pimephales promelas Source: IUCLID)	
LC50 - Fish [2]	290 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: IUCLID)	
EC50 - Crustacea [1]	646 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 72h - Algae [1]	> 500 mg/l (Species: Desmodesmus subspicatus)	
decyl alcohol (112-30-1)		
LC50 - Fish [1]	2.2 – 2.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
LC50 - Fish [2]	4.12 – 6.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)	
EC50 - Crustacea [1]	3 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
Aldehyde C-6 (66-25-1)		
LC50 - Fish [1]	12 – 16.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
12.2. Persistence and degradability		

Persistence and degradability	Not established.
Benzyl benzoate (120-51-4)	
Persistence and degradability	May cause long-term adverse effects in the environment.

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.3. Bioaccumulative potential	12.3. Bioaccumulative potential	
Bioaccumulative potential	Not established.	
Benzyl benzoate (120-51-4)		
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)	
Bioaccumulative potential	Not established.	
Benzaldehyde (100-52-7)		
BCF - Fish [1]	(no significant bioaccumulation)	
Partition coefficient n-octanol/water (Log Pow)	1.4 (at 25 °C)	
beta-lonone (14901-07-6)		
Partition coefficient n-octanol/water (Log Pow)	1.903 (at 27 °C (at pH 5.7)	
Aldehyde C-16 (77-83-8)		
Partition coefficient n-octanol/water (Log Pow)	2.4 (at 25 °C (cis isomer)	
Benzyl acetate (140-11-4)		
Partition coefficient n-octanol/water (Log Pow)	1.96 (at 25 °C (at pH 7)	
Oxypheylon (Raspberry ketone) crystals (54	71-51-2)	
Partition coefficient n-octanol/water (Log Pow)	1.33 (at 20 °C)	
alpha-lonone (127-41-3)		
Partition coefficient n-octanol/water (Log Pow)	3.896 (at 25 °C (at pH 7.2)	
Ethyl acetoacetate (141-97-9)		
Partition coefficient n-octanol/water (Log Pow)	0.8 (at 20 °C)	
Geranyl acetate (105-87-3)		
Partition coefficient n-octanol/water (Log Pow)	4.04	
Isoamyl acetate (123-92-2)		
Partition coefficient n-octanol/water (Log Pow)	2.7 (at 35 °C)	
Citronellol Pure (106-22-9)		
Partition coefficient n-octanol/water (Log Pow)	3.41 (at 25 °C)	
beta-Caryophyllene (87-44-5)		
Partition coefficient n-octanol/water (Log Pow)	6.23 (at 25 °C (at pH 7)	
decyl alcohol (112-30-1)		
Partition coefficient n-octanol/water (Log Pow)	4.5 (at 25 °C (at pH 6)	
Aldehyde C-6 (66-25-1)		
Partition coefficient n-octanol/water (Log Pow)	2.3 (at 25 °C (at pH 5)	
12.4. Mobility in soil		
No additional information available		
12.5. Results of BPT and vPvP assessment		

12.5. Results of PBT and vPvB assessment

No additional information available

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information

: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods	
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.
HP Code	: HP3 - "Flammable:"
	 – flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;

uid waste having a flash point below 60 °C or waste gas oil, aving a flash point > 55 °C and \leq 75 °C; - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;

- flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;

- flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
- water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;

- other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number or ID n	umber	· · · · · · · · · · · · · · · · · · ·		1
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shippin	g name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate)	Environmentally hazardous substance, liquid, n.o.s. (Benzyl benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate)
Transport document descr	iption			-
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Benzyl benzoate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl benzoate), 9, III
14.3. Transport hazard o	class(es)			
9	9	9	9	9

ADR	IMDG		ΙΑΤΑ	ADN	RID
				ADN	
14.4. Packing group					1
111	111		III	111	111
14.5. Environmental haz	ards		·	·	
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Ye		Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary informatic	on available				
14.6. Special precaution	s for user				
Overland transport					
Classification code (ADR) Special provisions (ADR) Limited quantities (ADR) Excepted quantities (ADR) Packing instructions (ADR) Special packing provisions (A Mixed packing provisions (AD Portable tank and bulk contain Portable tank and bulk contain (ADR) Tank code (ADR) Vehicle for tank carriage Transport category (ADR) Special provisions for carriage Special provisions for carriage and handling (ADR) Hazard identification number Orange plates	DR) PR) ner instructions (ADR) ner special provisions e - Packages (ADR) e - Loading, unloading (Kemler No.)	: 5I : E1 : P00 : PP : MPP : T4 : T7 : LG : AT : CV : 90 : 90 : -	4, 335, 375, 601 01, IBC03, LP01, R001 1 19 1, TP29 BV 2 13 90 3082		
EAC code Transport by sea Special provisions (IMDG) Limited quantities (IMDG) Excepted quantities (IMDG) Packing instructions (IMDG) Special packing provisions (IMD IBC packing instructions (IMDG) Tank instructions (IMDG) Tank special provisions (IMDG) Tank special provisions (IMDG) EmS-No. (Fire) EmS-No. (Spillage) Stowage category (IMDG)	ИDG))G) G)	: 5 L : E1 : LP(: PP : IBC : T4	4, 335, 969 01, P001 1 C03 1, TP29		
Air transport PCA Excepted quantities (IAT PCA Limited quantities (IATA PCA limited quantity max net PCA packing instructions (IAT) quantity (IATA)	: E1 : Y96 : 306 : 964	кgG		

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provisions (IATA)	: A97, A158, A197, A215
ERG code (IATA)	: 9L
Inland waterway transport	
Classification code (ADN)	: M6
Special provisions (ADN)	: 274, 335, 375, 601
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: Т
Equipment required (ADN)	: PP
Number of blue cones/lights (ADN)	: 0
Rail transport	
Classification code (RID)	: M6
Special provisions (RID)	: 274, 335, 375, 601
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions	: TP1, TP29
(RID)	
Tank codes for RID tanks (RID)	: LGBV
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Special provisions for carriage - Loading, unloading	: CW13, CW31
and handling (RID)	
Colis express (express parcels) (RID)	: CE8
Hazard identification number (RID)	: 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	Orange oil ; Isoamyl acetate ; Aldehyde C-6	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	; Benzyl benzoate ; Benzaldehyde ; Aldehyde C-16 ; Hexyl cinnamic aldehyde ; Orange oil ; Geranyl acetate ; Citronellol Pure ; Triplal (Vertocitral)	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(c)	; Benzyl benzoate ; beta-lonone ; Aldehyde C-16 ; Benzyl acetate ; Hexyl cinnamic aldehyde ; Orange oil ; alpha-lonone ; Geranyl acetate ; Triplal (Vertocitral) ; decyl alcohol	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	Orange oil ; Isoamyl acetate ; Aldehyde C-6	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases			
Code	Description		
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide		
Germany			
Employment restrictions	: Observe restrictions according Act on the Protection of Working Mothers (MuSchG).		
	Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).		

	(JAIDSCHG).
Water hazard class (WGK)	: WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV)	: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Netherlands

ABM category	: A(1) - highly toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment
SZW-lijst van kankerverwekkende stoffen	: Orange oil ,Triplal (Vertocitral) are listed
SZW-lijst van mutagene stoffen	: Orange oil ,Triplal (Vertocitral) are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: None of the components are listed
Denmark	
Class for fire hazard	: Class III-1
Store unit	: 50 liter
Classification remarks	: Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product
	Pregnant/breastfeeding women working with the product must not be in direct contact with the product
15.2. Chemical safety assessment	

No chemical safety assessment has been carried out

SECTION 16: Other information

Other information

: None.

Full text of H- and EUH-statements:		
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3	
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
H226	Flammable liquid and vapour.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H400	Very toxic to aquatic life.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	
Skin Sens. 1B	Skin sensitisation, category 1B	

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.