



Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 9/6/2021 Revision date: 11/20/2024 Supersedes version of: 10/23/2024 Version: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Trade name	: Baby Powder
UFI	: 5MYN-QCN8-V006-NUAG
Product code	: parf_baby_powder
Type of product	: Perfumes, fragrances
Product group	: Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	: Industrial use, Professional use
Industrial/Professional use spec	: For professional use only Industrial
Use of the substance/mixture	: Perfumes, fragrances
Function or use category	: Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

BAKED GAMES SRL
ROMANIA, BUCHAREST, SECTOR 4
+40771326626
contact@kitlumanari.ro | www.kitlumanari.ro

1.4. Emergency telephone number

Emergency number	: 1-800-255-3924; +01-813-248-0585; China: +400-120-0751; Mexico: +01-800-099-0731; Brazil: +0-800-591-6042; India: +000-800-100-4086
------------------	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4	H302
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment – Acute Hazard, Category 1	H400
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411
Full text of H- and EUH-statements: see section 16	

Adverse physicochemical, human health and environmental effects

Harmful if swallowed. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

GHS09

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Signal word (CLP)	: Warning
Contains	: benzyl benzoate; COUMARIN; Citronellol Pure; Patchouli oil; Veratryl aldehyde (Veratraldehyde); Phenylethyl alcohol; Geraniol; Nerol; (E)-3-methyl-5-cyclopentadecen-1-one
Hazard statements (CLP)	: H302 - Harmful if swallowed. H317 - May cause an allergic skin reaction. H410 - Very toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
Extra phrases	: For professional users only.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371-33	41.4 – 82.7	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Anisic aldehyde	CAS-No.: 123-11-5 EC-No.: 204-602-6 REACH-no: 01-2119977101-43	1.296 – 2.506	Aquatic Chronic 3, H412
Methyl ionone (mixture of isomers)	CAS-No.: 1335-46-2 EC-No.: 215-635-0	1.1 – 2.15	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 2, H411
COUMARIN	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756-26	0.9 – 1.75	Acute Tox. 4 (Oral), H302 Skin Sens. 1B, H317
Citronellol Pure	CAS-No.: 106-22-9 EC-No.: 203-375-0 REACH-no: 01-2119453995-23	0.809035 – 1.5250725	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Patchouli oil	CAS-No.: 8014-09-3 EC-No.: 616-944-7 EC Index-No.: 616-944-7	0.8 – 1.5	Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ethyl vanillin	CAS-No.: 121-32-4 EC-No.: 204-464-7 REACH-no: 01-211958961-24	0.511298 – 1.023403	Eye Irrit. 2, H319
Phenylethyl alcohol	CAS-No.: 60-12-8 EC-No.: 200-456-2 REACH-no: 01-2119963921-31	0.5 – 1	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319
Benzyl acetate substance with national workplace exposure limit(s) (BE, DK, ES, IE, LT, LV, PT, RO)	CAS-No.: 140-11-4 EC-No.: 205-399-7 REACH-no: 01-2119638272-42	0.4 – 0.75	Aquatic Chronic 3, H412
ACETYL HEXAMETHYL TETRALIN	CAS-No.: 21145-77-7 EC-No.: 244-240-6	0.2 – 0.4	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Veratryl aldehyde (Veratraldehyde)	CAS-No.: 120-14-9 EC-No.: 204-373-2	0.175 – 0.3625	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317
Geraniol	CAS-No.: 106-24-1 EC-No.: 203-377-1 EC Index-No.: 603-241-00-5 REACH-no: 01-2119552430-49	0.15 – 0.35	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317
Nerol	CAS-No.: 106-25-2 EC-No.: 203-378-7	0.09 – 0.25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
para-Cresyl methyl ether	CAS-No.: 104-93-8 EC-No.: 203-253-7	0.1 – 0.1	Acute Tox. 4 (Oral), H302 Repr. 2, H361 Skin Irrit. 2, H315
(E)-3-methyl-5-cyclopentadecen-1-one	CAS-No.: 82356-51-2 EC-No.: 429-900-5 EC Index-No.: 606-119-00-X	0.1 – 0.1	Skin Sens. 1B, H317 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
citral substance with national workplace exposure limit(s) (BE, ES, IE, PL, PT)	CAS-No.: 5392-40-5 EC-No.: 226-394-6 EC Index-No.: 605-019-00-3 REACH-no: 01-2119462829-23	0.003 – 0.015	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	0.001778 – 0.003683	Not classified
Toluene substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3	≤ 0.0000435	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of H- and EUH-statements: see section 16

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Wash with plenty of water/.... If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instruction on this label). Wash contaminated clothing before reuse. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Obtain emergency medical attention. Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Sand. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate area.

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- | | |
|-------------------------|--|
| For containment | : Collect spillage. |
| Methods for cleaning up | : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. |
| Other information | : Dispose of materials or solid residues at an authorized site. |

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- | | |
|-------------------------------|---|
| Precautions for safe handling | : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment. |
| Hygiene measures | : Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. |

7.2. Conditions for safe storage, including any incompatibilities

- | | |
|----------------------------|---|
| Storage conditions | : Keep only in the original container in a cool, well ventilated place away from : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Store in a well-ventilated place. Keep cool. |
| Incompatible products | : Strong bases. Strong acids. |
| Incompatible materials | : Sources of ignition. Direct sunlight. |
| Storage temperature | : 25 °C |
| Storage area | : Store in a well-ventilated place. Store away from heat. |
| Special rules on packaging | : Store in a closed container. |
| Packaging materials | : Do not store in corrodable metal. |

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Toluene (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	192 mg/m ³
	50 ppm
IOEL STEL	384 mg/m ³
	100 ppm
Remark	Possibility of significant uptake through the skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	190 mg/m ³

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
	50 ppm
MAK (OEL STEL)	380 mg/m ³
	100 ppm
OEL chemical category	Skin notation
Belgium - Occupational Exposure Limits	
OEL TWA	77 mg/m ³
	20 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Skin, Skin notation
Bulgaria - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
Bulgaria - Biological limit values	
BLV	1.6 mmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of exposure or end of work shift
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	192 mg/m ³
	50 ppm
KGVl (OEL STEL)	384 mg/m ³
	100 ppm
OEL chemical category	Skin notation
Croatia - Biological limit values	
BLV	1 mg/l Parameter: Toluene - Medium: blood - Sampling time: at the end of the work shift 20 ppm Parameter: Toluene - Medium: final exhaled air - Sampling time: during exposure 2.5 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine) 1 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine)
Cyprus - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	200 mg/m ³
OEL chemical category	Potential for cutaneous absorption

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
Czech Republic - Biological limit values	
BLV	1.6 µmol/mmol Creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1000 µmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.) 1.5 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1600 mg/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.)
Denmark - Occupational Exposure Limits	
OEL TWA	94 mg/m ³
	25 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Skin notation
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	81 mg/m ³
	25 ppm
HTP (OEL STEL)	380 mg/m ³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Finland - Biological limit values	
BLV	500 nmol/L Parameter: Toluene - Medium: blood - Sampling time: in the morning after a working day
France - Occupational Exposure Limits	
VME (OEL TWA)	76.8 mg/m ³ (restrictive limit)
	20 ppm (restrictive limit)
VLE (OEL C/STEL)	384 mg/m ³ (restrictive limit)
	100 ppm (restrictive limit)
OEL chemical category	Reproductive Toxin category 2, Risk of cutaneous absorption

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
France - Biological limit values	
BLV	20 µg/l Parameter: Toluene - Medium: blood - Sampling time: end of workweek (Semi-quantitative (ambiguous interpretation)) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (per the Authority, the values for this substance must be decided and/or determined on a case by case basis. Guidance for the calculation of and interpretation of values is provided in the source)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	190 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	50 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Chemical category	Skin notation
Germany - Biological limit values (TRGS 903)	
Biological limit value	600 µg/l Parameter: Toluene - Medium: whole blood - Sampling time: immediately after exposure 75 µg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 1.5 mg/l Parameter: o-Cresol (after hydrolysis) - Medium: urine - Sampling time: for long-term exposures: at the end of the shift after several shifts 1.5 mg/l Parameter: o-Cresol (after hydrolysis) - Medium: urine - Sampling time: end of shift
Gibraltar - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Skin notation
Greece - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	skin - potential for cutaneous absorption
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	190 mg/m ³
CK (OEL STEL)	384 mg/m ³
OEL chemical category	Potential for cutaneous absorption
Ireland - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Potential for cutaneous absorption

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
Italy - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	50 mg/m ³
	14 ppm
OEL chemical category	skin - potential for cutaneous exposure
Latvia - Biological Exposure Indices	
BEI	1.6 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift 0.05 mg/l Parameter: Toluene - Medium: blood - Sampling time: end of shift
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	192 mg/m ³
	50 ppm
TPRV (OEL STEL)	384 mg/m ³
	100 ppm
OEL chemical category	Reproductive toxin, Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	150 mg/m ³
	39 ppm
TGG-15min (OEL STEL)	384 mg/m ³
	100 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	100 mg/m ³
NDSch (OEL STEL)	200 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA	192 mg/m ³ (indicative limit value)

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
	50 ppm (indicative limit value)
OEL STEL	384 mg/m ³ (indicative limit value)
	100 ppm (indicative limit value)
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Skin notation
Romania - Biological limit values	
BLV	2 g/l Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift 3 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	192 mg/m ³
	50 ppm
NPHV (OEL C)	384 mg/m ³ (also biological monitoring considered)
OEL chemical category	Potential for cutaneous absorption
Slovakia - Biological limit values	
BLV	600 µg/l Parameter: Toluene - Medium: blood - Sampling time: end of exposure or work shift 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: after all work shifts (for long-term exposure) 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of exposure or work shift 2401 mg/g creatinine Parameter: Hippuric acid - Sampling time: end of exposure or work shift
Slovenia - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Category 2, Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	192 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value)
VLA-EC (OEL STEL)	384 mg/m ³
	100 ppm
OEL chemical category	skin - potential for cutaneous absorption

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
Spain - Biological limit values	
BLV	0.6 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift 0.05 mg/l Parameter: Toluene - Medium: blood - Sampling time: start of last shift of workweek 0.08 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	192 mg/m ³
	50 ppm
KGV (OEL STEL)	384 mg/m ³
	100 ppm
OEL chemical category	Skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	191 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	384 mg/m ³
	100 ppm
WEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	94 mg/m ³
	25 ppm
Korttidsverdi (OEL STEL)	141 mg/m ³ (value calculated)
	37.5 ppm (value calculated)
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	190 mg/m ³
	50 ppm
KZGW (OEL STEL)	760 mg/m ³
	200 ppm
OEL chemical category	Skin notation, Category 2 reproductive toxin
Switzerland - BAT	
BAT	600 µg/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 6.48 µmol/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 2 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 0.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 4.62 µmol/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 75 µg/l Parameter: Toluol - Medium: urine - Sampling time: end of shift
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	20 ppm

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI	0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 0.3 mg/g creatinine Parameter: o-Cresol with hydrolysis - Medium: urine - Sampling time: end of shift (background)
Dipropylene glycol monomethyl ether (34590-94-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	308 mg/m ³
	50 ppm
Remark	Possibility of significant uptake through the skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	307 mg/m ³ (mixed isomers)
	50 ppm (mixed isomers)
MAK (OEL STEL)	614 mg/m ³ (isomers mixtures)
	100 ppm (isomers mixtures)
OEL chemical category	Skin notation
Belgium - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Skin, Skin notation
Bulgaria - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	308 mg/m ³
	50 ppm
OEL chemical category	Skin notation
Cyprus - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	270 mg/m ³
OEL chemical category	Potential for cutaneous absorption
Denmark - Occupational Exposure Limits	
OEL TWA	309 mg/m ³
	50 ppm
OEL STEL	618 mg/m ³

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Skin notation
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	310 mg/m ³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
France - Occupational Exposure Limits	
VME (OEL TWA)	308 mg/m ³ (restrictive limit)
	50 ppm (restrictive limit)
OEL chemical category	Risk of cutaneous absorption
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	310 mg/m ³ (isomer mixture)
	50 ppm (isomer mixture)
Gibraltar - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Skin notation
Greece - Occupational Exposure Limits	
OEL TWA	600 mg/m ³
	100 ppm
OEL STEL	900 mg/m ³
	150 ppm
OEL chemical category	skin - potential for cutaneous absorption
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	308 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA	308 mg/m ³ ((2-Methoxymethylethoxy)propanol)
	50 ppm ((2-Methoxymethylethoxy)propanol)
OEL STEL	924 mg/m ³ (calculated (2-(2-Methoxypropoxy)-1-propanol)
	150 ppm (calculated (2-(2-Methoxypropoxy)-1-propanol)
OEL chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	308 mg/m ³ (1-(3-Methoxypropoxy)propan-1-ol)
	50 ppm (1-(3-Methoxypropoxy)propan-1-ol)
OEL chemical category	skin - potential for cutaneous absorption

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
Latvia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	skin - potential for cutaneous exposure
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	300 mg/m ³ (2-(2-Methoxypropoxy)-propanol)
	50 ppm (2-(2-Methoxypropoxy)-propanol)
TPRV (OEL STEL)	450 mg/m ³ (2-(2-Methoxypropoxy)-propanol)
	75 ppm (2-(2-Methoxypropoxy)-propanol)
OEL chemical category	Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	300 mg/m ³
	48.7 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	240 mg/m ³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
NDSch (OEL STEL)	480 mg/m ³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
Portugal - Occupational Exposure Limits	
OEL TWA	308 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value)
OEL STEL	150 ppm
OEL chemical category	skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Skin notation
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	308 mg/m ³
	50 ppm
OEL chemical category	Potential for cutaneous absorption

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
Slovenia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL STEL	308 mg/m ³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	308 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value)
OEL chemical category	skin - potential for cutaneous absorption
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	300 mg/m ³
	50 ppm
KGV (OEL STEL)	450 mg/m ³
	75 ppm
OEL chemical category	Skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	308 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	924 mg/m ³ (calculated)
	150 ppm (calculated)
WEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	300 mg/m ³
	50 ppm
Korttidsverdi (OEL STEL)	375 mg/m ³ (value calculated)
	75 ppm (value calculated)
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	300 mg/m ³ (aerosol, vapour)
	50 ppm (aerosol, vapour)
KZGW (OEL STEL)	300 mg/m ³ (aerosol, vapour)
	50 ppm (aerosol, vapour)
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	50 ppm (Dipropylene glycol methyl ether)
Benzyl acetate (140-11-4)	
Belgium - Occupational Exposure Limits	
OEL TWA	62 mg/m ³
	10 ppm

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Benzyl acetate (140-11-4)	
Denmark - Occupational Exposure Limits	
OEL TWA	61 mg/m ³
	10 ppm
OEL STEL	122 mg/m ³
	20 ppm
Ireland - Occupational Exposure Limits	
OEL TWA	10 ppm
OEL STEL	30 ppm (calculated)
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	5 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA	10 ppm
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen
Romania - Occupational Exposure Limits	
OEL TWA	50 mg/m ³
	8 ppm
OEL STEL	80 mg/m ³
	13 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	62 mg/m ³
	10 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	10 ppm
ACGIH chemical category	Not Classifiable as a Human Carcinogen
citral (5392-40-5)	
Belgium - Occupational Exposure Limits	
OEL TWA	32 mg/m ³ (vapor and aerosol)
	5 ppm (vapor and aerosol)
OEL chemical category	Skin
Ireland - Occupational Exposure Limits	
OEL TWA	5 ppm
OEL STEL	15 ppm (calculated)
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	27 mg/m ³
NDSch (OEL STEL)	54 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA	5 ppm (inhalable fraction; vapor)

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

citral (5392-40-5)	
OEL chemical category	Sensitizer dermal, A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	5 ppm (inhalable fraction and vapor)
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	5 ppm (inhalable fraction and vapor)
ACGIH chemical category	Not Classifiable as a Human Carcinogen, Skin - potential significant contribution to overall exposure by the cutaneous route, dermal sensitizer

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Conforms to standard.
Odour	: characteristic. characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 93 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 0.000620148 mm Hg (calculated value)
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: ≈ 0.98
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 3.3364115 % (calculated value)(CARB VOC) (%w/w)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Baby Powder	
ATE CLP (oral)	589.896 mg/kg bodyweight
benzyl benzoate (120-51-4)	
LD50 oral rat	> 2000 mg/kg (Source: ECHA_API)
LD50 oral	1160 mg/kg bodyweight
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)
Methyl ionone (mixture of isomers) (1335-46-2)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)
LD50 dermal	2900 mg/kg bodyweight
Anisic aldehyde (123-11-5)	
LD50 oral rat	3210 mg/kg (Source: ECHA)
LD50 oral	3210 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: EPA_HPVS)
LC50 Inhalation - Rat	> 0.32 mg/l (Exposure time: 7 h Source: ECHA)
COUMARIN (91-64-5)	
LD50 oral rat	> 5000 mg/kg (Source: JAPAN_GHS)
LD50 dermal rat	293 mg/kg (Source: ECHA_API)
Citronellol Pure (106-22-9)	
LD50 oral rat	3450 mg/kg (Source: NLM_CIP)
LD50 oral	3450 mg/kg bodyweight
LD50 dermal rabbit	2650 mg/kg (Source: EPA_HPVS)
LD50 dermal	2650 mg/kg bodyweight
Patchouli oil (8014-09-3)	
LD50 oral rat	> 5 g/kg (Source: NLM_CIP)
Veratryl aldehyde (Veratraldehyde) (120-14-9)	
LD50 oral rat	2 g/kg (Source: NLM_CIP)
LD50 oral	2000 mg/kg bodyweight
Toluene (108-88-3)	
LD50 oral rat	2600 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	12000 mg/kg (Source: JAPAN_GHS)

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
LC50 Inhalation - Rat	12.5 mg/l/4h
Dipropylene glycol monomethyl ether (34590-94-8)	
LD50 oral rat	5.35 g/kg (Source: NLM_HSDB)
LD50 dermal rabbit	9500 mg/kg (Source: NLM_CIP)
Ethyl vanillin (121-32-4)	
LD50 oral rat	1590 mg/kg (Source: NLM_CIP)
LD50 oral	3000 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)
Phenylethyl alcohol (60-12-8)	
LD50 oral rat	1609 mg/kg (Source: EPA_HPVS)
LD50 oral	1610 mg/kg
LD50 dermal rabbit	2535 mg/kg (Source: EPA_HPVS)
LC50 Inhalation - Rat	> 4.63 mg/l/4h
Benzyl acetate (140-11-4)	
LD50 oral rat	2490 mg/kg (Source: JAPAN_GHS)
LD50 oral	2490 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: JAPAN_GHS)
Geraniol (106-24-1)	
LD50 oral rat	3600 mg/kg (Source: NLM_CIP)
LD50 oral	3600 mg/kg bodyweight
LD50 dermal rabbit	> 5 g/kg (Source: NLM_CIP)
Nerol (106-25-2)	
LD50 oral rat	4500 mg/kg (Source: NLM_CIP)
LD50 oral	4500 mg/kg bodyweight
LD50 dermal rabbit	> 5 g/kg (Source: NLM_CIP)
citral (5392-40-5)	
LD50 oral rat	4960 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	2250 mg/kg (Source: NLM_CIP)
ACETYL HEXAMETHYL TETRALIN (21145-77-7)	
LD50 oral rat	570 mg/kg (Source: NLM_CIP)
LD50 oral	1000 mg/kg bodyweight
LD50 dermal rabbit	> 5 g/kg (Source: NLM_HSDB)
para-Cresyl methyl ether (104-93-8)	
LD50 oral rat	1920 mg/kg (Source: NLM_CIP)
LD50 oral	1900 mg/kg bodyweight
LD50 dermal rabbit	> 5 g/kg (Source: NLM_CIP)
LC50 Inhalation - Rat	> 6.1 mg/l/4h

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

(E)-3-methyl-5-cyclopentadecen-1-one (82356-51-2)

LD50 oral rat	> 2000 mg/kg (Source: ECHA_API)
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

COUMARIN (91-64-5)

IARC group	3 - Not classifiable
------------	----------------------

Toluene (108-88-3)

IARC group	3 - Not classifiable
------------	----------------------

Benzyl acetate (140-11-4)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

Toluene (108-88-3)

STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified

Toluene (108-88-3)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

benzyl benzoate (120-51-4)

Viscosity, kinematic	7.456 mm²/s
----------------------	-------------

Toluene (108-88-3)

Hydrocarbon	Yes
-------------	-----

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met,Harmful if swallowed.
---	--

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

benzyl benzoate (120-51-4)

LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
NOEC (chronic)	0.168 mg/l

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methyl ionone (mixture of isomers) (1335-46-2)	
LC50 - Fish [1]	2.3 mg/l (Exposure time: 96 h - Species: Danio rerio [static] Source: ECHA)
Toluene (108-88-3)	
LC50 - Fish [1]	15.22 – 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
EC50 - Crustacea [1]	5.46 – 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 - Crustacea [2]	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	12.5 mg/l (Species: Pseudokirchneriella subcapitata [static])
EC50 96h - Algae [1]	> 433 mg/l (Species: Pseudokirchneriella subcapitata)
Dipropylene glycol monomethyl ether (34590-94-8)	
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Ethyl vanillin (121-32-4)	
LC50 - Fish [1]	81.4 – 94.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
Phenylethyl alcohol (60-12-8)	
EC50 - Crustacea [1]	287.17 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	490 mg/l (Species: Desmodesmus subspicatus)
Geraniol (106-24-1)	
LC50 - Fish [1]	22 mg/l (Exposure time: 96 h - Species: Danio rerio [static] Source: ECHA)
Nerol (106-25-2)	
LC50 - Fish [1]	20.3 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
citral (5392-40-5)	
EC50 - Crustacea [1]	7 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	16 mg/l (Species: Desmodesmus subspicatus)
EC50 96h - Algae [1]	19 mg/l (Species: Desmodesmus subspicatus)
para-Cresyl methyl ether (104-93-8)	
EC50 - Crustacea [1]	44.2 mg/l (Exposure time: 48 h - Species: Daphnia magna Straus)
EC50 72h - Algae [1]	320 mg/l (Species: Desmodesmus subspicatus)
EC50 96h - Algae [1]	390 mg/l (Species: Desmodesmus subspicatus)
12.2. Persistence and degradability	
Baby Powder	
Persistence and degradability	Not established.
benzyl benzoate (120-51-4)	
Persistence and degradability	May cause long-term adverse effects in the environment.
Methyl ionone (mixture of isomers) (1335-46-2)	
Persistence and degradability	Rapidly degradable

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Anisic aldehyde (123-11-5)	
Persistence and degradability	Rapidly degradable
COUMARIN (91-64-5)	
Persistence and degradability	Rapidly degradable
Citronellol Pure (106-22-9)	
Persistence and degradability	Rapidly degradable
Patchouli oil (8014-09-3)	
Persistence and degradability	Rapidly degradable
Veratryl aldehyde (Veratraldehyde) (120-14-9)	
Persistence and degradability	Rapidly degradable
Toluene (108-88-3)	
Persistence and degradability	Rapidly degradable
Dipropylene glycol monomethyl ether (34590-94-8)	
Persistence and degradability	Rapidly degradable
Ethyl vanillin (121-32-4)	
Persistence and degradability	Rapidly degradable
Phenylethyl alcohol (60-12-8)	
Persistence and degradability	Rapidly degradable
Benzyl acetate (140-11-4)	
Persistence and degradability	Rapidly degradable
Geraniol (106-24-1)	
Persistence and degradability	Rapidly degradable
Nerol (106-25-2)	
Persistence and degradability	Rapidly degradable
citral (5392-40-5)	
Persistence and degradability	Rapidly degradable
ACETYL HEXAMETHYL TETRALIN (21145-77-7)	
Persistence and degradability	Rapidly degradable
para-Cresyl methyl ether (104-93-8)	
Persistence and degradability	Rapidly degradable
(E)-3-methyl-5-cyclopentadecen-1-one (82356-51-2)	
Persistence and degradability	Rapidly degradable
12.3. Bioaccumulative potential	
Baby Powder	
Bioaccumulative potential	Not established.

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

benzyl benzoate (120-51-4)	
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)
Bioaccumulative potential	Not established.
Methyl ionone (mixture of isomers) (1335-46-2)	
Partition coefficient n-octanol/water (Log Pow)	>4.5 - <5 - at 23 °C (at pH 6.2)
Anisic aldehyde (123-11-5)	
Partition coefficient n-octanol/water (Log Pow)	1.56 (at 25 °C (at pH >7.9-<8.25)
Citronellol Pure (106-22-9)	
Partition coefficient n-octanol/water (Log Pow)	3.41 (at 25 °C)
Veratryl aldehyde (Veratraldehyde) (120-14-9)	
Partition coefficient n-octanol/water (Log Pow)	0.8 (at 25 °C)
Toluene (108-88-3)	
Partition coefficient n-octanol/water (Log Pow)	2.73 (at 20 °C (at pH 7)
Dipropylene glycol monomethyl ether (34590-94-8)	
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7)
Ethyl vanillin (121-32-4)	
Partition coefficient n-octanol/water (Log Pow)	1.61 (at 25 °C)
Phenylethyl alcohol (60-12-8)	
Partition coefficient n-octanol/water (Log Pow)	1.36 (at 20 °C (at pH 7)
Benzyl acetate (140-11-4)	
Partition coefficient n-octanol/water (Log Pow)	1.96 (at 25 °C (at pH 7)
Geraniol (106-24-1)	
Partition coefficient n-octanol/water (Log Pow)	2.6 (at 25 °C)
Nerol (106-25-2)	
Partition coefficient n-octanol/water (Log Pow)	2.76 (at 30 °C (at pH 6.5)
citral (5392-40-5)	
Partition coefficient n-octanol/water (Log Pow)	2.76 (at 25 °C)
ACETYL HEXAMETHYL TETRALIN (21145-77-7)	
Partition coefficient n-octanol/water (Log Pow)	5.7 (at 24 °C)
para-Cresyl methyl ether (104-93-8)	
Partition coefficient n-octanol/water (Log Pow)	2.8 (at 35 °C (at pH 7)

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.






Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with local/national laws and regulations.

Ecological information : Avoid release to the environment.

HP Code : HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.
HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.
HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	Environmentally hazardous substance, liquid, n.o.s. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)
Transport document description				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate) , 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate) , 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Benzyl Benzoate) , 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate) , 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate) , 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				


Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90
Orange plates	: 

Tunnel restriction code (ADR)	: -
EAC code	: •3Z

Transport by sea

Special provisions (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP2, TP29
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-F
Stowage category (IMDG)	: A

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provisions (IATA)	: A97, A158, A197
ERG code (IATA)	: 9L

Inland waterway transport

Classification code (ADN)	: M6
Special provisions (ADN)	: 274, 335, 375, 601
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: M6
---------------------------	------

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Special provisions (RID)	: 274, 335, 375, 601
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBV
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Special provisions for carriage - Loading, unloading and handling (RID)	: CW13, CW31
Colis express (express parcels) (RID)	: CE8
Hazard identification number (RID)	: 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	Toluene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	Baby Powder ; benzyl benzoate ; Methyl ionone (mixture of isomers) ; Citronellol Pure ; Patchouli oil ; Toluene ; Phenylethyl alcohol ; Geraniol ; Nerol ; citral ; para-Cresyl methyl ether ; (E)-3-methyl-5-cyclopentadecen-1-one	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Baby Powder ; benzyl benzoate ; Methyl ionone (mixture of isomers) ; Anisic aldehyde ; Patchouli oil ; Benzyl acetate ; (E)-3-methyl-5-cyclopentadecen-1-one	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	Toluene	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.
48.	Toluene	Toluene

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 3.3364115 % (calculated value)(CARB VOC) (%w/w)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Toluene		108-88-3	2902 30 00	Category 3		Annex I

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(1) - highly toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment
SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : Toluene is listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Danish National Regulations

: Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Other information

: None.

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

The classification complies with

: ATP 12

Baby Powder

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.