Vanilla Liqueur

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Issue date: 11/17/2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	:	Mixture
Product name	:	Vanilla Liqueur
UFI	:	TK5A-Y4GH-Y003-8EKN
Product code	:	parf_vanilla_liqueur
Type of product	:	Perfumes, Fragrances
Product group	:	Raw material

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec	:	For professional use only Industrial
Use of the substance/mixture	:	Perfumes, Fragrances
Function or use category	:	Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

BAKED GAMES SRL
ROMANIA, BUCHAREST, SECTOR 4
+40771326626
contact@kitlumanari.ro | www.kitlumanari.ro

1.4. Emergency telephone number

Emergency number	:	1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731; Brazil: +0-800-591-6042; India: +000-800-100-4086

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral) Category 4	H302
Serious eye damage/eye irritation, Category 2	H319
Skin sensitization, Category 1	H317
Hazardous to the aquatic environment - Acute Hazard Category 1	H400
Hazardous to the aquatic environment - Chronic Hazard Category 2	H411

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye irritation. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :

GHS07 GHS09

Signal word (CLP) : Warning

Contains : Benzyl benzoate; acetyl propionyl; Heliotropine crystals; Coumarin crystals
Hazard statements (CLP) : H302 - Harmful if swallowed.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H410 - Very toxic to aquatic life with long lasting effects.
Precautionary statements (CLP) : P270 - Do not eat, drink or smoke when using this product.
P273 - Avoid release to the environment.
P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.
P330 - Rinse mouth.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371-33	11.496 – 22.992	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
HEXAMETHYLINDANOPYRAN	CAS-No.: 1222-05-5 EC-No.: 214-946-9 EC Index-No.: 603-212-00-7 REACH-no: 01-2119488227-29	4.7485 – 9.497	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Vanillin	CAS-No.: 121-33-5 EC-No.: 204-465-2 REACH-no: 01-2119516040-60	2.749 – 5.498	Eye Irrit. 2, H319
Phenylmethanol	CAS-No.: 100-51-6 EC-No.: 202-859-9 EC Index-No.: 603-057-00-5 REACH-no: 01-2119492630-38	2.4985 – 4.997	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319
Ethyl vanillin crystals	CAS-No.: 121-32-4 EC-No.: 204-464-7 REACH-no: 01-211958961-24	1.4995 – 2.999	Eye Irrit. 2, H319
acetyl propionyl	CAS-No.: 600-14-6 EC-No.: 209-984-8	1.089 – 2.178	Flam. Liq. 2, H225 Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT RE 2, H373
Heliotropine crystals	CAS-No.: 120-57-0 EC-No.: 204-409-7 REACH-no: 01-2119983608-21	0.9995 – 1.999	Skin Sens. 1B, H317

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetoin	CAS-No.: 513-86-0 EC-No.: 208-174-1	0.9075 – 1.815	Flam. Liq. 3, H226 STOT RE 2, H373
Coumarin crystals	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756-26	0.9075 – 1.815	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Veltol plus crystals	CAS-No.: 4940-11-8 EC-No.: 225-582-5	0.5 – 1	Acute Tox. 4 (Oral), H302
Ethyl acetate substance with a Community workplace exposure limit	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5 REACH-no: 01-2119475103-46	0.05 – 0.1	Flam. Liq. 1, H224 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center/doctor/physician if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.
Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

Phenylmethanol (100-51-6)	
Bulgaria - Occupational Exposure Limits	
OEL TWA	5 mg/m³
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	40 mg/m³
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	45 mg/m³
HTP (OEL TWA) [2]	10 ppm

Phenylmethanol (100-51-6)	
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	22 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
AGW (OEL TWA) [2]	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Chemical category	skin notation
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	5 mg/m³
Chemical category	skin notation
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	240 mg/m³
Slovenia - Occupational Exposure Limits	
OEL TWA	22 mg/m³
OEL TWA [ppm]	5 ppm
OEL STEL	44 mg/m³
OEL STEL [ppm]	10 ppm
Chemical category	Potential for cutaneous absorption
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	22 mg/m³ (aerosol, vapour)
MAK (OEL TWA) [2]	5 ppm (aerosol, vapour)
Chemical category	skin notation

acetyl propionyl (600-14-6)	
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	0.083 mg/m³
AGW (OEL TWA) [2]	0.02 ppm
Chemical category	skin notation, Skin sensitization
Slovenia - Occupational Exposure Limits	
OEL TWA	0.083 mg/m³
OEL TWA [ppm]	0.02 ppm
OEL STEL	0.083 mg/m³
OEL STEL [ppm]	0.02 ppm
Chemical category	Potential for cutaneous absorption
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	0.08 mg/m³
MAK (OEL TWA) [2]	0.02 ppm
KZGW (OEL STEL)	0.16 mg/m³
KZGW (OEL STEL) [ppm]	0.04 ppm

acetyl propionyl (600-14-6)	
Chemical category	Sensitizer, skin notation

Ethyl acetate (141-78-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	734 mg/m³
IOEL TWA [ppm]	200 ppm
IOEL STEL	1468 mg/m³
IOEL STEL [ppm]	400 ppm
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	734 mg/m³
MAK (OEL TWA) [ppm]	200 ppm
MAK (OEL STEL)	1468 mg/m³
MAK (OEL STEL) [ppm]	400 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	734 mg/m³
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m³
OEL STEL [ppm]	400 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	734 mg/m³
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m³
OEL STEL [ppm]	400 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	734 mg/m³
GVI (OEL TWA) [2]	200 ppm
KGVI (OEL STEL)	1468 mg/m³
KGVI (OEL STEL) [ppm]	400 ppm
Cyprus - Occupational Exposure Limits	
OEL TWA	734 mg/m³
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m³
OEL STEL [ppm]	400 ppm
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	700 mg/m³
Denmark - Occupational Exposure Limits	
OEL TWA [1]	540 mg/m³
OEL TWA [2]	150 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	500 mg/m³

Ethyl acetate (141-78-6)	
OEL TWA [ppm]	150 ppm
OEL STEL	1100 mg/m³
OEL STEL [ppm]	300 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	730 mg/m³
HTP (OEL TWA) [2]	200 ppm
HTP (OEL STEL)	1470 mg/m³
HTP (OEL STEL) [ppm]	400 ppm
France - Occupational Exposure Limits	
VME (OEL TWA)	1400 mg/m³
VME (OEL TWA) [ppm]	400 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	730 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
AGW (OEL TWA) [2]	200 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Gibraltar - Occupational Exposure Limits	
OEL TWA	200 mg/m³
OEL TWA [ppm]	734 ppm
OEL STEL	400 mg/m³
OEL STEL [ppm]	1468 ppm
Greece - Occupational Exposure Limits	
OEL TWA	734 mg/m³
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m³
OEL STEL [ppm]	400 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	734 mg/m³
CK (OEL STEL)	1468 mg/m³
Chemical category	Sensitizer
Ireland - Occupational Exposure Limits	
OEL TWA [1]	734 mg/m³
OEL TWA [2]	200 ppm
OEL STEL	1468 mg/m³
OEL STEL [ppm]	400 ppm
Italy - Occupational Exposure Limits	
OEL TWA	734 mg/m³
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m³
OEL STEL [ppm]	400 ppm

Ethyl acetate (141-78-6)	
Latvia - Occupational Exposure Limits	
OEL TWA	200 mg/m³
OEL TWA [ppm]	54 ppm
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	500 mg/m³
IPRV (OEL TWA) [ppm]	150 ppm
NRV (OEL C)	1100 mg/m³
NRV (OEL C) [ppm]	300 ppm
Luxembourg - Occupational Exposure Limits	
OEL STEL	1468 mg/m³
OEL STEL [ppm]	400 ppm
Malta - Occupational Exposure Limits	
OEL TWA	734 mg/m³
OEL TWA [ppm]	200 ppm
OEL STEL	1468 mg/m³
OEL STEL [ppm]	400 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	734 mg/m³
TGG-15min (OEL STEL)	1468 mg/m³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	734 mg/m³
NDSCh (OEL STEL)	1468 mg/m³
Portugal - Occupational Exposure Limits	
OEL TWA	734 mg/m³ (indicative limit value)
OEL TWA [ppm]	200 ppm (indicative limit value)
OEL STEL	1468 mg/m³ (indicative limit value)
OEL STEL [ppm]	400 ppm (indicative limit value)
Romania - Occupational Exposure Limits	
OEL TWA	400 mg/m³
OEL TWA [ppm]	111 ppm
OEL STEL	500 mg/m³
OEL STEL [ppm]	139 ppm
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	734 mg/m³
NPHV (OEL TWA) [2]	200 ppm
NPHV (OEL C)	1100 mg/m³
Slovenia - Occupational Exposure Limits	
OEL TWA	734 mg/m³
OEL TWA [ppm]	200 ppm

Ethyl acetate (141-78-6)	
OEL STEL	1468 mg/m³
OEL STEL [ppm]	400 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	734 mg/m³
VLA-ED (OEL TWA) [2]	200 ppm
VLA-EC (OEL STEL)	1468 mg/m³
VLA-EC (OEL STEL) [ppm]	400 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	550 mg/m³
NGV (OEL TWA) [ppm]	150 ppm
KTV (OEL STEL)	1100 mg/m³
KTV (OEL STEL) [ppm]	300 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	734 mg/m³
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	1468 mg/m³
WEL STEL (OEL STEL) [ppm]	400 ppm
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA) [1]	734 mg/m³
Grenseverdi (OEL TWA) [2]	200 ppm
Korttidsverdi (OEL STEL)	1468 mg/m³ (value from the regulation)
Korttidsverdi (OEL STEL) [ppm]	400 ppm (value from the regulation)
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	730 mg/m³
MAK (OEL TWA) [2]	200 ppm
KZGW (OEL STEL)	1460 mg/m³
KZGW (OEL STEL) [ppm]	400 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	400 ppm

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):

8.2.2.1. Eye and face protection

Eye protection:
Safety glasses

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Color	:	light yellow. amber.
Odor	:	characteristic.
Odor threshold	:	No data available
pH	:	No data available
Relative evaporation rate (butyl acetate=1)	:	No data available
Melting point	:	Not applicable
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	> 93 °C (closed cup) ASTM D7094
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Flammability (solid, gas)	:	Not applicable
Vapor pressure	:	No data available
Relative vapor density at 20 °C	:	No data available
Relative density	:	≈ 0.95
Solubility	:	No data available
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available

Explosion limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Vanilla Liqueur	
ATE CLP (oral)	1333.377 mg/kg body weight

Benzyl benzoate (120-51-4)	
LD50 oral rat	500 mg/kg
LD50 oral	1500 mg/kg body weight
LD50 dermal rabbit	4000 mg/kg
LD50 dermal	4000 mg/kg body weight

HEXAMETHYLINDANOPYRAN (1222-05-5)	
LD50 oral rat	> 3250 mg/kg
LD50 dermal rabbit	> 3250 mg/kg

Vanillin (121-33-5)	
LD50 dermal rabbit	> 5010 mg/kg

Phenylmethanol (100-51-6)	
LD50 oral rat	1230 mg/kg
LD50 oral	1620 mg/kg body weight

Phenylmethanol (100-51-6)	
LD50 dermal	2500 mg/kg body weight

Ethyl vanillin crystals (121-32-4)	
LD50 oral rat	1590 mg/kg
LD50 oral	3000 mg/kg body weight
LD50 dermal rat	> 2000 mg/kg

acetyl propionyl (600-14-6)	
LD50 oral rat	3 g/kg
LD50 oral	3000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg
LD50 dermal	2500 mg/kg body weight

Heliotropine crystals (120-57-0)	
LD50 oral rat	2700 mg/kg
LD50 oral	2700 mg/kg body weight
LD50 dermal rat	> 5000 mg/kg

acetoin (513-86-0)	
LD50 oral rat	> 5 g/kg

Coumarin crystals (91-64-5)	
LD50 oral rat	> 5000 mg/kg
LD50 oral	500 mg/kg body weight
LD50 dermal rat	293 mg/kg

Veltol plus crystals (4940-11-8)	
LD50 oral rat	1150 mg/kg
LD50 oral	1200 mg/kg body weight
LD50 dermal rabbit	> 5000 mg/kg

Ethyl acetate (141-78-6)	
LD50 oral rat	5620 mg/kg
LD50 dermal rabbit	> 18000 mg/kg
LC50 Inhalation - Rat [ppm]	4000 ppm/4h

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Coumarin crystals (91-64-5)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified
STOT-single exposure : Not classified

Ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

acetyl propionyl (600-14-6)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

acetoin (513-86-0)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

Benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])
NOEC (chronic)	0.168 mg/l

HEXAMETHYLINDANOPYRAN (1222-05-5)	
LC50 - Fish [1]	0.452 mg/l Wolf, 1996d-27682
LC50 - Other aquatic organisms [1]	> 0.14 mg/l REACH DOSSIER Pimephales promelas
EC50 - Crustacea [2]	260 µg/l REACH Dossier
EC50 - Other aquatic organisms [1]	0.131 mg/l REACH Dossier

Vanillin (121-33-5)	
LC50 - Fish [1]	53 – 61.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	88 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
NOEC (acute)	10000 mg/kg (Exposure time: 42 Days - Species: Eisenia foetida [soil dry weight])

Phenylmethanol (100-51-6)	
LC50 - Fish [1]	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
LC50 - Fish [2]	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 - Crustacea [1]	23 mg/l (Exposure time: 48 h - Species: water flea)

Ethyl vanillin crystals (121-32-4)	
LC50 - Fish [1]	81.4 – 94.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

Heliotropine crystals (120-57-0)	
LC50 - Fish [1]	2.5 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static])

Veltol plus crystals (4940-11-8)	
LC50 - Fish [1]	> 85 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)

Ethyl acetate (141-78-6)	
LC50 - Fish [1]	220 – 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 - Crustacea [1]	560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

12.2. Persistence and degradability

Benzyl benzoate (120-51-4)	
Persistence and degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

Benzyl benzoate (120-51-4)	
Partition coefficient n-octanol/water (Log Pow)	4
Bioaccumulative potential	Not established.
Vanillin (121-33-5)	
Partition coefficient n-octanol/water (Log Pow)	1.23 (at 22 °C)
Phenylmethanol (100-51-6)	
Partition coefficient n-octanol/water (Log Pow)	1.1
Ethyl acetate (141-78-6)	
BCF - Fish [1]	30
Partition coefficient n-octanol/water (Log Pow)	0.6

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number

UN-No. (ADR) : UN 3082
UN-No. (IMDG) : UN 3082
UN-No. (IATA) : UN 3082
UN-No. (ADN) : Not regulated
UN-No. (RID) : Not regulated

14.2. UN proper shipping name

Proper Shipping Name (ADR) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Proper Shipping Name (IATA) : Environmentally hazardous substance, liquid, n.o.s.
Proper Shipping Name (ADN) : Not regulated
Proper Shipping Name (RID) : Not regulated
Transport document description (ADR) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hexamethylindanopyran), 9, III, (-)

Transport document description (IMDG) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hexamethylindanopyran), 9, III, MARINE POLLUTANT

Transport document description (IATA) : UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Hexamethylindanopyran), 9, III

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 9

Hazard labels (ADR) : 9

:

IMDG

Transport hazard class(es) (IMDG) : 9

Hazard labels (IMDG) : 9

:

IATA

Transport hazard class(es) (IATA) : 9

Hazard labels (IATA) : 9

:

ADN

Transport hazard class(es) (ADN) : Not regulated

RID

Transport hazard class(es) (RID) : Not regulated

14.4. Packing group

Packing group (ADR) : III

Packing group (IMDG) : III

Packing group (IATA) : III

Packing group (ADN) : Not regulated

Packing group (RID) : Not regulated

14.5. Environmental hazards

Dangerous for the environment : Yes

Marine pollutant : Yes

Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : M6

Special provision (ADR) : 274, 335, 375, 601

Limited quantities (ADR) : 5l

Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR)	:	PP1
Mixed packing provisions (ADR)	:	MP19
Portable tank and bulk container instructions (ADR)	:	T4
Portable tank and bulk container special provisions (ADR)	:	TP1, TP29
Tank code (ADR)	:	LGBV
Vehicle for tank carriage	:	AT
Transport category (ADR)	:	3
Special provisions for carriage - Packages (ADR)	:	V12
Special provisions for carriage - Loading, unloading and handling (ADR)	:	CV13
Hazard identification number (Kemler No.)	:	90
Orange plates	:	
Tunnel restriction code (ADR)	:	-
EAC	:	•3Z

Transport by sea

Special provision (IMDG)	:	274, 335, 969
Limited quantities (IMDG)	:	5 L
Excepted quantities (IMDG)	:	E1
Packing instructions (IMDG)	:	LP01, P001
Packing provisions (IMDG)	:	PP1
IBC packing instructions (IMDG)	:	IBC03
Tank instructions (IMDG)	:	T4
Tank special provisions (IMDG)	:	TP1, TP29
EmS-No. (Fire)	:	F-A
EmS-No. (Spillage)	:	S-F
Stowage category (IMDG)	:	A

Air transport

PCA Excepted quantities (IATA)	:	E1
PCA Limited quantities (IATA)	:	Y964
PCA limited quantity max net quantity (IATA)	:	30kgG
PCA packing instructions (IATA)	:	964
PCA max net quantity (IATA)	:	450L
CAO packing instructions (IATA)	:	964
CAO max net quantity (IATA)	:	450L
Special provision (IATA)	:	A97, A158, A197, A215
ERG code (IATA)	:	9L

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)	
Reference code	**Applicable on**
3(a)	acetyl propionyl ; acetoin ; Ethyl acetate
3(b)	Vanilla Liqueur ; Benzyl benzoate ; Phenylmethanol ; acetyl propionyl ; acetoin ; Ethyl acetate
3(c)	Vanilla Liqueur ; Benzyl benzoate ; HEXAMETHYLINDANOPYRAN
40.	acetyl propionyl ; acetoin ; Ethyl acetate

Contains no REACH candidate substance
Contains no REACH Annex XIV substances.
Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.
Contains no substance(s) subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

France	
Professional diseases	
Code	**Description**
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions	:	Observe restrictions according Act on the Protection of Working Mothers (MuSchG) Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)
Water hazard class (WGK)	:	WGK 2, significant hazardous to water (Classification according to AwSV, Annex 1)
Hazardous Incident Ordinance (12. BImSchV)	:	Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen	:	None of the components are listed
SZW-lijst van mutagene stoffen	:	None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	:	None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	:	None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	:	None of the components are listed

Denmark

Classification remarks	:	Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations	:	Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Switzerland

Storage class (LK)	:	LK 10/12 - Liquids

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-phrases	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3

Full text of H- and EUH-phrases	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 1	Flammable liquids Category 1
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1B	Skin sensitization, Category 1B
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H224	Extremely flammable liquid and vapor.
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.