

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 5/14/2018 Revision date: 9/15/2023 Version: 2.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Caramelle

UFI : KRMY-201R-T00W-7A6K

Product code : parf_caramelle
Type of product : Perfumes, fragrances
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use,Professional use Industrial/Professional use spec : For professional use only

Industrial

Use of the substance/mixture : Perfumes, fragrances Function or use category : Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

BAKED GAMES SRL ROMANIA, BUCHAREST, SECTOR 4 +40771326626

contact@kitlumanari.ro | www.kitlumanari.ro

1.4. Emergency telephone number

Emergency number : 1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731;

Brazil: +0-800-591-6042; India: +000-800-100-4086

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4 H302
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment – Chronic Hazard, Category 2 H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful if swallowed. Causes serious eye irritation. Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS07

GHS09

Signal word (CLP) : Warning

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP) : H302 - Harmful if swallowed.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation. H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

Extra phrases : For professional users only.

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371- 33	40.9 – 81.79	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Ethyl vanillin	CAS-No.: 121-32-4 EC-No.: 204-464-7 REACH-no: 01-211958961-24	4.2 – 8.45	Eye Irrit. 2, H319
Methyl ester of rosin (partially hydrogenated)	CAS-No.: 8050-15-5 EC-No.: 232-476-2	1.6 – 3.1	Aquatic Chronic 3, H412
Vanillin	CAS-No.: 121-33-5 EC-No.: 204-465-2 REACH-no: 01-2119516040- 60	1.3 – 2.5	Eye Irrit. 2, H319
COUMARIN	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756- 26	0.6 – 1.2	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Heliotropine	CAS-No.: 120-57-0 EC-No.: 204-409-7 REACH-no: 01-2119983608- 21	0.5 – 0.9	Skin Sens. 1B, H317

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetyl propionyl substance with national workplace exposure limit(s) (DE, SI, CH)	CAS-No.: 600-14-6 EC-No.: 209-984-8	0.4 – 0.8	Flam. Liq. 2, H225 Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT RE 2, H373
1,2-Cyclopentanedione, 3-methyl-	CAS-No.: 765-70-8 EC-No.: 212-154-8	0.2 – 0.45	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317
Isobutyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH)	CAS-No.: 110-19-0 EC-No.: 203-745-1 EC Index-No.: 607-026-00-7	0.1 – 0.2	Flam. Liq. 2, H225 STOT SE 3, H336

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

4.1. Description of first aid measures	
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do NOT induce vomiting. Obtain emergency medical attention. Rinse mouth. Call a poison center or a doctor if you feel unwell

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

9/15/2023 (Revision date) EN (English) 3/18

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Protection during firefighting

Do not enter fire area without proper protective equipment, including respiratory protection.
 Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew

with proper protection. For further information refer to section 8: "Exposure

controls/personal protection".

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or

diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild

soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes.

Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures

Do not eat, drink or smoke when using this product. Always wash hands after handling the

: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash

contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep

container closed when not in use. Store in a well-ventilated place. Keep cool.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

Storage temperature : 25 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Store in a closed container.

Packaging materials : Do not store in corrodable metal

7.3. Specific end use(s)

No additional information available

9/15/2023 (Revision date) EN (English) 4/18

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

9 · · · · · · · · · · · · · · · · · · ·			
acetyl propionyl (600-14-6)			
Germany - Occupational Exposure Limits (TRGS 900)			
AGW (OEL TWA) [1]	0.083 mg/m³		
AGW (OEL TWA) [2]	0.02 ppm		
Chemical category	Skin notation, Skin sensitization		
Slovenia - Occupational Exposure Limits			
OEL TWA	0.083 mg/m³		
OEL TWA [ppm]	0.02 ppm		
OEL STEL	0.083 mg/m³		
OEL STEL [ppm]	0.02 ppm		
OEL chemical category	Potential for cutaneous absorption		
Switzerland - Occupational Exposure Limits			
MAK (OEL TWA) [1]	0.08 mg/m³		
MAK (OEL TWA) [2]	0.02 ppm		
KZGW (OEL STEL)	0.16 mg/m³		
KZGW (OEL STEL) [ppm]	0.04 ppm		
OEL chemical category	Sensitizer, Skin notation		
Isobutyl acetate (110-19-0)			
Austria - Occupational Exposure Limits			
MAK (OEL TWA)	241 mg/m³ (Butyl acetates)		
MAK (OEL TWA) [ppm]	50 ppm (Butyl acetates)		
MAK (OEL STEL)	480 mg/m³ (Butyl acetate)		
MAK (OEL STEL) [ppm]	100 ppm (Butyl acetate)		
Belgium - Occupational Exposure Limits			
OEL TWA	238 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL STEL	712 mg/m³		
OEL STEL [ppm]	150 ppm		
Bulgaria - Occupational Exposure Limits	Bulgaria - Occupational Exposure Limits		
OEL TWA	241 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL STEL	723 mg/m³		
OEL STEL [ppm]	150 ppm		
Croatia - Occupational Exposure Limits			
GVI (OEL TWA) [1]	241 mg/m³		
GVI (OEL TWA) [2]	50 ppm		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isobutyl acetate (110-19-0)			
KGVI (OEL STEL)	723 mg/m³		
KGVI (OEL STEL) [ppm]	150 ppm		
Cyprus - Occupational Exposure Limits			
OEL TWA	241 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL STEL	723 mg/m³		
OEL STEL [ppm]	150 ppm		
Czech Republic - Occupational Exposure Limits			
PEL (OEL TWA)	241 mg/m³		
Denmark - Occupational Exposure Limits			
OEL TWA [1]	241 mg/m³ (Butyl acetate, all isomers)		
OEL TWA [2]	50 ppm (Butyl acetate, all isomers)		
OEL STEL	723 mg/m³		
OEL STEL [ppm]	150 ppm		
Estonia - Occupational Exposure Limits			
OEL TWA	241 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL STEL	723 mg/m³		
OEL STEL [ppm]	150 ppm		
Finland - Occupational Exposure Limits			
HTP (OEL TWA) [1]	240 mg/m³ (Butyl acetate)		
HTP (OEL TWA) [2]	50 ppm (Butyl acetate)		
HTP (OEL STEL)	725 mg/m³ (Butyl acetate)		
HTP (OEL STEL) [ppm]	150 ppm (Butyl acetate)		
France - Occupational Exposure Limits			
VME (OEL TWA)	241 mg/m³ (restrictive limit)		
VME (OEL TWA) [ppm]	50 ppm (restrictive limit)		
VLE (OEL C/STEL)	723 mg/m³ (restrictive limit)		
VLE (OEL C/STEL) [ppm]	150 ppm (restrictive limit)		
Germany - Occupational Exposure Limits (TRGS 90	Germany - Occupational Exposure Limits (TRGS 900)		
AGW (OEL TWA) [1]	300 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)		
AGW (OEL TWA) [2]	62 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)		
Greece - Occupational Exposure Limits			
OEL TWA	241 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL STEL	723 mg/m³		
OEL STEL [ppm]	150 ppm		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isobutyl acetate (110-19-0)			
Hungary - Occupational Exposure Limits	Hungary - Occupational Exposure Limits		
AK (OEL TWA)	241 mg/m³		
CK (OEL STEL)	723 mg/m³		
OEL chemical category	Sensitizer		
Ireland - Occupational Exposure Limits			
OEL TWA [1]	241 mg/m³		
OEL TWA [2]	50 ppm		
OEL STEL	723 mg/m³ (calculated)		
OEL STEL [ppm]	150 ppm (calculated)		
Italy - Occupational Exposure Limits			
OEL TWA	241 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL STEL	723 mg/m³		
OEL STEL [ppm]	150 ppm		
Latvia - Occupational Exposure Limits			
OEL TWA	241 mg/m³		
OEL TWA [ppm]	50 ppm		
Lithuania - Occupational Exposure Limits			
IPRV (OEL TWA)	241 mg/m³		
IPRV (OEL TWA) [ppm]	50 ppm		
TPRV (OEL STEL)	723 mg/m³		
TPRV (OEL STEL) [ppm]	150 ppm		
Luxembourg - Occupational Exposure Limits			
OEL TWA	241 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL STEL	723 mg/m³		
OEL STEL [ppm]	150 ppm		
Malta - Occupational Exposure Limits			
OEL TWA	241 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL STEL	723 mg/m³		
OEL STEL [ppm]	150 ppm		
Netherlands - Occupational Exposure Limits			
TGG-8u (OEL TWA)	241 mg/m³		
TGG-8u (OEL TWA) [ppm]	50 ppm		
TGG-15min (OEL STEL)	723 mg/m³		
TGG-15min (OEL STEL) [ppm]	150 ppm		
Poland - Occupational Exposure Limits			
NDS (OEL TWA)	240 mg/m³		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isobutyl acetate (110-19-0)		
NDSCh (OEL STEL)	720 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	241 mg/m³ (indicative limit value)	
OEL TWA [ppm]	50 ppm (indicative limit value)	
OEL STEL	723 mg/m³ (indicative limit value)	
OEL STEL [ppm]	150 ppm (indicative limit value)	
Romania - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA) [1]	480 mg/m³	
NPHV (OEL TWA) [2]	100 ppm	
NPHV (OEL C)	700 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	241 mg/m³	
VLA-ED (OEL TWA) [2]	50 ppm	
VLA-EC (OEL STEL)	723 mg/m³	
VLA-EC (OEL STEL) [ppm]	150 ppm	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	241 mg/m³ (Butyl acetates)	
NGV (OEL TWA) [ppm]	50 ppm (Butyl acetates)	
KTV (OEL STEL)	723 mg/m³ (Butyl acetates)	
KTV (OEL STEL) [ppm]	150 ppm (Butyl acetates)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	724 mg/m³	
WEL TWA (OEL TWA) [2]	150 ppm	
WEL STEL (OEL STEL)	903 mg/m³	
WEL STEL (OEL STEL) [ppm]	187 ppm	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA) [1]	241 mg/m³	
Grenseverdi (OEL TWA) [2]	50 ppm	
Korttidsverdi (OEL STEL)	723 mg/m³ (value from the regulation)	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isobutyl acetate (110-19-0)		
Korttidsverdi (OEL STEL) [ppm]	150 ppm (value from the regulation)	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA) [1]	240 mg/m³	
MAK (OEL TWA) [2]	50 ppm	
KZGW (OEL STEL)	720 mg/m³	
KZGW (OEL STEL) [ppm]	150 ppm	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	50 ppm (Butyl acetates, all isomers)	
ACGIH OEL STEL [ppm]	150 ppm (Butyl acetates, all isomers)	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):







8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves. Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : light yellow. amber. Conforms to standard.

Odour : characteristic. : Not available Odour threshold : Not applicable Melting point Freezing point : Not available : Not available Boiling point Flammability : Not applicable : Not available **Explosive limits** : Not available Lower explosion limit Upper explosion limit : Not available

Flash point : > 93 °C (closed cup) ASTM D7094

Auto-ignition temperature : Not available Decomposition temperature Not available : Not available рΗ Viscosity, kinematic : Not available Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : Not available Vapour pressure at 50°C : Not available Density : Not available Relative density · ≈ 0.96 Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions. Not established.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Not established.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Acute toxicity (innalation) : Not classified		
Caramelle		
ATE CLP (oral)	569.541 mg/kg bodyweight	
Benzyl benzoate (120-51-4)		
LD50 oral rat	500 mg/kg (Source: NLM_CIP)	
LD50 oral	1160 mg/kg bodyweight	
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)	
Ethyl vanillin (121-32-4)		
LD50 oral rat	1590 mg/kg (Source: NLM_CIP)	
LD50 oral	3000 mg/kg bodyweight	
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)	
Methyl ester of rosin (partially hydrogenated)	(8050-15-5)	
LD50 oral rat	> 2000 mg/kg (Source: CHEMVIEW)	
LD50 dermal rabbit	> 10000 mg/kg (Source: ECHA_API)	
Vanillin (121-33-5)		
LD50 dermal rabbit	> 5010 mg/kg (Source: OECD_SIDS)	
LD50 dermal	2600 mg/kg bodyweight	
COUMARIN (91-64-5)		
LD50 oral rat	> 5000 mg/kg (Source: JAPAN_GHS)	
LD50 oral	290 mg/kg bodyweight	
LD50 dermal rat	293 mg/kg (Source: ECHA_API)	
Heliotropine (120-57-0)		
LD50 oral rat	2700 mg/kg (Source: NLM_CIP)	
LD50 oral	2700 mg/kg bodyweight	
LD50 dermal rat	> 5000 mg/kg (Source: ECHA_API)	
acetyl propionyl (600-14-6)		
LD50 oral rat	3 g/kg (Source: NLM_CIP)	
LD50 oral	3000 mg/kg bodyweight	
LD50 dermal rabbit	> 2000 mg/kg (Source: NIOSH)	
LD50 dermal	2500 mg/kg bodyweight	
1,2-Cyclopentanedione, 3-methyl- (765-70-8)		
LD50 oral	1067 mg/kg bodyweight	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isobutyl acetate (110-19-0)	
LD50 oral rat	15400 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	> 17400 mg/kg (Source: NLM_CIP)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
COUMARIN (91-64-5)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
Isobutyl acetate (110-19-0)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
acetyl propionyl (600-14-6)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Benzyl benzoate (120-51-4)	
Viscosity, kinematic	7.456 mm²/s
Heliotropine (120-57-0)	
Viscosity, kinematic	Not applicable

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Not classified

(acute

Hazardous to the aquatic environment, long–term : Toxic to aquatic life with long lasting effects.

(chronic)

(GITI GITIG)	
Benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
NOEC (chronic)	0.168 mg/l
Ethyl vanillin (121-32-4)	
LC50 - Fish [1]	81.4 – 94.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Vanillin (121-33-5)		
LC50 - Fish [1]	53 – 61.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
LC50 - Fish [2]	88 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)	
NOEC (acute)	10000 mg/kg (Exposure time: 42 Days - Species: Eisenia foetida [soil dry weight])	
Heliotropine (120-57-0)		
LC50 - Fish [1]	2.5 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static] Source: ECHA)	
Isobutyl acetate (110-19-0)		
LC50 - Fish [1]	17 mg/l (Exposure time: 96 h - Species: Oryzias latipes Source: ECHA)	

12.2. Persistence and degradability

Caramelle		
Persistence and degradability	Not established.	
Benzyl benzoate (120-51-4)		
Persistence and degradability	May cause long-term adverse effects in the environment.	

12.3. Bioaccumulative potential

Caramelle			
Bioaccumulative potential	Not established.		
Benzyl benzoate (120-51-4)			
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)		
Bioaccumulative potential	Not established.		
Ethyl vanillin (121-32-4)			
Partition coefficient n-octanol/water (Log Pow)	1.61 (at 25 °C)		
Methyl ester of rosin (partially hydrogenated) (8050-15-5)			
Partition coefficient n-octanol/water (Log Pow)	6.4 – 7.6 (at pH 6)		
Vanillin (121-33-5)			
Partition coefficient n-octanol/water (Log Pow)	1.23 (at 22 °C)		
Heliotropine (120-57-0)			
Partition coefficient n-octanol/water (Log Pow)	1.2 (at 35 °C)		
Isobutyl acetate (110-19-0)			
BCF - Fish [1]	(no significant bioconcentration)		
Partition coefficient n-octanol/water (Log Pow)	2.3 (at 25 °C (at pH 7)		

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

Product/Packaging disposal recommendations

Ecology - waste materials

HP Code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- Dispose in a safe manner in accordance with local/national regulations.
- Avoid release to the environment.
- HP3 "Flammable:"
 - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
 - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
 - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
 - flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
 - water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
 - other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
- HP6 "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.
- HP14 "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID						
ADR	IMDG	IATA	ADN	RID		
14.1. UN number or ID number						
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082		
14.2. UN proper shippin	g name					
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	Environmentally hazardous substance, liquid, n.o.s. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)		
Transport document descr	iption					
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Benzyl Benzoate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III		
14.3. Transport hazard class(es)						
9	9	9	9	9		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID		
14.4. Packing group						
III III		III	III	III		
14.5. Environmental hazards						
Dangerous for the environment: Yes environment: Yes Marine pollutant: Yes		Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes		

14.6. Special precautions for user

Overland transport

Classification code (ADR) : M6

Special provisions (ADR) : 274, 335, 375, 601

Limited quantities (ADR) : 5I Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions : TP1, TP29

(ADR)

Tank code (ADR) : LGBV
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Loading, unloading : CV13

and handling (ADR)

Hazard identification number (Kemler No.) : 90

Orange plates :

90 3082

Tunnel restriction code (ADR) : EAC code : •3Z

Transport by sea

Special provisions (IMDG) : 274, 335, 969

Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1 : LP01, P001 Packing instructions (IMDG) Special packing provisions (IMDG) : PP1 : IBC03 IBC packing instructions (IMDG) : T4 Tank instructions (IMDG) : TP1, TP29 Tank special provisions (IMDG) : F-A EmS-No. (Fire) : S-F EmS-No. (Spillage) Stowage category (IMDG) : A

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L

Special provisions (IATA) : A97, A158, A197, A215

ERG code (IATA) : 9L

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Inland waterway transport

Classification code (ADN) : M6

Special provisions (ADN) : 274, 335, 375, 601

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E1

Carriage permitted (ADN) : T

Equipment required (ADN) : PP

Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : M6

Special provisions (RID) : 274, 335, 375, 601

Limited quantities (RID) : 5L Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions : TP1, TP29

(RID)

Tank codes for RID tanks (RID) : LGBV

Transport category (RID) : 3

Special provisions for carriage – Packages (RID) : W12

Special provisions for carriage - Loading, unloading : CW13, CW31

and handling (RID)

Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (R	EU restriction list (REACH Annex XVII)			
Reference code	Applicable on	Entry title or description		
3(a)	acetyl propionyl ; Isobutyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F		
3(b)	Caramelle ; Benzyl benzoate ; acetyl propionyl ; Isobutyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10		
3(c)	Caramelle ; Benzyl benzoate ; Methyl ester of rosin (partially hydrogenated)	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1		
40.	acetyl propionyl ; Isobutyl acetate	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Piperonal		120-57-0	2932 93 00	Category 1		Annex I

15.1.2. National regulations

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(1) - highly toxic for aquatic organisms, may have longterm hazardous effects in aquatic

: None of the components are listed

: None of the components are listed

: Resin acids and Rosin acids, hydrogenated, methyl esters is listed

: Resin acids and Rosin acids, hydrogenated, methyl esters is listed

environment

SZW-lijst van kankerverwekkende stoffen

SZW-lijst van mutagene stoffen

SZW-lijst van reprotoxische stoffen - Borstvoeding

SZW-lijst van reprotoxische stoffen –

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with

the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Other information : None.

Full text of H- and EUH-statements:		
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3	
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:			
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1		
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2		
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3		
Eye Dam. 1	Serious eye damage/eye irritation, Category 1		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Liq. 2	Flammable liquids, Category 2		
H225	Highly flammable liquid and vapour.		
H301	Toxic if swallowed.		
H302	Harmful if swallowed.		
H311	Toxic in contact with skin.		
H317	May cause an allergic skin reaction.		
H318	Causes serious eye damage.		
H319	Causes serious eye irritation.		
H331	Toxic if inhaled.		
H336	May cause drowsiness or dizziness.		
H373	May cause damage to organs through prolonged or repeated exposure.		
H400	Very toxic to aquatic life.		
H411	Toxic to aquatic life with long lasting effects.		
H412	Harmful to aquatic life with long lasting effects.		
Skin Sens. 1	Skin sensitisation, Category 1		
Skin Sens. 1B	Skin sensitisation, category 1B		
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2		
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis		

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.