

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Trade name	: ROASTED COFFEE #EU35918F
UFI	: YRF6-K390-V00Q-5MF6
Product code	: EU35918F
Type of product	: Perfumes, fragrances
Product group	: Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	: Industrial use, Professional use
Industrial/Professional use spec	: For professional use only Industrial
Use of the substance/mixture	: Perfumes, fragrances
Function or use category	: Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

FRENCH COLOR & FRAGRANCE International GmbH
Mittlerer Weg 35
DE 79424 Auggen
Germany
T 49-7631-931-8900
SDS@frenchcolor.com, www.frenchcolor.com

1.4. Emergency telephone number

Emergency number	: 1-800-255-3924; +01-813-248-0585; China: +400-120-0751; Mexico: +01-800-099-0731; Brazil: +0-800-591-6042; India: +000-800-100-4086
------------------	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4	H302
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment – Acute Hazard, Category 1	H400
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411
Full text of H- and EUH-statements: see section 16	


Adverse physicochemical, human health and environmental effects

Harmful if swallowed. Toxic to aquatic life with long lasting effects. Very toxic to aquatic life. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Signal word (CLP)	: Warning
Contains	: benzyl benzoate; Ethyl maltol; 1,2-Cyclopentanedione, 3-methyl-; TOLU BALSAM; 3(2H)-Furanone, 4-hydroxy-2,5-dimethyl-; Acetyl Propionyl
Hazard statements (CLP)	: H302 - Harmful if swallowed. H317 - May cause an allergic skin reaction. H410 - Very toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
Extra phrases	: Restricted to professional users. For professional users only.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371-33	39.65 – 79.3497	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Resin acids and Rosin acids, hydrogenated, methyl esters	CAS-No.: 8050-15-5 EC-No.: 232-476-2	4.5 – 9	Aquatic Chronic 3, H412
Ethyl vanillin	CAS-No.: 121-32-4 EC-No.: 204-464-7 REACH-no: 01-211958961-24	1.4 – 2.7	Eye Irrit. 2, H319
Ethyl maltol	CAS-No.: 4940-11-8 EC-No.: 225-582-5	0.9 – 1.8367	Acute Tox. 4 (Oral), H302
1,2-Cyclopentanedione, 3-methyl-	CAS-No.: 765-70-8 EC-No.: 212-154-8	0.2 – 0.45	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317
Benzothiazole substance with national workplace exposure limit(s) (PL)	CAS-No.: 95-16-9 EC-No.: 202-396-2	0.2 – 0.35	Acute Tox. 4 (Oral), H302 Acute Tox. 2 (Dermal), H310 Acute Tox. 4 (Inhalation), H332 Acute Tox. 3 (Inhalation:vapour), H331 Eye Irrit. 2, H319
3(2H)-Furanone, 4-hydroxy-2,5-dimethyl-	CAS-No.: 3658-77-3 EC-No.: 222-908-8	0.1 – 0.1627	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Irrit. 2, H319 Skin Sens. 1A, H317

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Acetyl Propionyl substance with national workplace exposure limit(s) (DE, SI, CH)	CAS-No.: 600-14-6 EC-No.: 209-984-8	0.1 – 0.1217	Flam. Liq. 2, H225 Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT RE 2, H373
TOLU BALSAM	CAS-No.: 9000-64-0	0.05 – 0.1125	Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 Aquatic Chronic 3, H412
ethanol; ethyl alcohol substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR)	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5	0 – 0.0382	Flam. Liq. 2, H225
pyridine substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 110-86-1 EC-No.: 203-809-9 EC Index-No.: 613-002-00-7	0 – 0.0074	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332
2,6-xylenol substance with national workplace exposure limit(s) (LV, RO)	CAS-No.: 576-26-1 EC-No.: 209-400-1 EC Index-No.: 604-006-00-X	0 – 0.0059	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 2, H411
Isovaleraldehyde substance with national workplace exposure limit(s) (AT, DE, LT, SI)	CAS-No.: 590-86-3 EC-No.: 209-691-5	0 – 0.0045	Flam. Liq. 2, H225 Eye Irrit. 2, H319 Skin Sens. 1B, H317 STOT SE 3, H335 Aquatic Chronic 2, H411
acetaldehyde; ethanal substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, LT, NL, PL, PT, RO, SE, SI, SK, NO, CH)	CAS-No.: 75-07-0 EC-No.: 200-836-8 EC Index-No.: 605-003-00-6	0 – 0.0018	Flam. Liq. 1, H224 Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Muta. 2, H341 Carc. 1B, H350 STOT SE 3, H335

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Do NOT induce vomiting. Obtain emergency medical attention. Rinse mouth. Call a poison center or a doctor if you feel unwell.

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

4.2. Most important symptoms and effects, both acute and delayed

- | | |
|-------------------------------------|--|
| Symptoms/effects | : Not expected to present a significant hazard under anticipated conditions of normal use. |
| Symptoms/effects after skin contact | : May cause an allergic skin reaction. |

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- | | |
|--------------------------------|--|
| Suitable extinguishing media | : Sand. Water spray. Dry powder. Foam. Carbon dioxide. |
| Unsuitable extinguishing media | : Do not use a heavy water stream. |

5.2. Special hazards arising from the substance or mixture

- | | |
|--|--------------------------------|
| Hazardous decomposition products in case of fire | : Toxic fumes may be released. |
|--|--------------------------------|

5.3. Advice for firefighters

- | | |
|--------------------------------|--|
| Firefighting instructions | : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment. |
| Protection during firefighting | : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- | | |
|----------------------|--|
| Emergency procedures | : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. |
|----------------------|--|

6.1.2. For emergency responders

- | | |
|----------------------|--|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection". |
| Emergency procedures | : Ventilate area. |

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- | | |
|-------------------------|--|
| For containment | : Collect spillage. |
| Methods for cleaning up | : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. |
| Other information | : Dispose of materials or solid residues at an authorized site. |

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Store in a well-ventilated place. Keep cool.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight.
- Storage temperature : 25 °C
- Storage area : Store in a well-ventilated place. Store away from heat.
- Special rules on packaging : Store in a closed container.
- Packaging materials : Do not store in corrodable metal.

Switzerland

- Storage class (LK) : LK 10/12 - Liquids

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Benzothiazole (95-16-9)		
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	20 mg/m³	
Acetyl Propionyl (600-14-6)		
Germany - Occupational Exposure Limits (TRGS 900)		
AGW (OEL TWA)	0.083 mg/m³	
	0.02 ppm	
Chemical category	Skin notation, Skin sensitization	
Slovenia - Occupational Exposure Limits		
OEL TWA	0.083 mg/m³	
	0.02 ppm	
OEL STEL	0.083 mg/m³	
	0.02 ppm	
OEL chemical category	Potential for cutaneous absorption	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	0.08 mg/m³	
	0.02 ppm	

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Acetyl Propionyl (600-14-6)	
KZGW (OEL STEL)	0.16 mg/m ³
	0.04 ppm
OEL chemical category	Sensitizer, Skin notation
ethanol; ethyl alcohol (64-17-5)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	1900 mg/m ³
	1000 ppm
MAK (OEL STEL)	3800 mg/m ³
	2000 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	1907 mg/m ³
	1000 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	1000 mg/m ³
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	1900 mg/m ³
	1000 ppm
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	1000 mg/m ³
Denmark - Occupational Exposure Limits	
OEL TWA	1900 mg/m ³
	1000 ppm
OEL STEL	3800 mg/m ³
	2000 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	1000 mg/m ³
	500 ppm
OEL STEL	1900 mg/m ³
	1000 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	1900 mg/m ³
	1000 ppm
HTP (OEL STEL)	2500 mg/m ³
	1300 ppm
France - Occupational Exposure Limits	
VME (OEL TWA)	1900 mg/m ³
	1000 ppm
VLE (OEL C/STEL)	9500 mg/m ³
	5000 ppm

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethanol; ethyl alcohol (64-17-5)	
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	380 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	200 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Greece - Occupational Exposure Limits	
OEL TWA	1900 mg/m ³
	1000 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	1900 mg/m ³
CK (OEL STEL)	3800 mg/m ³
Ireland - Occupational Exposure Limits	
OEL STEL	1000 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	1000 mg/m ³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	1000 mg/m ³
	500 ppm
TPRV (OEL STEL)	1900 mg/m ³
	1000 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	260 mg/m ³
	137 ppm
TGG-15min (OEL STEL)	1900 mg/m ³
	1000 ppm
MAC chemical category	Skin notation
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	1900 mg/m ³
Portugal - Occupational Exposure Limits	
OEL STEL	1000 ppm
OEL chemical category	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
Romania - Occupational Exposure Limits	
OEL TWA	1900 mg/m ³
	1000 ppm
OEL STEL	9500 mg/m ³
	5000 ppm
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	960 mg/m ³
	500 ppm
NPHV (OEL C)	1920 mg/m ³

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethanol; ethyl alcohol (64-17-5)	
Slovenia - Occupational Exposure Limits	
OEL TWA	960 mg/m ³
	500 ppm
OEL STEL	1920 mg/m ³
	1000 ppm
Spain - Occupational Exposure Limits	
VLA-EC (OEL STEL)	1910 mg/m ³
	1000 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	1000 mg/m ³
	500 ppm
KGV (OEL STEL)	1900 mg/m ³
	1000 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	1920 mg/m ³
	1000 ppm
WEL STEL (OEL STEL)	5760 mg/m ³ (calculated)
	3000 ppm (calculated)
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	950 mg/m ³
	500 ppm
Korttidsverdi (OEL STEL)	1187.5 mg/m ³ (value calculated)
	625 ppm (value calculated)
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	960 mg/m ³
	500 ppm
KZGW (OEL STEL)	1920 mg/m ³
	1000 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL STEL	1000 ppm
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
pyridine (110-86-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	15 mg/m ³ (existing scientific data on health effects appear to be particularly limited)
	5 ppm (existing scientific data on health effects appear to be particularly limited)
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	15 mg/m ³
	5 ppm
MAK (OEL STEL)	60 mg/m ³

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

pyridine (110-86-1)	
	20 ppm
OEL chemical category	Skin notation
Belgium - Occupational Exposure Limits	
OEL TWA	3.3 mg/m ³
	1 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	15 mg/m ³
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	15 mg/m ³
	5 ppm
Cyprus - Occupational Exposure Limits	
OEL TWA	15 mg/m ³
	5 ppm
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	5 mg/m ³
OEL chemical category	Potential for cutaneous absorption
Denmark - Occupational Exposure Limits	
OEL TWA	15 mg/m ³
	5 ppm
OEL STEL	30 mg/m ³
	10 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	15 mg/m ³
	5 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	3 mg/m ³
	1 ppm
HTP (OEL STEL)	16 mg/m ³
	5 ppm
OEL chemical category	Potential for cutaneous absorption
France - Occupational Exposure Limits	
VME (OEL TWA)	15 mg/m ³
	5 ppm
VLE (OEL C/STEL)	30 mg/m ³
	10 ppm
Gibraltar - Occupational Exposure Limits	
OEL TWA	15 mg/m ³ (existing scientific data on health effects appear to be particularly limited)
	5 ppm (existing scientific data on health effects appear to be particularly limited)

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

pyridine (110-86-1)	
Greece - Occupational Exposure Limits	
OEL TWA	15 mg/m³
	5 ppm
OEL STEL	30 mg/m³
	10 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	15 mg/m³
CK (OEL STEL)	30 mg/m³
OEL chemical category	Sensitizer, Potential for cutaneous absorption
Ireland - Occupational Exposure Limits	
OEL TWA	15 mg/m³
	5 ppm
OEL STEL	30 mg/m³
	10 ppm (total resin acid-airborne)
Latvia - Occupational Exposure Limits	
OEL TWA	15 mg/m³
	5 ppm
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	15 mg/m³
	5 ppm
Luxembourg - Occupational Exposure Limits	
OEL TWA	15 mg/m³
	5 ppm
Malta - Occupational Exposure Limits	
OEL TWA	15 mg/m³
	5 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	0.9 mg/m³
	0.3 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	5 mg/m³
Portugal - Occupational Exposure Limits	
OEL TWA	15 mg/m³ (indicative limit value)
	5 ppm (indicative limit value)
OEL chemical category	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
Romania - Occupational Exposure Limits	
OEL TWA	15 mg/m³
	5 ppm

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

pyridine (110-86-1)	
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	15 mg/m ³
	5 ppm
Slovenia - Occupational Exposure Limits	
OEL TWA	15 mg/m ³
	5 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	3 mg/m ³
	1 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	7 mg/m ³
	2 ppm
KGV (OEL STEL)	10 mg/m ³
	3 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	16 mg/m ³
	5 ppm
WEL STEL (OEL STEL)	33 mg/m ³
	10 ppm
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	15 mg/m ³
	5 ppm
Korttidsverdi (OEL STEL)	22.5 mg/m ³ (value calculated)
	10 ppm (value calculated)
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	15 mg/m ³
	5 ppm
KZGW (OEL STEL)	30 mg/m ³
	10 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1 ppm
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
2,6-xylenol (576-26-1)	
Latvia - Occupational Exposure Limits	
OEL TWA	2 mg/m ³
Romania - Occupational Exposure Limits	
OEL TWA	15 mg/m ³
OEL STEL	20 mg/m ³

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2,6-xylenol (576-26-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1 ppm (inhalable fraction and vapor)
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans, dermal sensitizer
Isovaleraldehyde (590-86-3)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	39 mg/m ³
	10 ppm
MAK (OEL STEL)	39 mg/m ³
	10 ppm
OEL C	39 mg/m ³
	10 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	39 mg/m ³
	10 ppm
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	10 mg/m ³
Slovenia - Occupational Exposure Limits	
OEL TWA	39 mg/m ³
	10 ppm
OEL STEL	39 mg/m ³
	10 ppm
acetaldehyde; ethanal (75-07-0)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	90 mg/m ³
	50 ppm
MAK (OEL STEL)	90 mg/m ³
	50 ppm
OEL C	90 mg/m ³
	50 ppm
OEL chemical category	Group B Carcinogen
Belgium - Occupational Exposure Limits	
OEL TWA	46 mg/m ³
	25 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	30 mg/m ³
OEL STEL	200 mg/m ³
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	37 mg/m ³

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

acetaldehyde; ethanal (75-07-0)	
	20 ppm
KGVI (OEL STEL)	92 mg/m ³
	50 ppm
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	50 mg/m ³
Denmark - Occupational Exposure Limits	
OEL C	45 mg/m ³
	25 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	45 mg/m ³
	25 ppm
OEL STEL	90 mg/m ³
	50 ppm
OEL chemical category	Carcinogenic substance
Finland - Occupational Exposure Limits	
HTP (OEL STEL)	46 mg/m ³
	25 ppm
France - Occupational Exposure Limits	
VME (OEL TWA)	180 mg/m ³
	100 ppm
OEL chemical category	Carcinogen category 1B, Mutagen category 2
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	91 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	50 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Greece - Occupational Exposure Limits	
OEL TWA	180 mg/m ³
	100 ppm
OEL STEL	270 mg/m ³
	150 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	45 mg/m ³
CK (OEL STEL)	45 mg/m ³
Ireland - Occupational Exposure Limits	
OEL STEL	45 mg/m ³
	25 ppm
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	45 mg/m ³
	25 ppm

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

acetaldehyde; ethanal (75-07-0)	
TPRV (OEL STEL)	90 mg/m ³
	50 ppm
OEL chemical category	Carcinogen
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	37 mg/m ³
	20 ppm
TGG-15min (OEL STEL)	92 mg/m ³
	50 ppm
Poland - Occupational Exposure Limits	
NDSP (OEL C)	45 mg/m ³
Portugal - Occupational Exposure Limits	
OEL C	25 ppm
OEL chemical category	A2 - Suspected Human Carcinogen
Romania - Occupational Exposure Limits	
OEL TWA	90 mg/m ³
	50 ppm
OEL STEL	180 mg/m ³
	100 ppm
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	91 mg/m ³
	50 ppm
Slovenia - Occupational Exposure Limits	
OEL TWA	91 mg/m ³
	50 ppm
OEL STEL	91 mg/m ³
	50 ppm
OEL chemical category	Category 2
Spain - Occupational Exposure Limits	
VLA-EC (OEL STEL)	46 mg/m ³
	25 ppm
OEL chemical category	C1B
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	45 mg/m ³
	25 ppm
KGV (OEL STEL)	90 mg/m ³
	50 ppm
OEL chemical category	Carcinogen
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	37 mg/m ³

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

acetaldehyde; ethanal (75-07-0)	
	20 ppm
WEL STEL (OEL STEL)	92 mg/m ³
	50 ppm
WEL chemical category	Capable of causing cancer and/or heritable genetic damage
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	45 mg/m ³
	25 ppm
Korttidsverdi (OEL STEL)	67.5 mg/m ³ (value calculated)
	37.5 ppm (value calculated)
OEL chemical category	Carcinogen
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	90 ppm
	50 ppm
KZGW (OEL STEL)	90 mg/m ³
	50 ppm
OEL chemical category	Category C2 carcinogen
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL C	25 ppm
ACGIH chemical category	Suspected Human Carcinogen

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Safety glasses

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves. Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light yellow. amber. Conforms to standard.
Odour	: characteristic. characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 93 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 0.001364217 mm Hg (calculated value)
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: ≈ 1.1
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 2.821 % (calculated value)(CARB VOC) (%w/w)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.2. Chemical stability

Stable under normal conditions. Not established.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Not established.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

ROASTED COFFEE #EU35918F

ATE CLP (oral)	623.844 mg/kg bodyweight
----------------	--------------------------

benzyl benzoate (120-51-4)

LD50 oral rat	> 2000 mg/kg (Source: ECHA_API)
LD50 oral	1160 mg/kg bodyweight
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)

Resin acids and Rosin acids, hydrogenated, methyl esters (8050-15-5)

LD50 oral rat	> 2000 mg/kg (Source: ECHA)
LD50 dermal rabbit	> 10000 mg/kg (Source: ECHA_API)

Ethyl vanillin (121-32-4)

LD50 oral rat	1590 mg/kg (Source: NLM_CIP)
LD50 oral	3000 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)

Ethyl maltol (4940-11-8)

LD50 oral rat	1150 mg/kg (Source: NLM_CIP)
LD50 oral	1200 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA_API)

1,2-Cyclopentanedione, 3-methyl- (765-70-8)

LD50 oral	1067 mg/kg bodyweight
-----------	-----------------------

Benzothiazole (95-16-9)

LD50 oral rat	380 mg/kg (Source: JAPAN_GHS)
LD50 oral	240 mg/kg bodyweight

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Benzothiazole (95-16-9)	
LD50 dermal rabbit	126 – 200 mg/kg (Source: JAPAN_GHS)
LD50 dermal	1000 mg/kg bodyweight
LC50 Inhalation - Rat	5 mg/l/4h
3(2H)-Furanone, 4-hydroxy-2,5-dimethyl- (3658-77-3)	
LD50 oral	1608 mg/kg bodyweight
Acetyl Propionyl (600-14-6)	
LD50 oral rat	3 g/kg (Source: NLM_CIP)
LD50 oral	3000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg (Source: NIOSH)
ethanol; ethyl alcohol (64-17-5)	
LD50 oral rat	7060 mg/kg (Source: NLM_CIP)
LC50 Inhalation - Rat	133.8 mg/l/4h
pyridine (110-86-1)	
LD50 oral rat	866 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	1000 – 2000 mg/kg (Source: CHEMVIEW)
LC50 Inhalation - Rat	12.898 mg/l/4h
LC50 Inhalation - Rat (Vapours)	15 mg/l
2,6-xyleneol (576-26-1)	
LD50 oral rat	296 mg/kg (Source: JAPAN_GHS)
LD50 oral	296 mg/kg bodyweight
LD50 dermal rabbit	1 g/kg (Source: NLM_CIP)
LD50 dermal	960 mg/kg bodyweight
Isovaleraldehyde (590-86-3)	
LD50 oral rat	5600 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	2730 mg/kg (Source: NLM_CIP)
LD50 dermal	2534 mg/kg
LC50 Inhalation - Rat	42.7 mg/l/4h
acetaldehyde; ethanal (75-07-0)	
LD50 oral rat	660 mg/kg (Source: JAPAN_GHS)
LD50 oral	700 mg/kg
LD50 dermal rabbit	3540 mg/kg (Source: NLM_HSDB)
LD50 dermal	3540 mg/kg
LC50 Inhalation - Rat [ppm]	13000 ppm/4h
Skin corrosion/irritation	: Not classified
pyridine (110-86-1)	
pH	8.5 (conc: 0.2 M (aqueous solution))
Serious eye damage/irritation	: Not classified

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

pyridine (110-86-1)	
pH	8.5 (conc: 0.2 M (aqueous solution))
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
pyridine (110-86-1)	
IARC group	2B - Possibly carcinogenic to humans
acetaldehyde; ethanal (75-07-0)	
IARC group	1 - Carcinogenic to humans, 2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
Isovaleraldehyde (590-86-3)	
STOT-single exposure	May cause respiratory irritation.
acetaldehyde; ethanal (75-07-0)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
TOLU BALSAM (9000-64-0)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Acetyl Propionyl (600-14-6)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
benzyl benzoate (120-51-4)	
Viscosity, kinematic	7.456 mm²/s

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects. Very toxic to aquatic life.
Hazardous to the aquatic environment, short-term (acute) : Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
NOEC (chronic)	0.168 mg/l

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ethyl vanillin (121-32-4)	
LC50 - Fish [1]	81.4 – 94.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
Ethyl maltol (4940-11-8)	
LC50 - Fish [1]	> 85 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: ECHA)
Benzothiazole (95-16-9)	
LC50 - Fish [1]	58.8 – 69.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
ethanol; ethyl alcohol (64-17-5)	
LC50 - Fish [2]	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
EC50 - Crustacea [1]	9268 – 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 - Crustacea [2]	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
pyridine (110-86-1)	
LC50 - Fish [1]	63.4 – 73.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	26 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static] Source: EPA)
2,6-xyleneol (576-26-1)	
LC50 - Fish [1]	27 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
EC50 - Crustacea [1]	11.2 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 - Crustacea [2]	11.2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
Isovaleraldehyde (590-86-3)	
LC50 - Fish [1]	2.98 – 3.54 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
EC50 - Crustacea [1]	177 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	80 mg/l (Species: Desmodesmus subspicatus)
EC50 96h - Algae [1]	78 mg/l (Species: Desmodesmus subspicatus)
acetaldehyde; ethanal (75-07-0)	
LC50 - Fish [1]	28 – 34 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	53 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
EC50 - Crustacea [1]	3.64 – 6.15 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 - Crustacea [2]	48.3 mg/l (Exposure time: 48 h - Species: Daphnia magna)
12.2. Persistence and degradability	
ROASTED COFFEE #EU35918F	
Persistence and degradability	Not established.
benzyl benzoate (120-51-4)	
Persistence and degradability	May cause long-term adverse effects in the environment.
Resin acids and Rosin acids, hydrogenated, methyl esters (8050-15-5)	
Persistence and degradability	Rapidly degradable

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ethyl vanillin (121-32-4)	
Persistence and degradability	Rapidly degradable
Ethyl maltol (4940-11-8)	
Persistence and degradability	Rapidly degradable
1,2-Cyclopentanedione, 3-methyl- (765-70-8)	
Persistence and degradability	Rapidly degradable
Benzothiazole (95-16-9)	
Persistence and degradability	Rapidly degradable
TOLU BALSAM (9000-64-0)	
Persistence and degradability	Rapidly degradable
3(2H)-Furanone, 4-hydroxy-2,5-dimethyl- (3658-77-3)	
Persistence and degradability	Rapidly degradable
Acetyl Propionyl (600-14-6)	
Persistence and degradability	Rapidly degradable
ethanol; ethyl alcohol (64-17-5)	
Persistence and degradability	Rapidly degradable
pyridine (110-86-1)	
Persistence and degradability	Rapidly degradable
2,6-xylenol (576-26-1)	
Persistence and degradability	Rapidly degradable
Isovaleraldehyde (590-86-3)	
Persistence and degradability	Rapidly degradable
acetaldehyde; ethanal (75-07-0)	
Persistence and degradability	Rapidly degradable
12.3. Bioaccumulative potential	
ROASTED COFFEE #EU35918F	
Bioaccumulative potential	Not established.
benzyl benzoate (120-51-4)	
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)
Bioaccumulative potential	Not established.
Resin acids and Rosin acids, hydrogenated, methyl esters (8050-15-5)	
Partition coefficient n-octanol/water (Log Pow)	6.4 – 7.6 (at pH 6)
Ethyl vanillin (121-32-4)	
Partition coefficient n-octanol/water (Log Pow)	1.61 (at 25 °C)
Ethyl maltol (4940-11-8)	
Partition coefficient n-octanol/water (Log Pow)	2.9 (at 25 °C)

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Benzothiazole (95-16-9)	
BCF - Fish [1]	2.1 – 7.5
Partition coefficient n-octanol/water (Log Pow)	2.01
3(2H)-Furanone, 4-hydroxy-2,5-dimethyl- (3658-77-3)	
Partition coefficient n-octanol/water (Log Pow)	0.95 (at 20 °C (at pH 2.5)
ethanol; ethyl alcohol (64-17-5)	
Partition coefficient n-octanol/water (Log Pow)	-0.35 (at 24 °C (at pH 7.4)
pyridine (110-86-1)	
Partition coefficient n-octanol/water (Log Pow)	0.65
2,6-xyleneol (576-26-1)	
Partition coefficient n-octanol/water (Log Pow)	2.36
Isovaleraldehyde (590-86-3)	
Partition coefficient n-octanol/water (Log Pow)	1.5 (at 25 °C (at pH 7)
acetaldehyde; ethanal (75-07-0)	
Partition coefficient n-octanol/water (Log Pow)	0.45 – 0.63 (at 25 °C (at pH 7)

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecological information	: Avoid release to the environment.
HP Code	: HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure. HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment


SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	Environmentally hazardous substance, liquid, n.o.s. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)
Transport document description				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Benzyl Benzoate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Orange plates	:	90 3082
Tunnel restriction code (ADR)	:	-
EAC code	:	•3Z

Transport by sea

Special provisions (IMDG)	:	274, 335, 969
Limited quantities (IMDG)	:	5 L
Excepted quantities (IMDG)	:	E1
Packing instructions (IMDG)	:	LP01, P001
Special packing provisions (IMDG)	:	PP1
IBC packing instructions (IMDG)	:	IBC03
Tank instructions (IMDG)	:	T4
Tank special provisions (IMDG)	:	TP1, TP29
EmS-No. (Fire)	:	F-A
EmS-No. (Spillage)	:	S-F
Stowage category (IMDG)	:	A

Air transport

PCA Excepted quantities (IATA)	:	E1
PCA Limited quantities (IATA)	:	Y964
PCA limited quantity max net quantity (IATA)	:	30kgG
PCA packing instructions (IATA)	:	964
PCA max net quantity (IATA)	:	450L
CAO packing instructions (IATA)	:	964
CAO max net quantity (IATA)	:	450L
Special provisions (IATA)	:	A97, A158, A197, A215
ERG code (IATA)	:	9L

Inland waterway transport

Classification code (ADN)	:	M6
Special provisions (ADN)	:	274, 335, 375, 601
Limited quantities (ADN)	:	5 L
Excepted quantities (ADN)	:	E1
Equipment required (ADN)	:	PP
Number of blue cones/lights (ADN)	:	0

Rail transport

Classification code (RID)	:	M6
Special provisions (RID)	:	274, 335, 375, 601
Limited quantities (RID)	:	5L
Excepted quantities (RID)	:	E1
Packing instructions (RID)	:	P001, IBC03, LP01, R001
Special packing provisions (RID)	:	PP1
Mixed packing provisions (RID)	:	MP19
Portable tank and bulk container instructions (RID)	:	T4
Portable tank and bulk container special provisions (RID)	:	TP1, TP29
Tank codes for RID tanks (RID)	:	LGBV
Transport category (RID)	:	3
Special provisions for carriage – Packages (RID)	:	W12
Special provisions for carriage - Loading, unloading and handling (RID)	:	CW13, CW31
Colis express (express parcels) (RID)	:	CE8
Hazard identification number (RID)	:	90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
28.	acetaldehyde; ethanal	Substances which are classified as carcinogen category 1A or 1B in Part 3 of Annex VI to Regulation (EC) No 1272/2008 and are listed in Appendix 1 or Appendix 2, respectively.
3(a)	Acetyl Propionyl ; ethanol; ethyl alcohol ; pyridine ; Isovaleraldehyde ; acetaldehyde; ethanal	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	ROASTED COFFEE #EU35918F ; benzyl benzoate ; Benzothiazole ; TOLU BALSAM ; 3(2H)- Furanone, 4-hydroxy-2,5- dimethyl- ; Acetyl Propionyl ; pyridine ; Isovaleraldehyde ; acetaldehyde; ethanal	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	ROASTED COFFEE #EU35918F ; benzyl benzoate ; Resin acids and Rosin acids, hydrogenated, methyl esters ; TOLU BALSAM ; Isovaleraldehyde	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	Acetyl Propionyl ; ethanol; ethyl alcohol ; pyridine ; Isovaleraldehyde ; acetaldehyde; ethanal	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 2.821 % (calculated value)(CARB VOC) (%w/w)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions	: Observe restrictions according Act on the Protection of Working Mothers (MuSchG). Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
Water hazard class (WGK)	: WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
Major Accidents Ordinance (12. BImSchV)	: Is not subject to the Major Accidents Ordinance (12. BImSchV)

Netherlands

ABM category	: A(1) - highly toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment
SZW-lijst van kankerverwekkende stoffen	: Resin acids and Rosin acids, hydrogenated, methyl esters, Ethyl alcohol, Acetaldehyde are listed
SZW-lijst van mutagene stoffen	: Resin acids and Rosin acids, hydrogenated, methyl esters is listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: Ethyl alcohol is listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: Ethyl alcohol is listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: Ethyl alcohol is listed

Denmark

Classification remarks	: Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 2 (Dermal)	Acute toxicity (dermal), Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Carc. 1B	Carcinogenicity, Category 1B
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 1	Flammable liquids, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Muta. 2	Germ cell mutagenicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

ROASTED COFFEE #EU35918F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.